



Tire Direct
La nueva generación



TIRE DIRECT



/TIRE_DIRECT



/TIREDIRECTMX



TIRE DIRECT



PCR TIRE

TBR TIRE

Tire Direct
La nueva generación



BRAND VALUE

Linglong has sponsored over 90 sports events and teams worldwide, such as Juventus and VfL Wolfsburg, to enhance its brand awareness and influence. It strengthens the retail network construction, with nearly 100,000 marketing outlets globally, promoting its brand reputation and customer loyalty through reliable product quality and excellent service. To attracting more target consumers, the company launches at airports and high-speed rail stations in major cities across the world and several CCTV programs. For many years, Linglong has been participating SEMA show and Automechanika Dubai etc. to enhance its product reputation and build the international brand image. Linglong's brand value reached 59.672 Billion RMB in 2021.

The company's products are exported to 173 countries across the world, covering Europe, Middle East, Americas, Asia Pacific, and Africa, and provides OE service for over 100 manufacturing bases of 60 global well-known automakers. Seven of Top 10 global automakers would like to choose Linglong Tire.

CONTENTS

PCR TIRE

PASSENGER CAR TIRE	01
SPORT UTILITY VEHICLE TIRE	15
LIGHT TRUCK TIRE	28
WINTER TIRE	31

TBR TIRE

LONG HAUL	39
REGIONAL	45
ON&OFF ROAD	60
OFF ROAD	67
LIGHT TRUCK	71
COACH&URBAN	79

PCR TIRE



PASSENGER CAR TIRE

AM520	PAGE 02	FORCE HP	PAGE 09
AM520 LRS	PAGE 03	SPORT GREEN	PAGE 11
AC300	PAGE 04	GREEN	PAGE 12
AS350	PAGE 04	GREEN2 4S	PAGE 14
AE130	PAGE 05		
FORCE UHP	PAGE 06		

SPORT UTILITY VEHICLE TIRE

A2	PAGE 16	SPORT GREEN SUV	PAGE 21
X7 LRS	PAGE 17	PARALLER 4X4 HP	PAGE 22
A50	PAGE 18	PARALLER H/T	PAGE 23
A51	PAGE 19	PARALLER A/T	PAGE 24
HT601	PAGE 20	SHARP	PAGE 25
AT760	PAGE 20	PARALLER M/T	PAGE 26

LIGHT TRUCK TIRE

GREEN VAN	PAGE 28	AR939	PAGE 30
R772	PAGE 30		

WINTER TIRE

I3	PAGE 32	POLARBEAR 2	PAGE 36
I5	PAGE 33	POLARBEAR SUV	PAGE 37
AW31	PAGE 34	POLARBEAR VAN	PAGE 38
POLARBEAR 1	PAGE 35		



PASSENGER CAR TIRE



High handling performance

AM520

- ◀ Open shoulder groove design to lower noise.
- ◀ 4 longitudinal groove design for superior driving stability and comfortable ride.

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
16	205/55R16	91	W	6 1/2J	615	300
	215/55R16 XL	97	W	7J	730	340
	225/55R16 XL	99	W	7J	775	340
	205/50R17 XL	93	W	6 1/2J	650	340
	215/45R17 XL	91	W	7J	615	340
17	215/50R17 XL	95	W	7J	690	340
	215/55R17	94	W	7J	670	300
	225/45R17 XL	94	W	7 1/2J	670	340
	225/50R17 XL	98	W	7J	750	340
	225/55R17 XL	101	W	7J	825	340
	235/45R17 XL	97	W	8J	730	340
	235/50R17	96	W	7 1/2J	710	300
	245/45R17 XL	99	W	8J	775	340
18	255/45R17	98	W	8 1/2J	750	300
	225/40R18 XL	92	W	8J	630	340
	225/45R18 XL	95	W	7 1/2J	690	340
	235/45R18 XL	98	W	8J	750	340
	245/40R18 XL	97	W	8 1/2J	730	340
	245/45R18 XL	100	W	8J	800	340
	245/50R18 XL	104	W	7 1/2J	900	340
19	255/45R18 XL	103	W	8 1/2J	875	340
	225/45R19 XL	96	W	7 1/2J	710	340
	245/45R19 XL	102	Y	8J	850	340

MADE IN CHINA



Super ability LRS tire dedicated
for luxury brand Car

AM520 LRS

- ◀ Open shoulder groove design to lower noise.
- ◀ Asymmetric tread pattern design for better handling performance and fashionable appearance.
- ◀ LRS technology used for driving the vehicle's safety.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
16	195/55R16	87	V	6J	545	300
	205/55R16	91	V	6 1/2J	615	300
	225/55R16	95	W	7J	690	300
	205/50R17	89	W	6 1/2J	580	300
17	205/55R17	91	W	6 1/2J	615	300
	225/45R17	91	W	7 1/2J	600	300
	225/50R17	94	W	7J	670	300
	225/55R17	97	W	7J	730	300
18	225/40R18	88	W	8J	560	300
	225/45R18	91	W	7 1/2J	615	300
	245/45R18	96	W	8J	710	300
	245/50R18	100	W	7 1/2J	800	300
19	255/35R18	90	Y	9J	600	300
	255/40R18	95	W	9J	690	300
	275/40R18	99	Y	9 1/2J	775	300
	225/40R19	89	Y	8J	580	300
20	245/40R19 XL	98	Y	8 1/2J	750	340
	245/45R19	98	Y	8J	750	300
	255/35R19	92	Y	9J	630	300
	275/35R19	96	Y	9 1/2J	710	300
21	275/40R19	101	Y	9 1/2J	825	300
	245/40R20 XL	99	Y	8 1/2J	775	340
	275/35R20 XL	102	Y	9 1/2J	850	340
	275/40R20 XL	106	Y	9 1/2J	950	340
22	315/35R20 XL	110	Y	11J	1060	340

MADE IN CHINA



Low-noise comfort tire

AC300

- ◀ Multi-band pattern design—Effectively suppress noise generation.
- ◀ Four main groove designs—Accelerate the drainage speed and improve the safety of driving on rainy days.
- ◀ Closure design of fetal shoulder pattern—Effectively block the noise in the center of the tread, bringing a quieter driving experience.
- ◀ Use finite element analysis tools to optimize the outline and tire structure design.—Improve comfort.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
17	205/55R17 XL	95	W	6 1/2J	690	340
	215/45R17 XL	91	V	7J	615	340
	215/50R17 XL	95	V	7J	690	340
	215/55R17	94	V	7J	670	300
	225/45R17 XL	94	V	7 1/2J	670	340
	225/50R17 XL	98	V	7J	750	340
	225/55R17 XL	101	V	7J	825	340
	235/45R17 XL	97	V	8J	730	340
	235/50R17	96	V	7 1/2J	710	300
	245/45R17 XL	99	V	8J	775	340
18	255/45R17	98	V	8 1/2J	750	300
	225/45R18 XL	95	V	7 1/2J	690	340
	235/45R18	94	V	8J	670	300
	245/45R18 XL	100	V	8J	800	340

MADE IN CHINA



All-season Tire

AS350

- ◀ Open shoulder groove design for superior safety and quiet ride.
- ◀ Straight center pattern blocks for more comfortable ride.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	175/65R15	84	H	5J	500	300
16	195/50R16 XL	88	V	6J	560	340
	195/55R16	87	V	6J	545	300

Three Grooves

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	185/55R15	82	V	6J	475	300
	185/60R15	84	H	5 1/2J	500	300
	185/65R15	88	H	5 1/2J	560	300
	195/55R15	85	V	6J	515	300
	195/60R15	88	V	6J	560	300
	195/65R15	91	V	6J	615	300
	205/65R15	94	V	6J	670	300
	205/70R15	96	H	6J	710	300
	215/70R15	98	S	6 1/2J	750	300
	195/60R16	89	H	6J	580	300
16	205/50R16 XL	91	V	6 1/2J	615	340
	205/55R16	91	V	6 1/2J	615	300
	205/60R16	92	V	6J	630	300
	215/55R16	93	V	7J	650	300
	215/60R16	95	H	6 1/2J	690	300
	225/60R16	98	H	6 1/2J	750	300

MADE IN CHINA

Four Grooves



Economy and Long-mileage Tire

AE130

- ▶ Wider tread design--increase the tire wear performance.
- ▶ Three main groove design--Meet the drainage requirements of wet grip road.
- ▶ Big shoulder pattern block--improve abrasability and grip performance.

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
14	175/65R14	82	H	5J	475	300
	175/70R14	84	H	5J	500	300
	185/65R14	86	H	5 1/2J	530	300
	185/70R14	88	H	5 1/2J	560	300
	185/60R15	84	H	5 1/2J	500	300
	185/65R15	88	H	5 1/2J	560	300
15	195/55R15 XL	89	H	6J	580	340
	195/60R15	88	H	6J	560	300
	195/65R15	91	H	6J	615	300
	205/65R15	94	H	6J	670	300
	205/70R15	96	H	6J	800	300
	215/65R15 XL	100	H	6 1/2J	800	340
16	195/55R16 XL	91	H	6J	615	340

MADE IN CHINA



High handling performance UHP tire

FORCE UHP

- ▶ Excellent dry and wet handling performance.
- ▶ Asymmetric tread pattern design for better drainage performance inside and grip performance outside, excellent steering performance.
- ▶ Wide tread surface for superior comfortable ride.

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
16	195/45R16 XL	84	V	6 1/2J	500	340
	205/50R16	87	W	6 1/2J	545	300
	205/55R16	91	W	6 1/2J	615	300
	215/50R16 XL	94	W	7J	670	340
	215/55R16 XL	97	W	7J	730	340
	225/50R16	92	W	7J	630	300
	225/55R16	95	W	7J	690	300
	195/40R17 XL	81	V	7J	462	340
	195/45R17 XL	85	W	6 1/2J	515	340
	205/40R17 XL	84	W	7 1/2J	500	340
17	205/45R17 XL	88	W	7J	560	340
	205/50R17 XL	93	W	6 1/2J	650	340
	215/45R17 XL	91	W	7J	615	340
	215/50R17 XL	95	W	7J	690	340
	215/55R17	94	W	7J	670	300
	225/45R17 XL	94	W	7 1/2J	670	340
	225/50R17 XL	98	W	7J	750	340
	225/55R17	97	W	7J	730	300
	235/45R17 XL	97	W	8J	730	340
	235/50R17	96	W	7 1/2J	710	300
18	235/55R17	99	W	7 1/2J	775	300
	245/40R17	91	W	8 1/2J	615	300
	245/45R17 XL	99	W	8J	775	340
	245/65R17 XL	111	H	7J	1090	340
	255/40R17	98	W	9J	750	340
	275/40R17	98	W	9 1/2J	750	300
	195/35R18 XL	79	W	7J	437	340
	205/35R18 XL	81	W	7 1/2J	462	340
	205/40R18 XL	86	W	7 1/2J	530	340
	215/35R18 XL	84	W	7 1/2J	500	340
18	215/40R18 XL	89	Y	7 1/2J	580	340
	215/45R18 XL	93	Y	7J	650	340
	225/35R18 XL	87	W	8J	545	340
	225/40R18 XL	92	Y	8J	630	340
	225/45R18 XL	95	Y	7 1/2J	690	340
	225/50R18	95	W	7J	690	300
	235/40R18 XL	95	Y	8 1/2J	690	340
	235/45R18 XL	98	Y	8J	750	340
	235/50R18	97	Y	7 1/2J	730	300
	245/40R18 XL	97	Y	8 1/2J	730	340
18	245/45R18 XL	100	Y	8J	800	340
	245/50R18	100	Y	7 1/2J	800	300

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure
					kg	kPa	
18	255/35R18 XL	94	Y	9J	670	340	
	255/40R18 XL	99	Y	9J	775	340	
	255/45R18 XL	103	W	8 1/2J	875	340	
	255/55R18 XL	109	W	8J	1030	340	
	265/35R18 XL	97	W	9 1/2J	730	340	
	265/40R18 XL	101	Y	9 1/2J	825	340	
	275/35R18	95	Y	9 1/2J	690	300	
	275/40R18 XL	103	Y	9 1/2J	875	340	
	305/30R18	97	W	11J	730	300	
	215/35R19 XL	85	V	7 1/2J	515	340	
19	225/35R19 XL	88	W	8J	560	340	
	225/40R19 XL	93	Y	8J	650	340	
	225/45R19 XL	96	Y	7 1/2J	710	340	
	235/35R19 XL	91	Y	8 1/2J	615	340	
	235/40R19 XL	96	Y	8 1/2J	710	340	
	235/55R19 XL	105	Y	7 1/2J	925	340	
	245/35R19 XL	93	W	8 1/2J	650	340	
	245/40R19 XL	98	Y	8 1/2J	750	340	
	245/45R19 XL	102	W	8J	850	340	
	245/50R19 XL	105	W	7 1/2J	925	340	
	245/55R19	103	V	7 1/2J	875	300	
	255/35R19 XL	96	Y	9J	710	340	
	255/40R19 XL	100	Y	9J	800	340	
	255/45R19 XL	104	Y	8 1/2J	900	340	
	255/50R19 XL	107	Y	8J	975	340	
	255/60R19	109	H	7 1/2J	1030	300	
	265/30R19 XL	93	W	9 1/2J	650	340	
	265/35R19 XL	98	Y	9 1/2J	750	340	
	265/40R19 XL	102	Y	9 1/2J	850	340	
	265/50R19 XL	110	W	8 1/2J	1060	340	
20	275/30R19 XL	96	W	9 1/2J	710	340	
	275/35R19 XL	100	Y	9 1/2J	800	340	
	275/40R19 XL	105	Y	9 1/2J	925	340	
	275/45R19 XL	108	W	9J	1000	340	
	275/55R19	111	Y	8 1/2J	1090	300	
	285/35R19 XL	103	Y	10J	875	340	
	285/45R19 XL	111	Y	9 1/2J	1090	340	
	295/30R19 XL	100	W	10 1/2J	800	340	
	215/30R20 XL	82	W	7 1/2J	475	340	
	225/30R20 XL	85	W	8J	515	340	
	225/35R20 XL	90	W	8J	600	340	
	235/30R20 XL	88	W	8 1/2J	560	340	
	235/35R20 XL	92	W	8 1/2J	630	340	
	245/30R20 XL	90	W	8 1/2J	600	340	
	245/35R20 XL	95	W	8 1/2J	690	340	
	245/40R20 XL	99	Y	8 1/2J	775	340	
	245/45R20 XL	103	Y	8J	875	340	
	245/50R20 XL	102	V	7 1/2J	850	300	
	255/30R20 XL	92	W	9J	630	340	
	255/35R20 XL	97	Y	9J	730	340	
21	255/40R20 XL	101	W	9J	825	340	
	255/45R20 XL	105	Y	8 1/2J	925	340	
	255/50R20 XL	109	Y	8J	1030	340	
	265/35R20 XL	99	Y	9 1/2J	775	340	
	265/45R20 XL	108	Y	9J	1000	340	
	265/50R20 XL	111	V	8 1/2J	1090	340	
	275/30R20 XL	97	Y	9 1/2J	730	340	
	275/35R20 XL	102	Y	9 1/2J	850	340	
	275/40R20 XL	106	Y	9 1/2J	950	340	
	275/45R20 XL	110	W	9J	1060	340	
22	285/25R20 XL	93	W	10 1/2J	650	340	
	285/30R20 XL	97	W	10 1/2J	750	340	
	285/35R20 XL	101	W	10 1/2J	850	340	
	285/40R20 XL	105	W	10 1/2J	950	340	
	285/45R20 XL	109	W	10 1/2J	1050	340	
	295/30R20 XL	100	W	10 1/2J	800	340	
	295/35R20 XL	104	W	10 1/2J	900	340	
	295/40R20 XL	108	W	10 1/2J	1000	340	
	295/45R20 XL	112	V	11J	1120	340	
	295/50R20 XL	116	V	11J	1240	340	
24	245/30R24 XL	94	W	8 1/2J	670	340	
	255/30R24 XL	97	W	9J	730	340	
	265/30R24 XL	101	W	10J	830	340	
	275/30R24 XL	105	W	10J	930	340	
	285/30R24 XL	109	W	10J	1030	340	
	295/30R24 XL	113	V	11J	1180	340	
	305/30R24 XL	118	V	10J	1320	340	
	245/35R24 XL	97	W	9J	730	340	
	255/35R24 XL	101	W	10J	830	340	
	265/35R24 XL	105	W	10J	930	340	
26	275/35R24 XL	109	W	10J	1030	340	
	285/35R24 XL	113	V	11J	1180	340	
	295/35R24 XL	117	V	11J	1300	340	
	305/35R24 XL	122	V	12J	1450	340	
	255/30R26 XL	99	W	9J	775	340	
	275/30R26 XL	103	W	10J	875	340	
	295/30R26 XL	107	W	10 1/2J	975	340	
	305/30R26 XL	109	W	11J	1030	340	
	275/25R28 XL	99	W	10J	775	340	
	295/25R28 XL	103	V	10 1/2J	875	340	
30	275/25R30 XL	101	W	10J	825	340	

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure
					kg	kPa	
20	285/50R20	112	V	9J	1120	300	
	295/25R20 XL	95	Y	10 1/2J	690	340	
	305/25R20 XL	97	Y	11J	730	340	
	315/35R20 XL	110	W	11J	1060	340	
	235/35R21	89	W	8 1/2J	580	300	
	245/30R21 XL	91	W	8 1/2J	615	340	
	245/35R21 XL	96	W	8 1/2J	710	340	
	255/30R21 XL	93	W	9J	650	340	
	265/40R21 XL	105	V	9 1/2J	925	340	
	275/35R21	99	W	9 1/2J	775	300	
21	285/30R21 XL	100	Y	10J	800	340	
	295/35R21 XL	107	Y	10 1/2J	975	340	
	235/30R22 XL	90	W	8 1/2J	600	340	
	245/30R22 XL	92	W	8 1/2J	630	340	
	255/30R22 XL	95	W	9J	690	340	
	265/30R22 XL	97	W	9 1/2J	730	340	
	265/35R22 XL	102	V	9 1/2J	850	340	
	265/40R22 XL	106	V	9 1/2J	950	340	
	285/25R22 XL	95	Y	10 1/2J	690	340	
	285/35R22 XL	106	W	10J	950	340	
22	285/40R22 XL	110	V	10J	1060	340	
	285/45R22 XL	114	V	9 1/2J	1180	340	
	295/25R22 XL	97	W	10 1/2J	730	340	
	295/30R22 XL	103	V	10 1/2J	875	340	
	305/25R22 XL	99	Y	11J	775	340	
	305/40R22 XL	114	V	11J	1180	340	
	305/45R22 XL	118	V	10J	1320	340	
	245/30R24 XL	94	W	8 1/2J	670	340	
	255/30R24 XL	97	W	9J	730	340	
	265/30R24 XL	101	W	10J	830	340	
24	275/30R24 XL	105	W	10J	930	340	
	295/30R24 XL	109	W	10 1/2J	1030	340	
	305/30R24 XL	113	V	11J	1180	340	
	255/35R26 XL	99	W	9J	775	340	
	275/35R26 XL	103	W	10J	875	340	
	295/35R26 XL	107	W	10 1/2J	975	340	
	305/35R26 XL	111	V	11J	1120	340	
	255/30R28 XL	99	W	9J	775	340	
	275/30R28 XL	103	W	10J	875	340	
	295/30R28 XL	107	W	10 1/2J	975	340	
28	275/25R28 XL	99	W	10J	775	340	
	295/25R28 XL	103	V	10 1/2J	875	340	
	305/25R28 XL	107	W	10 1/2J	975	340	
	315/25R28 XL	111	V	11J	1120	340	
	255/30R30 XL	99	W	9J	775	340	
	275/30R30 XL	103	W	10J	875	340	
	295/30R30 XL	107	W	10 1/2J	975	340	
	305/30R30 XL	111	V	11J	1120	340	
	255/35R30 XL	103	W	10J	925	340	
	275/35R30 XL	107	W	10 1/2J	1025	340	

MADE IN THAILAND



All-season Tire

FORCE HP

◀ Open shoulder groove design for superior safety and quiet ride.

◀ Straight center pattern blocks for more comfortable ride.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
13	175/70R13 WR	82	H	5.00B	475	300
	185/60R13 WR	80	H	5 1/2J	450	300
14	175/65R14	82	H	5J	475	300
	185/60R14	82	H	5 1/2J	475	300
	185/65R14	86	H	5 1/2J	530	300
	175/65R15	84	H	5J	500	300
15	185/55R15	82	V	6J	475	300
	185/60R15	84	H	5 1/2J	500	300
	185/65R15	88	H	5 1/2J	560	300
	195/50R15	82	H	6J	475	300
	195/55R15	85	V	6J	515	300
	195/60R15	88	H	6J	560	300
	195/65R15	91	H	6J	615	300
	195/50R16	84	V	6J	500	300
16	195/55R16	87	V	6J	545	300

Three Grooves

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	205/60R15	91	H	6J	615	300
	205/65R15	94	H	6J	670	300
	215/60R15	94	H	6 1/2J	670	300
	235/75R15	105	S	6 1/2J	925	300
	205/50R16	87	V	6 1/2J	545	300
	205/55R16	91	V	6 1/2J	615	300
	205/60R16	92	V	6J	630	300
	205/65R16	95	H	6J	690	300
	215/55R16 XL	97	H	7J	730	340
	215/60R16	95	V	6 1/2J	690	300
16	215/65R16	98	H	6 1/2J	750	300
	225/55R16	95	V	7J	690	300
	225/60R16	98	H	6 1/2J	750	300
	225/65R16	100	H	6 1/2J	800	300
	225/70R16 XL	107	H	6 1/2J	975	340
	235/60R16	100	H	7J	800	300
	235/65R16	103	H	7J	875	300
	205/50R17 XL	93	V	6 1/2J	650	340
	215/45R17 XL	91	V	7J	615	340
	215/50R17 XL	95	V	7J	690	340
17	215/55R17	94	V	7J	670	300
	215/60R17	96	H	6 1/2J	710	300
	215/65R17	99	H	6 1/2J	775	300
	225/45R17 XL	94	V	7 1/2J	670	340
	225/50R17 XL	98	V	7J	750	340
	225/55R17	97	V	7J	730	300
	225/60R17	99	H	6 1/2J	775	300
	225/65R17	102	H	6 1/2J	850	300
	235/45R17 XL	97	V	8J	730	340
	235/55R17	99	V	7 1/2J	775	300
	235/60R17	102	H	7J	850	300
	235/65R17	104	H	7J	900	300
	245/45R17 XL	99	V	8J	775	340
	245/50R17	99	V	7 1/2J	775	300
	225/40R18 XL	92	V	8J	630	340
18	225/45R18 XL	95	V	7 1/2J	690	340
	225/50R18 XL	99	V	7J	775	340
	225/55R18	98	V	7J	750	300
	225/60R18	100	H	6 1/2J	800	300
	235/40R18 XL	95	V	8 1/2J	690	340
	235/45R18	94	V	8J	670	300
	235/50R18	97	V	7 1/2J	730	300
	235/55R18	100	V	7 1/2J	800	300
	235/60R18	103	V	7J	875	300
	245/40R18 XL	97	V	8 1/2J	730	340
19	245/45R18 XL	100	V	8J	800	340
	235/55R19	101	V	7 1/2J	825	300
	245/40R19 XL	98	V	8 1/2J	750	340
	255/50R19 XL	107	V	8J	975	340
20	245/45R20	99	V	8J	775	300
	245/50R20	102	V	7 1/2J	850	300

MADE IN THAILAND

Four Grooves



High handling performance

SPORT GREEN

- ◀ Superior grip and handling performance.
- ◀ Excellent stability.



Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
195/45R15	78	V	6 1/2J	425	300
195/50R15	82	H	6J	475	300
195/50R15	82	V	6J	475	300
185/50R16	81	V	6J	462	300
185/55R16 XL	87	V	6J	545	340
195/45R16 XL	84	V	6 1/2J	500	340
195/50R16	84	V	6J	500	300
205/45R16	83	W	7J	487	300
205/50R16	87	V	6 1/2J	545	300
205/50R16	87	W	6 1/2J	545	300
205/55R16	91	W	6 1/2J	615	300
215/55R16 XL	97	W	7J	730	340
215/55R16 XL	97	V	7J	730	340
225/50R16	92	V	7J	630	300
225/55R16	95	V	7J	690	300
225/55R16 XL	99	W	7J	775	340
205/45R17 XL	88	W	7J	560	340
205/50R17 XL	93	W	6 1/2J	650	340
215/40R17 XL	87	W	7 1/2J	545	340
215/45R17 XL	91	W	7J	615	340
215/50R17 XL	95	W	7J	690	340
215/55R17	94	W	7J	670	300
225/45R17 XL	94	W	7 1/2J	670	340
225/50R17 XL	98	W	7J	750	340
225/55R17 XL	101	W	7J	825	340
235/45R17 XL	97	W	8J	730	340
235/55R17 XL	103	W	7 1/2J	875	340
245/40ZR17	91	W	8 1/2J	615	300
245/45R17 XL	99	W	8J	775	340
255/40ZR17	94	W	9J	670	300
215/35ZR18 XL	84	W	7 1/2J	500	340
215/40R18 XL	89	W	7 1/2J	580	340
215/45R18 XL	93	W	7J	650	340
225/40R18 XL	92	W	8J	630	340
225/45R18 XL	95	W	7 1/2J	690	340
235/40R18 XL	95	W	8 1/2J	690	340
235/50R18 XL	101	Y	7 1/2J	825	340
245/40R18 XL	97	W	8 1/2J	730	340
245/45R18 XL	100	W	8J	800	340
255/45R18 XL	103	W	8 1/2J	875	340
225/35ZR19 XL	88	W	8J	560	340
225/40R19 XL	93	W	8J	650	340



Low fuel consumption

GREEN

- ◀ Good straight driving stability.
- ◀ More comfortable and quiet ride.
- ◀ Low rolling resistance for better fuel efficiency.
- ◀ Excellent wet grip to effectively reduce risk of hydroplaning.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
13	135/80R13	70	T	3 1/2J	335	300
	145/70R13	71	T	4 1/2J	345	300
	145/80R13	75	T	4J	387	300
	155/70R13	75	T	4 1/2J	387	300
	155/80R13	79	T	4 1/2J	437	300
	155/65R13	73	T	4 1/2J	365	300
	165/55R13	77	T	5J	412	300
	165/70R13	79	T	5J	437	300
	165/80R13	83	T	4 1/2J	487	300
	175/65R13	80	T	5J	450	300
	175/70R13	82	T	5J	475	300
	185/70R13	86	T	5 1/2J	530	300
14	155/65R14	75	T	4 1/2J	387	300
	165/60R14	75	H	5J	387	300
	165/65R14	79	T	5J	437	300
	165/70R14	81	T	5J	462	300
	165/70R14 XL	85	T	5J	515	340
	175/60R14	79	H	5J	437	300
	175/65R14	82	T	5J	475	300
	175/65R14	82	H	5J	475	300
	175/65R14 XL	86	T	5J	530	340
	175/70R14	84	T	5J	500	300
	175/70R14 XL	88	T	5J	560	340
	175/80R14	88	T	5J	560	340

MADE IN CHINA & THAILAND

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
14	185/55R14	80	H	6J	450	300
	185/60R14	82	H	5 1/2J	475	300
	185/65R14	86	T	5 1/2J	530	300
	185/65R14	86	H	5 1/2J	530	300
	185/70R14	88	T	5 1/2J	560	300
	185/70R14	88	H	5 1/2J	560	300
	195/60R14	86	H	6J	530	300
	195/65R14	89	H	6J	580	300
	195/70R14	91	T	6J	615	300
	195/70R14	91	H	6J	615	300
	175/60R15	81	V	5J	462	300
	175/65R15	84	T	5J	462	300
	175/65R15	84	H	5J	500	300
	185/55R15	82	H	6J	475	300
	185/55R15	82	V	6J	475	300
	185/60R15	84	H	5 1/2J	500	300
	185/60R15 XL	88	H	5 1/2J	560	340
	185/65R15	88	T	5 1/2J	560	300
	185/65R15	88	H	5 1/2J	560	300
	185/65R15 XL	92	T	5 1/2J	630	340
15	195/50R15	82	H	6J	475	300
	195/50R15	82	V	6J	475	300
	195/55R15	85	H	6J	515	300
	195/55R15	85	V	6J	515	300
	195/60R15	88	H	6J	560	300
	195/60R15	88	V	6J	560	300
	195/65R15	91	H	6J	615	300
	195/65R15	91	T	6J	615	300
	195/65R15	91	V	6J	615	300
	195/65R15 XL	95	T	6J	690	340
	195/70R15 XL	97	T	6J	730	340
	205/55R15	88	V	6 1/2J	560	300
	205/60R15	91	H	6J	615	300
	205/60R15	91	V	6J	615	300
	205/65R15	94	H	6J	670	300
	205/65R15	94	V	6J	670	300
	205/70R15	96	H	6J	710	300
	215/65R15 XL	100	H	6 1/2J	800	340
	225/60R15	96	V	6 1/2J	710	300
16	195/50R16	84	V	6J	500	300
	195/50R16 XL	88	V	6J	560	340
	195/55R16	87	H	6J	545	300
	195/55R16	87	V	6J	545	300
	205/55R16	91	H	6 1/2J	615	300
	205/55R16	91	V	6 1/2J	615	300
	205/55R16 XL	94	V	6 1/2J	670	340
	205/60R16	92	H	6J	630	300
	205/60R16	92	V	6J	630	300
	215/60R16 XL	99	V	6 1/2J	775	340
17	215/65R16	98	H	6 1/2J	750	300
	225/60R16 XL	102	V	6 1/2J	850	340
	205/40R17 XL	84	W	7 1/2J	500	340



All Season High Performance

GREEN2 4S

- ◀ Excellent handling.
- ◀ Low rolling resistance for better fuel efficiency.
- ◀ All season tire which is applicable to different weather and road conditions.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
155/65R13	73	T	4.50B	365	300
155/80R13	79	T	4.50B	437	300
165/70R14	81	T	5J	462	300
175/65R14	82	T	5J	475	300
175/65R15	84	H	5J	500	300
185/55R15 XL	86	H	6J	530	340
185/60R14 XL	86	H	5 1/2J	530	340
185/60R15 XL	88	H	5 1/2J	560	340
185/65R14	86	H	5 1/2J	530	300
185/65R15 XL	92	V	5 1/2J	630	340
195/55R15 XL	89	V	6J	580	340
195/55R16 XL	91	H	6J	615	340
195/60R15 XL	92	V	6J	630	340
195/65R15 XL	95	V	6J	690	340
205/50R17 XL	93	V	6 1/2J	650	340
205/55R16 XL	94	V	6 1/2J	670	340
205/60R16 XL	96	V	6J	710	340
205/65R15 XL	99	V	6J	775	340
215/50R17 XL	95	V	7J	690	340
215/55R16 XL	97	V	7J	730	340
215/55R17 XL	98	V	7J	750	340
215/60R16 XL	99	V	6 1/2J	775	340
215/60R17 XL	100	V	6 1/2J	800	340
215/65R16 XL	102	V	6 1/2J	850	340
225/50R17 XL	98	V	7J	750	340
225/45R17 XL	94	V	7 1/2J	670	340
225/55R17 XL	101	V	7J	825	340
235/55R17 XL	103	V	7 1/2J	875	340
235/55R18 XL	104	V	7 1/2J	900	340
225/55R19	99	V	7J	775	300

MADE IN CHINA



SPORT UTILITY VEHICLE TIRE



Dry/wet handling performance and drainage performance

A2

- ◀ Asymmetric tread pattern design for better drainage performance inside and grip performance outside.
- ◀ Big shoulder blocks to effectively improve handling performance.

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
18	235/50R18	97	V	7 1/2J	730	300
	235/60R18	103	V	7J	875	300
	255/55R18 XL	109	W	8J	1030	340
19	225/55R19	99	V	7J	775	300
	235/50R19	99	W	7 1/2J	775	300
	235/55R19 XL	105	W	7 1/2J	925	340
	245/55R19	103	V	7 1/2J	875	300
	255/45R19	100	Y	8 1/2J	800	300
	255/50R19 XL	107	W	8J	975	340
	255/55R19 XL	111	W	8J	1090	340
20	265/50R19	106	W	8 1/2J	950	300
	275/45R19 XL	108	Y	9J	1000	340
	245/45R20 XL	103	W	8J	875	340
	255/45R20	101	W	8 1/2J	825	300
	255/50R20 XL	109	Y	8J	1030	340
	275/40R20 XL	106	Y	9 1/2J	950	340
	275/45R20 XL	110	W	9J	1060	340
	295/40R20	106	Y	10 1/2J	950	300

MADE IN CHINA



Super ability LRS tire dedicated for luxury brand SUV

X7 LRS

- ◀ Asymmetric tread pattern design for better drainage performance inside and grip performance outside.
- ◀ Big shoulder blocks to effectively improve handling performance.
- ◀ LRS technology used for driving the vehicle's safety.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
18	225/50R18	95	W	7J	690	300
	235/50R18	97	W	7 1/2J	730	300
	245/40R18	93	W	8 1/2J	650	300
	225/45R19	92	W	7 1/2J	630	300
19	245/50R19	101	W	7 1/2J	825	300
	255/40R19	96	W	9J	710	300
	255/45R19	100	W	8 1/2J	800	300
	285/45R19	107	W	9 1/2J	975	300
20	245/45R20	99	W	8J	775	300
	255/35R20	93	W	9J	650	300
	255/45R20	101	W	8 1/2J	825	300
	275/45R20	106	W	9J	950	300
	275/50R20	109	W	8 1/2J	1030	300
	285/45R20	108	W	9 1/2J	1000	300
	295/45R20	110	W	10J	1060	300
	305/40R20 XL	112	W	11J	1120	340
21	255/50R21	106	W	8J	950	300
	285/35R21	101	W	10J	825	300
	285/45R21	109	W	9 1/2J	1030	300

MADE IN CHINA



Comfortable SUV HP tire

A50

- ◀ Asymmetric pattern design to lower noise effectively.
- ◀ Wide tread surface for superior comfortable ride.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	195/65R15	91	V	6J	615	300
16	205/60R16	92	V	6J	630	300
	205/65R16	95	V	6J	690	300
	215/60R16	95	V	6 1/2J	690	300
	215/65R16	98	V	6 1/2J	750	300
17	215/70R16	100	H	6 1/2J	800	300
	235/60R16	100	H	7J	800	300
	215/55R17 XL	98	V	7J	750	340
	215/60R17	96	V	6 1/2J	710	300
18	225/60R17	99	H	6 1/2J	775	300
	225/65R17	102	V	6 1/2J	850	300
	235/55R17	99	V	7 1/2J	775	300
	245/65R17	107	H	7J	975	300
	215/55R18 XL	99	V	7J	775	340
	225/55R18	98	V	7J	750	300
18	225/60R18	100	H	6 1/2J	800	300
	235/55R18	100	V	7 1/2J	800	300
	245/60R18	105	V	7J	925	300

MADE IN CHINA



Comfortable SUV HP tire

A51

- ◀ Low noise to offer a quiet ride.
- ◀ Wide tread surface for superior comfortable ride.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
16	215/65R16	98	V	6 1/2J	750	300
	215/60R17	96	V	6 1/2J	710	300
	225/60R17	99	H	6 1/2J	775	300
17	225/65R17	102	V	6 1/2J	850	300
	235/55R17	99	V	7 1/2J	775	300
	235/65R17 XL	108	H	7J	1000	340
	245/65R17	107	H	7J	975	300
	235/60R17	102	V	7J	850	300
18	215/55R18	95	V	7J	690	300
	225/55R18	98	V	7J	750	300
	225/60R18	100	H	6 1/2J	800	300
	235/50R18	97	V	7 1/2J	730	300
	235/55R18	100	V	7 1/2J	800	300
	235/60R18 XL	107	V	7J	975	340
	235/65R18	106	H	7J	950	300
	245/60R18	105	H	7J	925	300
20	265/40R20 XL	104	W	9 1/2J	900	340
21	275/40R21 XL	107	W	9 1/2J	975	340
	295/40R21 XL	111	W	10 1/2J	1090	340

MADE IN CHINA



SUV Tire for Urban Road Use, with Low Noise and Good Dry/wet Performance

HT601

- ◀ Optimized pattern pitches to offer more comfortable and quiet ride.
- ◀ Big pattern blocks design to improve wear resistance ability.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
16	245/70R16 XL	111	H	7J	1090	340
	265/70R16	112	H	8J	1120	300
17	225/60R17 XL	103	H	6 1/2J	875	340
	225/65R17	102	H	6 1/2J	850	300

MADE IN CHINA



All-terrain tire

AT760

- ◀ Open pattern groove design to provide superior off-road traction ability.
- ◀ Deep pattern groove design to improve wear resistance and off-road performance.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	LT215/75R15 OWL	8PR	106/103	S	6J	D875 S950	450
	LT235/75R15 OWL	8PR	110/107	S	6 1/2J	D975 S1060	450
16	235/70R16 OWL	/	106	T	7J	950	300
	245/70R16 OWL	/	107	T	7J	975	300
	LT265/70R16 OWL	8PR	117/114	S	8J	D1180 S1285	450
	LT265/65R17 OWL	10PR	120/117	S	8J	D1285 S1400	550
17	235/65R17 OWL	/	104	T	7J	900	300
18	265/60R18 XL OWL	/	114	H	8J	1180	340

MADE IN CHINA



High handling performance

SPORT GREEN SUV

- ◀ Excellent steering and handling performance.
- ◀ Superior drainage performance.
- ◀ Lower noise.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
16	215/65R16	98	H	6 1/2J	750	300
	215/70R16	100	H	6 1/2J	800	300
	225/70R16	103	H	6 1/2J	875	300
	235/60R16	100	H	7J	800	300
	235/70R16	106	H	7J	950	300
	245/70R16	107	H	7J	975	300
17	255/65R16	109	H	7 1/2J	1030	300
	265/70R16	112	H	8J	1120	300
	215/60R17	96	H	6 1/2J	710	300
	225/65R17	102	H	6 1/2J	850	300
	235/55R17	99	V	7 1/2J	775	300
	235/65R17 XL	108	V	7J	1000	340
18	245/65R17	107	H	7J	975	300
	265/65R17	112	H	8J	1120	300
	225/55R18	98	V	7J	750	300
	235/50R18	97	W	7 1/2J	730	300
	235/55R18	100	V	7 1/2J	800	300
	235/60R18 XL	107	W	7J	975	340
19	255/55R18 XL	109	W	8J	1030	340
	255/70R18	113	H	7 1/2J	1150	300
20	275/50R19 XL	107	W	8J	975	340
	275/40R20 XL	106	W	9 1/2J	950	340
21	275/45R20 XL	110	W	9J	1060	340
	295/35R21 XL	107	Y	10 1/2J	975	340

MADE IN CHINA



Balanced Performance Asymmetric Design

PARALLER 4X4 HP

- ◀ Four circumferential grooves help channel water to resist hydroplaning and help maintain wet traction.
- ◀ Solid center-rib tread design provides continuous tread contact with the road to enhance steering response and handling



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	235/70R15 XL	106	H	7J	950	340
	205/70R16	97	V	6J	730	300
	215/65R16 XL	102	H	6 1/2J	850	340
	215/70R16	100	H	6 1/2J	800	300
	225/75R16	104	H	6J	900	300
	235/70R16	106	H	7J	950	300
16	245/70R16 XL	111	H	7J	1090	340
	265/70R16	112	H	8J	1120	300
	275/70R16	114	H	8J	1180	300
	215/60R17	96	H	6 1/2J	710	300
	225/55R17 XL	101	V	7J	825	340
	225/60R17	99	H	6 1/2J	775	300
17	225/65R17	102	H	6 1/2J	850	300
	235/55R17 XL	103	W	7 1/2J	875	340
	235/60R17 XL	106	V	7J	950	340
	235/65R17 XL	108	V	7J	1000	340
	235/70R17 XL	109	T	7J	1030	340
	245/65R17 XL	111	H	7J	1090	340
18	255/60R17	106	H	7 1/2J	950	300
	255/65R17	110	H	7 1/2J	1060	300
	255/70R17	112	T	7 1/2J	1120	300
	265/65R17	112	H	8J	1120	300
	225/60R18	100	H	6 1/2J	800	300
	235/55R18 XL	104	V	7 1/2J	900	340
19	235/60R18 XL	107	V	7J	975	340
	235/65R18	106	H	7J	950	300
	245/60R18	105	V	7J	925	300
	255/55R18 XL	109	V	8J	1030	340
	255/65R18	111	H	7 1/2J	1090	300
	255/70R18	113	T	7 1/2J	1150	300
20	265/60R18	110	H	8J	1060	300
	265/65R18	114	H	8J	1180	300
	265/70R18	116	T	8J	1250	300
	275/65R18	116	H	8J	1250	300
	255/55R19 XL	111	V	8J	1090	340

MADE IN THAILAND



All-season Performance Long&Regular Wear

PARALLER H/T

- ◀ noise reduction, handling performance.
- ◀ Braking & Traction Performance:
Long interlocking center rib and wide shoulder blocks maximize the traction and provide short stopping distances.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	235/75R15 XL	/	109	T	6 1/2J	1030	340
	215/70R16	/	100	T	6 1/2J	800	300
	225/70R16	/	103	T	6 1/2J	875	300
	235/70R16	/	106	T	7J	950	300
	245/70R16	/	107	T	7J	975	300
	245/75R16	/	111	T	7J	1090	300
16	255/70R16	/	111	T	7 1/2J	1090	300
	265/70R16	/	112	T	8J	1120	300
	265/75R16	/	116	T	7 1/2J	1250	300
	LT215/85R16	10PR	115/112	S	6J	1120 1215	550
	LT225/75R16	10PR	115/112	S	6J	1120 1215	550
	LT235/65R16	10PR	121/119	R	7J	1360 1450	550
	LT235/85R16	10PR	120/116	R	6 1/2J	1285 1400	550
	LT245/75R16	10PR	120/116	R	7J	1260 1380	550
	LT265/75R16	10PR	123/120	R	7 1/2J	1400 1550	550
	235/65R17	/	104	T	7J	900	300
17	245/65R17	/	107	T	7J	975	300
	245/70R17	/	110	T	7J	1060	300
	265/65R17	/	112	T	8J	1120	300
	265/70R17	/	115	T	8J	1215	300
	LT265/70R17	10PR	121/118	R	8J	1320 1450	550
	265/50R20 XL	/	111	V	8 1/2J	1090	340
20	275/55R20 XL	/	117	T	8 1/2J	1285	340
	275/60R20	/	115	T	8J	1215	300

MADE IN THAILAND



On & Off Performance Snow /Ice Traction

PARALLER A/T

- ◀ Excellent traction off-road and wet performance.
- ◀ Closed shoulder design help provide long tread life and resist uneven wear.
- ◀ Designed to combine a quiet highway ride and long tread life with all-terrain performance.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	235/75R15 XL OWL	/	109	T	6 1/2J	1030	340
	265/70R15 OWL	/	112	T	8J	1120	300
	31X10.50R15LT OWL	6PR	109	R	8 1/2J	1030	350
	31X10.50R15LT OWL	6PR	109	Q	8 1/2J	1030	350
	LT235/75R15 OWL	6PR	104/101	R	6 1/2J	825 900	350
	LT235/75R15 OWL	6PR	104/101	Q	6 1/2J	825 900	350
	235/70R16 OWL	/	106	T	7J	950	300
	245/70R16 XL OWL	/	111	T	7J	1090	340
	245/75R16 OWL	/	111	T	7J	1090	300
	255/70R16 OWL	/	111	S	7 1/2J	1090	300
16	265/70R16 OWL	/	112	T	8J	1120	300
	265/75R16 OWL	/	116	T	7 1/2J	1250	300
	LT215/85R16 OWL	10PR	115/112	Q	6J	1120 1215	550
	LT225/75R16 OWL	10PR	115/112	Q	6J	1120 1215	550
	LT235/85R16 OWL	10PR	120/116	S	6 1/2J	1260 1380	550
	LT235/85R16 OWL	10PR	120/116	Q	6 1/2J	1260 1380	550
	LT245/75R16 OWL	10PR	120/116	Q	7J	1260 1380	550
	LT265/75R16 OWL	10PR	123/120	R	7 1/2J	1400 1550	550
	LT285/75R16 OWL	10PR	126/123	R	8J	1550 1700	550
	LT305/70R16 OWL	10PR	124/121	R	9J	1450 1600	450
	245/65R17 OWL XL	/	111	T	7J	1090	340
	245/70R17 OWL	/	110	S	7J	1060	300
	265/65R17 OWL	/	112	T	8J	1120	300
	265/70R17 OWL	/	115	T	8J	1215	300
17	285/70R17 OWL	/	116	T	8 1/2J	1250	300
	LT235/80R17 OWL	10PR	120/117	R	6 1/2J	1285 1400	550
	LT235/80R17 OWL	10PR	120/117	Q	6 1/2J	1285 1400	550
	LT235/80R17 OWL	10PR	120/117	Q	6 1/2J	1285 1400	550

MADE IN THAILAND

RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
17	LT245/70R17 OWL	10PR	119/116	Q	7J	1250 1360	550
	LT245/75R17 OWL	10PR	121/118	R	7J	1320 1450	550
	LT265/70R17 OWL	10PR	121/118	R	8J	1320 1450	550
	LT265/70R17 OWL	10PR	121/118	Q	8J	1320 1450	550
	LT285/70R17 OWL	8PR	121/118	S	8 1/2J	1320 1450	450
	LT285/70R17 OWL	10PR	121/118	S	8 1/2J	1320 1450	450
18	LT305/70R17 OWL	8PR	119/116	R	9J	1250 1360	350
	255/70R18 OWL	/	113	S	7 1/2J	1150	300
	265/70R18 OWL	/	116	T	8J	1250	300
	275/65R18 OWL	/	116	T	8J	1250	300
	LT265/65R18 OWL	10PR	122/119	Q	8J	1360 1500	550
	LT265/70R18 OWL	10PR	124/121	S	8J	1450 1600	550
20	LT275/65R18 OWL	10PR	123/120	S	8J	1400 1550	550
	LT275/70R18 OWL	10PR	125/122	S	8J	1500 1650	550
	LT305/60R20 OWL	10PR	121/118	R	9J	1320 1450	450
	275/55R20 OWL	/	113	S	8 1/2J	1150	300
	275/60R20 OWL	/	115	T	8J	1215	300
	LT275/55R20 OWL	10PR	120/117	Q	8 1/2J	1285 1400	550
20	LT275/60R20 OWL	10PR	123/120	Q	8J	1400 1550	550
	LT275/65R20 OWL	10PR	126/123	R	8J	1550 1700	550
	LT285/55R20 OWL	10PR	122/119	S	9J	1360 1500	550
	LT305/55R20 OWL	10PR	121/118	R	9 1/2J	1320 1450	450



Mud-Terrain Tire

SHARP

- ▶ Aggressive tread pattern design for superior mud shedding and desilting ability.
- ▶ Wide horizontal groove design for better off-road performance and more traction.

RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	LT215/75R15 OWL	6PR	100/97	Q	6J	D730 S800	350
	LT235/75R15 OWL	6PR	104/101	Q	6 1/2J	D825 S900	350
16	LT265/75R16 OWL	10PR	123/120	Q	7 1/2J	D1400 S1550	550
17	LT265/70R17 OWL	10PR	121/118	Q	8J	D1320 S1450	550

MADE IN CHINA



Mud Terrain Muddy ruts for added pulling power

PARALLER M/T

- ▶ Advanced tread compound as well as work against the sides of muddy ruts for added pulling power.
- ▶ Large & Strong block and deep tread enhance grip on various off-road.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	265/70R15	/	112	Q	8J	1120	300
	265/75R15	/	112	Q	7 1/2J	1120	300
	LT215/75R15	6PR	100/97	Q	6J	D 730 S 800	350
	LT235/75R15	6PR	104/101	Q	6 1/2J	D 825 S 900	350
	30X9.50R15LT	6PR	104	Q	7 1/2J	900	350
	31X10.50R15LT	6PR	109	Q	8 1/2J	1030	350
16	33X12.50R15LT	6PR	108	Q	10J	1000	300
	35X12.50R15LT	6PR	113	Q	10J	1150	300
	205R16LT	8PR	110/108	Q	6J	D 1000 S 1060	450
	LT225/75R16	8PR	110/107	Q	6J	D 975 S 1060	450
	LT235/85R16 OWL	10PR	120/116	S	6 1/2J	D 1260 S 1380	550
	LT245/75R16	10PR	120/116Q	Q	7J	D 1260 S 1380	550
16	LT255/70R16	8PR	115/112	Q	7 1/2J	D 1120 S 1215	450
	LT265/70R16	6PR	110/107	Q	8J	D 975 S 1060	350
	LT265/75R16	10PR	123/120	Q	7 1/2J	D 1550 S 1650	550
	LT285/75R16	10PR	126/123	Q	8J	D 1550 S 1700	550
	LT305/70R16	10PR	124/121	Q	9J	D 1450 S 1600	450
	LT315/75R16	10PR	127/124	Q	8 1/2J	D 1600 S 1750	450
17	LT375/65R16	8PR	126/123	Q	11J	D 1550 S 1700	350
	LT235/80R17	10PR	120/117	Q	6 1/2J	D 1285 S 1400	550
	LT265/65R17	10PR	120/117	Q	8J	D 1285 S 1400	550
	LT265/70R17	10PR	121/118	Q	8J	D 1320 S 1450	550
	LT285/70R17	10PR	121/118	Q	8 1/2J	D 1320 S 1450	550
	LT295/70R17	10PR	121/118	Q	8 1/2J	D 1320 S 1450	550
17	LT305/65R17	10PR	121/118	Q	9J	D 1320 S 1450	450
	LT305/70R17	8PR	119/116	Q	9J	D 1250 S 1360	350
	LT315/70R17	10PR	121/118	Q	9 1/2J	D 1250 S 1450	450

RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load	Max Pressure
						kg	kPa
17	33X12.50R17LT	10PR	120	Q	10J	1400	450
	35X12.50R17LT	10PR	121	Q	10J	1450	450
	37X12.50R17LT	8PR	124	Q	10J	1600	350
	37X13.50R17LT	10PR	121	Q	11J	1450	450
	40X13.50R17LT	8PR	121	Q	11J	1450	350
18	LT275/70R18	10PR	125/122	Q	8J	1500 1650	550
	LT295/70R18	10PR	129/126	Q	8 1/2J	1700 1850	550
	LT305/60R18	10PR	121/118	Q	9J	1320 1450	450
	LT305/70R18	10PR	126/123	Q	9J	1550 1700	450
	33X12.50R18LT	10PR	118	Q	10J	1320	450
	33X12.50R18LT	12PR	122	Q	10J	1500	550
	35X12.50R18LT	8PR	118	Q	10J	1320	350
	35X12.50R18LT	10PR	123	Q	10J	1550	450
	35X12.50R18LT	12PR	128	Q	10J	1800	550
	37X13.50R18LT	8PR	124	Q	11J	1600	350
	LT285/55R20	8PR	117/114	Q	9J	1180 1285	450
	LT285/55R20	10PR	122/119	Q	9J	1360 1500	550
	LT285/65R20	10PR	127/124	Q	8 1/2J	1600 1750	550
	LT295/60R20	10PR	126/123	Q	8 1/2J	1550 1700	550
	LT305/55R20	10PR	121/118	Q	9 1/2J	1320 1450	450
20	33X12.50R20LT	10PR	114	Q	10J	1180	450
	33X12.50R20LT	12PR	119	Q	10J	1360	550
	35X12.50R20LT	10PR	121	Q	10J	1450	450
	35X12.50R20LT	12PR	125	Q	10J	1650	550
	36X15.50R20LT	10PR	126	Q	12 1/2J	1700	450
	37X13.50R20LT	10PR	127	Q	11J	1750	450
	37X13.50R20LT	12PR	128	Q	11J	1800	550
	38X15.50R20LT	8PR	125	Q	12 1/2J	1650	350
22	40X14.50R20LT	8PR	128	Q	11 1/2J	1800	350
	33X12.50R22LT	10PR	109	Q	10J	1030	450
	33X12.50R22LT	12PR	114	Q	10J	1180	550
	35X12.50R22LT	10PR	117	Q	10J	1285	450
	35X12.50R22LT	12PR	121	Q	10J	1450	550
	37X13.50R22LT	10PR	123	Q	11J	1550	450
	37X13.50R22LT	12PR	128	Q	11J	1800	550
	33X12.50R24LT	10PR	101	Q	11 1/2J	825	450
24	37X13.50R24LT	10PR	120	Q	11J	1400	450
26	37X13.50R26LT	10PR	114	Q	11J	1180	450

MADE IN THAILAND



LIGHT TRUCK TIRE



High wear performance

GREEN VAN

- ◀ Excellent grip and handling performance.
- ◀ Better grip performance on slippery road together with high safety coefficient.
- ◀ Suitable for commercial vehicles.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
205/80R16	/	104	S	5 1/2J	900	340
195/55R10C	/	98/96	P	6.00I	D710 5750	250
155R12C	8PR	88/86	N	4.50B	D530 5560	450
155R13C	8PR	90/88	R	4.50B	D560 5600	450
155R13C	8PR	90/88	S	4.50B	D560 5600	450
165R13C	8PR	94/93	R	4.50B	D650 5670	450
175R13C	8PR	97/95	R	5.00B	D690 5730	450
195/50R13C	/	104/101	N	6J	D825 5900	650
165/70R14C	6PR	89/87	R	5J	D545 5580	350
175R14C	8PR	99/98	R	5J	D750 5775	450
175/65R14C	6PR	90/88	T	5J	D560 5600	375
185R14C	8PR	102/100	Q	5 1/2J	D800 5850	450
195R14C	8PR	106/104	Q	5 1/2J	D900 5950	450
205R14C	8PR	109/107	Q	6J	D975 51030	450
215R14C	8PR	112/110	Q	6J	D1060 51120	450
185R15C	8PR	103/102	Q	5 1/2J	D850 5875	450
195R15C	8PR	106/104	R	5 1/2J	D900 5950	450
195/70R15C	8PR	104/102	S	6J	D850 5900	450
205/65R15C	6PR	102/100	T	6J	D800 5850	350
205/70R15C	8PR	101/99	S	5J	D775 5825	450
215/70R15C	8PR	109/107	S	6 1/2J	D975 51030	450
225/70R15C	8PR	112/110	S	6 1/2J	D1060 51120	450
175/75R16C	8PR	104/102	S	5J	D850 5900	475
185/75R16C	6PR	99/97	H	6J	D730 5775	375
195/60R16C	8PR	104/102	S	6J	D850 5900	475
195/65R16C	8PR	107/105	S	5 1/2J	D925 5975	475
195/75R16C	8PR	110/108	T	6J	D1000 51060	450
205R16C	8PR	107/105	T	6J	D925 5975	475
205/65R16C	8PR	106/104	S	6J	D900 5950	450
205/75R16C	8PR	110/108	S	5 1/2J	D1000 51060	475
215/60R16C	6PR	103/101	T	6 1/2J	D825 5875	375
215/65R16C	8PR	109/107	S	6 1/2J	D975 51030	475
215/70R16C	6PR	108/106	T	6 1/2J	D950 51000	350
215/75R16C	8PR	113/111	S	6J	D1090 51150	475
225/65R16C	8PR	112/110	S	6 1/2J	D1060 51120	475
235/65R16C	8PR	115/113	S	7J	D1150 51215	475

MADE IN CHINA & THAILAND



Commercial tire with high endurance and wear performance

AR939

- ◀ Effectively improve the endurance of the tyre with the new construction design.
- ◀ Excellent stability.
- ◀ Great grip performance and driving force of turning.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
14	175/70R14LT	8PR	93/90	Q	5J	D600 5650	450
	185R14LT	8PR	102/100	Q	5 1/2J	D800 5850	450
15	195/70R15LT	8PR	99/96	S	6J	D710 5775	450
	195R15LT	8PR	106/104	R	5 1/2J	D900 5950	450
	215/70R15LT	8PR	104/101	Q	6 1/2J	D825 5900	450
	225/70R15LT	8PR	107/103	Q	6 1/2J	D875 5975	450

MADE IN CHINA



Commercial Tire for Egypt Market

R772

- ◀ Wide tread surface for superior wear resistance performance.
- ◀ Big shoulder blocks to enhance tire traction and stiffness performance.
- ◀ Optimized pattern pitches distribution to offer more comfortable and quiet ride.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
14	195R14C WR	8PR	106/104	P	5 1/2J	D900 5950	450
	205/75R14C WR	8PR	109/107	S	5 1/2J	D 975 5 1030	475
	205/70R15C	8PR	106/104	S	6J	D900 5950	450
15	215/70R15C WR	8PR	109/107	R	6 1/2J	D975 51030	450
	225/70R15C WR	8PR	112/110	R	6 1/2J	D1060 51120	450



WINTER TIRE



Tire dedicated for car on ice-snow ground

13

- ◀ Outstanding grip and traction performance on ice and snow surface with directional tread pattern design.
- ◀ Directional grooves to help evacuate snow and mud.
- ◀ Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Max Pressure
					kg	kPa
14	165/70R14	81	S	5J	462	300
	175/65R14	82	S	5J	475	300
	175/70R14	84	S	5J	500	300
	185/60R14	82	S	5 1/2J	475	300
	185/65R14	86	S	5 1/2J	530	300
15	185/70R14	88	S	5 1/2J	560	300
	185/55R15	82	S	6J	475	300
	185/60R15	84	S	5 1/2J	500	300
	185/65R15	88	S	5 1/2J	560	300
	195/55R15	85	S	6J	515	300
	195/60R15	88	S	6J	560	300
	195/65R15	91	S	6J	615	300
	205/65R15	94	S	6J	670	300
	195/55R16 XL	91	S	6J	615	340
	195/60R16	89	S	6J	580	300
16	205/55R16	91	S	6 1/2J	615	300
	205/60R16	92	S	6J	630	300
	215/55R16	93	S	7J	650	300
	215/60R16	95	S	6 1/2J	690	300
	225/55R16	95	S	7J	690	300
	225/60R16	98	S	6 1/2J	750	300
	215/50R17 XL	95	S	7J	690	340
	215/55R17	94	S	7J	670	300
17	225/45R17 XL	94	S	7 1/2J	670	340
	225/50R17	94	S	7J	670	300
	225/55R17	97	S	7J	730	300
	235/45R17 XL	97	S	8J	730	340
	235/50R17	96	S	7 1/2J	710	300
	235/55R17	99	S	7 1/2J	775	300
	245/45R17 XL	99	S	8J	775	340
	225/45R18 XL	95	S	7 1/2J	690	340
18	245/45R18	96	S	8J	710	300

MADE IN CHINA



Tires for SUV on ice-snow ground specially

15

- ◀ Fine lines on the tire surface and densely groove design to provide a strong power for ice and snow road.
- ◀ Outstanding grip performance on ice and snow surface with sput Hole design.
- ◀ Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	205/70R15	96	S	6J	710	300
	215/75R15	100	S	6J	800	300
	235/75R15	105	S	6 1/2J	925	300
	215/65R16	98	S	6 1/2J	750	300
	215/70R16	100	S	6 1/2J	800	300
16	225/70R16	103	S	6 1/2J	875	300
	235/60R16 XL	104	S	7J	900	340
	235/70R16	106	S	7J	950	300
	245/70R16	107	S	7J	975	300
	265/70R16	112	S	8J	1120	300
17	275/70R16	114	S	8J	1180	300
	215/60R17	96	S	6 1/2J	710	300
	215/65R17	99	S	6 1/2J	775	300
	225/60R17	99	S	6 1/2J	775	300
	225/65R17	102	S	6 1/2J	850	300
18	235/65R17	104	S	7J	900	300
	245/65R17	107	S	7J	975	300
	255/60R17	106	S	7 1/2J	950	300
	265/65R17	112	S	8J	1120	300
	275/65R17	115	S	8J	1215	300
19	285/65R17	116	S	8 1/2J	1250	300
	215/55R18 XL	99	S	7J	775	340
	225/55R18	98	S	7J	750	300
	225/60R18	100	S	6 1/2J	800	300
	235/50R18	97	S	7 1/2J	730	300
20	235/55R18	100	S	7 1/2J	800	300
	235/60R18	103	S	7J	875	300
	235/65R18	106	S	7J	950	300
	245/60R18	105	S	7J	925	300
	255/55R18 XL	109	S	8J	1030	340
21	265/60R18	110	S	8J	1060	300
	285/60R18	116	S	8 1/2J	1250	300
	225/55R19	99	S	7J	775	300
	235/50R19	99	S	7 1/2J	775	300
	235/55R19 XL	105	S	7 1/2J	925	340
22	245/55R19	103	S	7 1/2J	875	300
	255/50R19 XL	107	S	8J	975	300
	255/55R19	107	S	8J	975	300
	275/45R19 XL	108	S	9J	1000	340
	265/50R19	106	S	8 1/2J	950	300
23	245/45R20	99	S	8J	775	300
	245/50R20	102	S	7 1/2J	850	300
	255/45R20	101	S	8 1/2J	825	300
	255/50R20 XL	109	S	8J	1030	340
	255/55R20 XL	110	S	8J	1060	340
24	275/40R20	102	S	9 1/2J	950	300
	275/45R20 XL	107	S	9J	1060	340
	275/50R20 XL	113	S	8 1/2J	1150	340
	275/55R20	113	S	8 1/2J	1150	300
	285/50R20	112	S	9J	1120	300
25	315/35R20	106	S	11J	950	300
	275/45R21	107	S	9J	975	300
	275/40R22 XL	107	S	9 1/2J	975	340

MADE IN CHINA



Tire dedicated for car on ice-snow ground

AW31

- ◀ Outstanding grip and traction performance on ice and snow surface with asymmetric tread pattern design.
- ◀ Special suction and drainage line design, fast water film guide, providing excellent grip.
- ◀ Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
15	175/65R15 XL	84	S	5J	500	300
	185/60R15	84	S	5 1/2J	500	300
	185/65R15	88	S	5 1/2J	560	300
	195/60R15	88	S	6J	560	300
	195/65R15	91	S	6J	615	300
16	215/65R15 XL	100	S	6 1/2J	800	340
	215/70R15	98	S	6 1/2J	750	300
	185/55R16 XL	87	S	6J	545	340
	205/50R16 XL	91	S	6 1/2J	615	340
	205/55R16	91	S	6 1/2J	615	300
17	205/60R16	92	S	6J	630	300
	215/60R16	95	S	6 1/2J	690	300
	205/50R17 XL	93	S	6 1/2J	650	340
	215/45R17 XL	91	S	7J	615	340
	215/55R17	94	S	7J	670	300
18	225/50R17	94	S	7J	670	300
	225/55R17	97	S	7J	730	300
	225/40R18	92	S	8J	630	300
	235/45R18 XL	98	S	8J	750	340
	245/40R18 XL	97	S	8 1/2J	730	340
19	245/50R18 XL	104	S	7 1/2J	900	340
	255/45R18 XL	103	S	8 1/2J	875	340
	225/45R19 XL	96	S	7 1/2J	710	340
	245/40R19 XL	98	S	8 1/2J	750	340
	245/45R19	98	S	8J	750	300
20	245/45R19 XL	102	S	8J	850	340
	255/40R19 XL	100	S	9J	800	340
	255/45R19 XL	104	S	8 1/2J	900	340
	275/35R19	96	S	9 1/2J	710	300
	275/35R19 XL	100	S	9 1/2J	800	340
21	275/40R19 XL	105	S	9 1/2J	925	340
	245/40R20 XL	99	S	8 1/2J	775	340
	275/35R20 XL	102	S	9 1/2J	850	340

MADE IN CHINA



Suitable for snow road with excellent handling and grip

POLARBEAR 1

◀ Excellent snow evacuation.

◀ Good handling and traction performance on ice & snow road.



Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
145/70R12	69	T	4.50B	325	300
145/70R13	71	T	4.50B	345	300
145/80R13	75	T	4.00B	387	300
155/65R13	73	T	4.50B	365	300
155/65R14	75	T	4 1/2J	387	300
155/70R13	75	T	4.50B	387	300
155/80R13	79	T	4.50B	437	300
165/60R14 XL	79	T	5J	437	340
165/65R13	77	T	5.00B	412	300
165/65R14	79	T	5J	437	300
165/65R15	81	T	5J	462	300
165/70R13	79	T	5.00B	437	300
165/70R14	81	T	5J	462	300
165/70R14 XL	85	T	5J	515	340
175/60R15	81	H	5J	462	300
175/65R13	80	T	5.00B	450	300
175/65R14	82	T	5J	475	300
175/65R14 XL	86	T	5J	530	340
175/65R15	84	T	5J	500	300
175/70R13	82	T	5.00B	475	300
175/70R14	84	T	5J	500	300
175/70R14 XL	88	T	5J	560	340
175/80R14	88	T	5J	560	300
185/60R14	82	T	5 1/2J	475	300
185/60R15	84	T	5 1/2J	500	300
185/60R15 XL	88	T	5 1/2J	560	340
185/65R14	86	T	5 1/2J	530	300
185/65R15	88	T	5 1/2J	560	300
185/65R15 XL	92	T	5 1/2J	630	340
185/70R14	88	T	5 1/2J	560	300
195/60R15	88	T	6J	560	300
195/60R15 XL	88	H	6J	560	300
195/60R15 XL	92	H	6J	630	340
195/65R15	91	T	6J	615	300
195/65R15 XL	91	H	6J	615	300
195/65R15 XL	95	T	6J	690	340
205/70R14	91	T	6J	615	300
205/60R15	91	H	6J	615	300
205/60R16	92	H	6J	630	300
205/60R16 XL	96	H	6J	710	340
205/65R15	94	H	6J	670	300
205/70R15	96	T	6J	710	300
215/60R16 XL	99	H	6 1/2J	775	340
215/65R16	98	H	6 1/2J	750	300
225/60R16 XL	102	V	6 1/2J	850	340

MADE IN CHINA



Excellent handling performance

POLARBEAR 2

◀ Excellent handling performance and high comfort.

◀ Outstanding snow evacuation.

◀ Excellent grip on wet and slush condition.



Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
185/55R14	80	H	6J	450	300
185/55R15	82	H	6J	475	300
195/45R16 XL	84	H	6 1/2J	500	340
195/50R15	82	H	6J	475	300
195/50R16 XL	88	V	6J	560	340
195/55R15	85	H	6J	515	300
195/55R16	87	H	6J	545	300
205/45R16 XL	87	V	7J	545	340
205/45R17 XL	88	V	7J	560	340
205/50R16 XL	91	V	6 1/2J	615	340
205/50R17 XL	93	V	6 1/2J	650	340
205/55R16	91	H	6 1/2J	615	300
205/55R16 XL	94	H	6 1/2J	670	340
205/55R17 XL	95	V	6 1/2J	690	340
215/45R17 XL	91	V	7J	615	340
215/50R17 XL	95	V	7J	690	340
215/55R16 XL	97	H	7J	730	340
215/55R17 XL	98	V	7J	750	340
225/40R18 XL	92	V	8J	630	340
225/45R17 XL	94	V	7 1/2J	670	340
225/45R18 XL	95	V	7 1/2J	690	340
225/50R17 XL	98	V	7J	750	340
225/55R16 XL	99	H	7J	775	340
225/55R17 XL	101	V	7J	825	340
235/40R18 XL	95	V	8 1/2J	690	340
235/45R17 XL	97	V	8J	730	340
235/45R18 XL	98	V	8J	750	340
235/55R17 XL	103	V	7 1/2J	875	340
245/40R18 XL	97	V	8 1/2J	730	340
245/45R17 XL	99	V	8J	775	340
245/45R18 XL	100	V	8J	800	340

MADE IN CHINA



High snow performance

POLARBEAR SUV

◀ High snow evacuation performance.

◀ Better handling and traction on ice&snow road surface.



Size	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
215/65R16	98	H	6 1/2J	750	300
215/70R16	100	H	6 1/2J	800	300
215/60R17	96	V	6 1/2J	710	300
215/65R17	99	V	6 1/2J	775	300
225/60R17	99	H	6 1/2J	775	300
225/65R17 XL	106	V	6 1/2J	950	340
235/65R17 XL	108	V	7J	1000	340
225/55R18 XL	102	V	7J	850	340
235/55R18 XL	104	H	7 1/2J	900	340
235/60R18 XL	107	V	7J	975	340
255/55R18 XL	109	V	8J	1030	340
235/55R19 XL	105	V	7 1/2J	925	340
275/40R20 XL	106	V	9 1/2J	950	340

MADE IN CHINA



High snow and handling performance

POLARBEAR VAN

◀ Superior grip and handling performance.

◀ Excellent stability performance.

◀ Good snow evacuation ability.

◀ Improved handling on ice& snow condition to provide high safety.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load kg	Max Pressure kPa
165/70R14C	6PR	89/87	R	5J	D545 5580	375
175/65R14C	6PR	90/88	T	5J	D560 5600	375
195/70R15C	8PR	104/102	R	6J	D850 5900	450
205/70R15C	8PR	106/104	R	6J	D900 5950	450
215/70R15C	8PR	109/107	R	6 1/2J	D975 51030	450
225/70R15C	8PR	112/110	R	6 1/2J	D1060 51120	450
195/60R16C	6PR	99/97	T	6J	D730 5775	375
195/65R16C	8PR	104/102	T	6J	D850 5900	475
195/75R16C	8PR	107/105	R	5 1/2J	D925 5975	475
205/65R16C	8PR	107/105	R	6J	D925 5975	475
205/75R16C	8PR	110/108	R	5 1/2J	D1000 51060	475
215/60R16C	6PR	103/101	T	6 1/2J	D825 5875	375
215/65R16C	8PR	109/107	R	6 1/2J	D975 51030	475
215/75R16C	8PR	113/111	R	6J	D1090 51150	450
225/65R16C	8PR	112/110	R	6 1/2J	D1060 51120	475
225/75R16C	10PR	121/120	R	6J	D1400 51450	550
235/65R16C	8PR	115/113	R	7J	D1150 51215	475

MADE IN CHINA

TBR TIRE

LONG HAUL

STRD-09..... PAGE 40

DRV-09..... PAGE 40

AP-100 II..... PAGE 41

APW091..... PAGE 41

TRW-02..... PAGE 42

STRD-09e+..... PAGE 42

DRV-09e+..... PAGE 43

STRD-09e+ II..... PAGE 43

DRV-29e+..... PAGE 44



Radial Truck Tire

STRD-09

Suitable for the steer axle of the trucks running on highway.

◀ Good handling.

◀ Long life.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
11R22.5	14	144/142	M	8.25	2650	720	2800	720	1054	279	14.5	TRA
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1054	279	14.5	TRA
11R24.5	14	146/143	M	8.25	2725	720	3000	720	1104	279	14.5	TRA
11R24.5	16	149/146	M	8.25	3000	830	3250	830	1104	279	14.5	TRA
295/75R22.5	14	144/141	M	9.00	2575	760	2800	760	1014	298	14.5	TRA
295/75R24.5	16	146/143	M	9.00	2725	830	3000	830	1014	298	14.5	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1050	283	14.5	TRA
285/75R24.5	16	147/144	M	8.25	2800	830	3075	830	1050	283	14.5	TRA



Radial Truck Tire

DRV-09

Suitable for the drive axle of the trucks running on highway.

◀ Good braking and grip on wet road.

◀ Long life.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
11R22.5	14	144/142	M	8.25	2650	720	2800	720	1065	279	22.0	TRA
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1065	279	22.0	TRA
11R24.5	14	146/143	M	8.25	2725	720	3000	720	1116	279	22.0	TRA
11R24.5	16	149/146	M	8.25	3000	830	3250	830	1116	279	22.0	TRA
295/75R22.5	14	144/141	M	9.00	2575	760	2800	760	1026	298	22.0	TRA
295/75R24.5	16	146/143	M	9.00	2725	830	3000	830	1026	298	22.0	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1062	283	22.0	TRA
285/75R24.5	16	147/144	M	8.25	2800	830	3075	830	1062	283	22.0	TRA



Radial Truck Tire

AP-100 II

Suitable for the steer axle of the trucks running on highway.

◀ Stable and safe when running on wet and slippery road.

◀ Low fuel consumption.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
12R22.5	16	152/148	L	9.00	3150	850	3550	850	1084	300	14.5	ETRTO
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	14.5	ETRTO
295/80R22.5	18	152/149	M	9.00	3250	900	3550	900	1044	298	14.5	GB
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	14.5	ETRTO



Radial Truck Tire

APW091

◀ Special design for steer and trailer axle of trucks.

◀ Good side-wear resistance.

◀ High-speed performance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
315/80R22.5	18	154/150	M	9.00	3350	825	3790	825	1076	312	14.5	ETRTO
315/80R22.5	20	156/150	L	9.00	3350	850	4000	850	1076	312	14.5	ETRTO
315/80R22.5	22	158/150(154/150)	L(M)	9.00	3350	900	4250	900	1076	312	14.5	ETRTO



Radial Truck Tire

TRW-02

Suitable for the trailer axle of the trucks running on highway.

◀ Low fuel consumption.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
445/45R19.5	18	156	J	15.00	—	—	4000	900	895	446	15.5	ETRTO
445/45R19.5	20	160	J	15.00	—	—	4500	900	895	446	15.5	ETRTO



Radial Truck Tire (Long Haul Steer)

STRD-09e+

◀ Good handling.

◀ Low fuel consumption.

◀ Certified by U.S.A SmartWay.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
11R22.5	14	144/142	M	8.25	2650	720	2800	720	1054	279	14.5	TRA
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1054	279	14.5	TRA
11R24.5	14	146/143	M	8.25	2725	720	3000	720	1104	279	14.5	TRA
11R24.5	16	149/146	M	8.25	3000	830	3250	830	1104	279	14.5	TRA
295/75R22.5	14	144/141	M	9.00	2575	760	2800	760	1014	298	14.5	TRA
295/75R22.5	16	146/143	M	9.00	2725	830	3000	830	1014	298	14.5	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1050	283	14.5	TRA
285/75R24.5	16	147/144	M	8.25	2800	830	3075	830	1050	283	14.5	TRA



Radial Truck Tire

DRV-09e+

- ✓ Suitable for the drive axle of the trucks running on highway
- ✓ Good braking and grip on wet road.
- ✓ Long life.
- ✓ Low fuel consumption.
- ✓ Certified by U.S.A SmartWay.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm	
					Dual	Single	kg					
11R22.5	14	144/142	M	8.25	2650	720	2800	720	1065	279	17.5	TRA
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1065	279	17.5	TRA
11R24.5	14	146/143	M	8.25	2725	720	3000	720	1116	279	22.0	TRA
11R24.5	16	149/146	M	8.25	3000	830	3250	830	1116	279	22.0	TRA
295/75R22.5	14	144/141	M	9.00	2575	760	2800	760	1026	298	22.0	TRA
295/75R22.5	16	146/143	M	9.00	2725	830	3000	830	1026	298	22.0	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1062	283	22.0	TRA
285/75R24.5	16	147/144	M	8.25	2800	830	3075	830	1062	283	22.0	TRA



Radial Truck Tire (Long Haul Trailer)

STRD-09e+ II

- ✓ Excellent straight running performance.
- ✓ Sipes in shoulder offer low noise and strong heat dissipation.
- ✓ Low fuel consumption.
- ✓ Certified by U.S.A SmartWay.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm	
					Dual	Single	PSI					
11R22.5	14	144/142	M	8.25	2650	720	2800	720	1054	279	9.5	TRA
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1054	279	9.5	TRA
11R24.5	14	146/143	M	8.25	2725	720	3000	720	1104	279	9.5	TRA
11R24.5	16	149/146	M	8.25	3000	830	3250	830	1104	279	9.5	TRA
295/75R22.5	14	144/141	M	9.00	2575	760	2800	760	1014	298	10.0	TRA
295/75R22.5	16	146/143	M	9.00	2725	830	3000	830	1014	298	10.0	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1050	283	9.5	TRA
285/75R24.5	16	147/144	M	8.25	2800	830	3075	830	1050	283	9.5	TRA



Radial Truck Tire (Long Haul)

DRV-29e+


- ✓ Closed shoulder design helps promote uniform wear throughout the life of the tire.
- ✓ Aggressive center lugs help to improve traction in wet or dry conditions for the life of the tread.
- ✓ Optimized the footprint for long and even wear.
- ✓ Strong carcass materials help promote tire durability and provide tire retreadability.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
11R22.5	14	144/142	L	8.25	2650	720	2800	720	1066	279	23.8	TRA
11R22.5	16	146/143	L	8.25	2725	830	3000	830	1066	279	23.8	TRA
11R24.5	14	146/143	L	8.25	2725	720	3000	720	1117	279	23.8	TRA
11R24.5	16	149/146	L	8.25	3000	830	3250	830	1117	279	23.8	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1067	283	23.8	TRA
285/75R24.5	16	147/144	L	8.25	2725	830	3000	830	1067	283	23.8	TRA
295/75R22.5	14	144/141	L	9.00	2575	760	2800	760	1028	298	23.8	TRA
295/75R22.5	16	146/143L	L	9.00	2800	830	3075	830	1028	298	23.8	TRA



REGIONAL

KTS300	PAGE 46	APW091	PAGE 52
KTD300	PAGE 46	AP-100	PAGE 52
KTT307	PAGE 47	AP-100 I	PAGE 53
AP-303	PAGE 47	DRV-OS V	PAGE 53
DRV-303	PAGE 48	DRV-OS	PAGE 54
AT185/AT12	PAGE 48	TR-09	PAGE 54
AT177	PAGE 49	APW-092	PAGE 55
DRV186/AT23	PAGE 49	APW-093	PAGE 55
AP-200	PAGE 50	AW-09	PAGE 56
DRV-OS X	PAGE 50	AP-09	PAGE 56
AP-100XI	PAGE 51	AP-800	PAGE 57
AP-100II	PAGE 51	DRV-OS III	PAGE 57
		AP-100e+	PAGE 58
		TR-09e+	PAGE 58
		STR-29e+	PAGE 59



Radial truck tire
(For national and regional transportation)

KTS300

Suitable for the steer axle of trucks running under a wide range of use, from highway to light unpaved road

- ◀ Optimization of the shoulder block improves resistance to shoulder damage.
- ◀ Lasting grip and stability, with stone rejection design.
- ◀ High wear resistance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
295/80R22.5	18	154/149	L	9.00	3250	850	3750	850	1044	298	16.5	ETRTD
295/80R22.5	16	152/148	M	9.00	3150	850	3650	850	1044	298	16.5	ETRTD



Radial truck tire
(For national and regional transportation)

KTD300

Suitable for the drive axle of trucks running under a wide range of use, from highway to light unpaved road

- ◀ Optimization of the shoulder block improves resistance to shoulder damage.
- ◀ Lasting grip and stability, with M+S and 3PMFS marking.
- ◀ High wear resistance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	20.5	ETRTD




Radial truck tire (Regional Trailer)

KTT307

- ▶ Low fuel consumption.
- ▶ HAT technology: low heat generation.
- ▶ Stone rejection design.
- ▶ New technology for tire to reduce the weight.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
11R22.5	16	148/145	L	8.25	2900	850	3150	850	1050	279	14	ETRTD




Radial truck tire (For national and regional transportation)

AP-303

- Suitable for all position axle of trucks running under a wide range of use, from highway to light unpaved road
- ▶ Optimization of the shoulder block improves resistance to shoulder damage.
 - ▶ Lasting grip and stability with stone rejection design.
 - ▶ HAT technology: low heat generation.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
10.00R20	16	146/143	K	7.5	2725	830	3000	830	1054	278	14.5	GB
10.00R20	18	149/146	K	7.5	3000	930	3250	930	1054	278	14.5	GB
9.5R17.5	14	129/127	M	6.75	1750	750	1850	750	842	240	11.5	ETRTD
9.5R17.5	18	143/141	M	6.75	2575	875	2725	875	842	240	11.5	ETRTD
11R22.5	16	146/143	L	8.25	2725	830	3000	830	1054	279	14.0	TRA
11R22.5	16	148/145	L	8.25	2900	850	3150	850	1054	279	14.0	ETRTD
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	14.0	ETRTD
295/80R22.5	18	152/149	L	9.00	3250	900	3550	900	1044	298	14.0	GB
215/75R17.5	14	126/124	L	6.00	1600	700	1700	700	767	211	12.0	ETRTD
215/75R17.5	16	135/133	L/J	6.00	2060	850	2180	850	767	211	12.0	ETRTD
235/75R17.5	14	132/130	L	6.75	1900	775	2000	775	797	233	12.5	ETRTD
235/75R17.5	16	141/140	L	6.75	2500	850	2575	850	797	233	12.5	ETRTD
235/75R17.5	18	143/141	L/J	6.75	2575	875	2725	875	797	233	12.5	ETRTD



Radial truck tire (For national and regional transportation)

DRV-303

- Suitable for drive axle of trucks running under a wide range of use, from highway to light unpaved road
- ▶ Optimization of the shoulder block improves resistance to shoulder damage.
 - ▶ Lasting grip and stability with M+5.
 - ▶ HAT technology: low heat generation.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure			Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm	
					Dual	Single	kg					
					kPa	kPa	kPa					
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	17.0	ETRTD
295/80R22.5	18	152/149	L	9.00	3250	900	3550	900	1044	298	17.0	GB
215/75R17.5	14	126/124	L	6.00	1600	700	1700	700	767	211	14.0	ETRTD
215/75R17.5	16	135/133	L	6.00	2060	850	2180	850	767	211	14.0	ETRTD
235/75R17.5	14	132/130	L	6.75	1900	775	2000	775	797	233	14.5	ETRTD
235/75R17.5	16	141/140	L	6.75	2500	850	2575	850	797	233	14.5	ETRTD
235/75R17.5	18	143/141	L	6.75	2575	875	2725	875	797	233	14.5	ETRTD



Radial truck tire (Regional Steer)

AT185/AT12

- ▶ Optimization of the shoulder and the proportion of pattern block in the middle.
- ▶ Four straight groove matching 5 type variable angle groove design and ensure good steering tyre and self-cleaning properties.
- ▶ Ultra strong skeleton materials applications and promote tire safety performance.
- ▶ High wear resistance of new formula application and wear mileage increases more than 20%.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	17.0	ETRTD
295/80R22.5	18	152/149	M	9.00	3250	900	3550	900	1044	298	17.0	GB




Radial truck tire (Regional Steer)

AT177

- ▶ Optimization of the shoulder and the proportion of pattern block in the middle.
- ▶ Four straight groove matching S type variable angle groove design and ensure good steering tyre and self-cleaning properties.
- ▶ Ultra strong skeleton materials applications and promote tire safety performance.
- ▶ High wear resistance of new formula application and wear mileage increases more than 20%.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
315/80R22.5	18	154/150	M	9.00	3350	825	3750	825	1076	312	17.0	ETRT0
315/80R22.5	20	156/150	L	9.00	3350	850	4000	850	1076	312	17.0	ETRT0




Radial truck tire (Regional Drive)

DRV186/AT23

- ▶ Optimization of the shoulder and the proportion of pattern block in the middle.
- ▶ Classic mahjong block pattern style matching variable angle groove design and ensure a strong drive and self-cleaning.
- ▶ Ultra strong skeleton materials applications and promote tire safety performance.
- ▶ High wear resistance of new formula application and wear mileage increases more than 20%.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
12R22.5	16	152/148	L	9.00	3150	850	3550	850	1084	300	22.0	ETRT0
12R22.5	18	152/149	L	9.00	3250	930	3550	930	1085	300	22.0	GB
295/80R22.5	16	152/148	L	9.00	3150	850	3550	850	1044	298	23.0	ETRT0
295/80R22.5	18	152/149	L	9.00	3250	900	3550	900	1044	298	23.0	GB



Radial truck tire (Regional Steer)

AP-200

- ▶ Long life.
- ▶ Retreadability.
- ▶ Low eccentric wear.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
11.00R20	16	150/147	K	8.0	3075	830	3350	830	1085	293	16.0	GB
11.00R20	18	152/149	K	8.0	3250	930	3550	930	1085	293	16.0	GB
11R22.5	14	144/142	M	8.25	2650	720	2800	720	1054	279	16.0	TRA
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1054	279	16.0	TRA
11R22.5	16	148/145	M	8.25	2900	850	3150	850	1050	279	16.0	ETRT0
12R22.5	18	152/149	L	9.00	3250	930	3550	930	1085	300	17.0	GB
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	17.0	ETRT0
295/80R22.5	18	152/149	M	9.00	3250	900	3550	900	1044	298	17.0	GB
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	17.0	ETRT0
315/80R22.5	18	154/150	M	9.00	3350	825	3750	825	1076	312	17.0	ETRT0
315/80R22.5	20	156/150	M	9.00	3350	850	4000	850	1076	312	17.0	ETRT0
315/80R22.5	22	158/150/154/150	L(M)	9.00	3350	900	4250	900	1076	312	17.0	ETRT0



Radial truck tire (Regional Drive)

DRV-OS X

- ▶ Typical block pattern design makes good grip performance.
- ▶ High wear resistance and long life.
- ▶ Retreadability.
- ▶ Low eccentric wear.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
12R22.5	16	152/148	L	9.00	3150	850	3550	850	1084	300	23.0	ETRT0
12R22.5	18	152/149	M	9.00	3250	930	3550	930	1085	300	23.0	GB
295/80R22.5	16	152/148	L	9.00	3150	850	3550	850	1044	298	23.0	ETRT0
295/80R22.5	18	152/149	L	9.00	3250	900	3550	900	1044	298	23.0	GB



Radial Truck Tire

AP-100XI

- ◀ Special design for steer and trailer axle of trucks.
- ◀ Good side-wear resistance.
- ◀ High-speed performance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	kPa	Single kg	kPa				
275/80R22.5	16	149/146	M	8.25	3000	850	3250	850	1012	276	14.5	ETRTD




Radial Truck Tire

AP-100 II

- ◀ Special design for steer and trailer axle of trucks.
- ◀ Good side-wear resistance.
- ◀ High-speed performance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	kPa	Single kg	kPa				
12R22.5	16	152/148	L	9.00	3150	850	3550	850	1084	300	14.5	ETRTD
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	14.5	ETRTD
295/80R22.5	18	152/149	M	9.00	3250	900	3550	900	1044	298	14.5	GB
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	14.5	ETRTD



Radial Truck Tire

APW091

- ◀ Special design for steer and trailer axle of trucks.
- ◀ Good side-wear resistance.
- ◀ High-speed performance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	kPa	Single kg	kPa				
315/80R22.5	18	154/150	M	9.00	3350	825	3750	825	1076	312	14.5	ETRTD
315/80R22.5	20	156/150	L	9.00	3350	850	4000	850	1076	312	14.5	ETRTD
315/80R22.5	22	158/150(154/150)	L(M)	9.00	3350	900	4250	900	1076	312	14.5	ETRTD



Radial Truck Tire

AP-100

- ◀ Special design for steer and trailer axle of trucks.
- ◀ Good side-wear resistance.
- ◀ High-speed performance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	kPa	Single kg	kPa				
12.00R20	18	154/151	L	8.5	3450	830	3750	830	1125	315	15.5	TRA
11R22.5	14	144/142	M	8.25	2650	720	2800	720	1054	279	14.5	TRA
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1054	279	14.5	TRA
11R22.5	16	146/145	M	8.25	2900	850	3150	850	1060	279	14.5	ETRTD
11R24.5	14	146/143	M	8.25	2725	720	3000	720	1104	279	14.5	TRA
11R24.5	16	149/146	M	8.25	3000	830	3250	830	1104	279	14.5	TRA
295/75R22.5	14	144/141	M	9.00	2575	760	2800	760	1014	298	14.5	TRA
295/75R22.5	16	146/143	M	9.00	2725	830	3000	830	1014	298	14.5	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1050	283	14.5	TRA
285/75R24.5	16	147/144	M	8.25	2800	830	3075	830	1050	283	14.5	TRA




Radial Truck Tire

AP-100 I

- Special design for all position of buses and steer and trailer axle of trucks.
- Good side-wear resistance.
- High-speed performance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	16.0	ETRTO



Radial Truck Tire

DRV-OS V

- Typical block pattern design suitable for the drive axle of trucks.
- Good braking and grip on the road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	17.5	ETRTO
275/70R22.5	16	148/145	M	8.25	2900	900	3150	900	958	276	17.5	ETRTO



Radial Truck Tire

DRV-OS

- Typical block pattern design suitable for the drive axle of trucks.
- Good braking and grip on the road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
10.00R20	16	146/143	L	7.5	2725	830	3000	830	1054	278	20.0	TRA
10.00R20	18	149/146	K	7.5	3000	930	3250	930	1054	278	20.0	GB
11R22.5	14	144/142	L	8.25	2650	720	2800	720	1059	279	20.5	TRA
11R22.5	16	146/143	L	8.25	2725	830	3000	830	1059	279	20.5	TRA
11R22.5	16	148/145	L	8.25	2900	850	3150	850	1050	279	20.5	ETRTO
11R24.5	14	146/143	L	8.25	2725	720	3000	720	1110	279	20.5	TRA
11R24.5	16	149/146	L	8.25	3000	830	3250	830	1110	279	20.5	TRA
295/75R22.5	14	144/141	M	9.00	2575	760	2800	760	1020	298	20.5	TRA
295/75R22.5	16	146/143	M	9.00	2725	830	3000	830	1020	298	20.5	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1056	283	20.5	TRA
285/75R24.5	16	147/144	M	8.25	2800	830	3075	830	1056	283	20.5	TRA



Radial Truck Tire

TR-09

Suitable for the trailer axle of the trucks running on the high-grade road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
11R22.5	14	144/142	M	8.25	2650	720	2800	720	1054	279	10.75	TRA
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1054	279	10.75	TRA
11R24.5	14	146/143	M	8.25	2725	720	3000	720	1104	279	10.75	TRA
11R24.5	16	149/146	M	8.25	3000	830	3250	830	1104	279	10.75	TRA
295/75R22.5	14	144/141	M	9.00	2575	760	2800	760	1014	298	10.75	TRA
295/75R22.5	16	146/143	M	9.00	2725	830	3000	830	1014	298	10.75	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1050	283	10.75	TRA
285/75R24.5	16	147/144	M	8.25	2800	830	3075	830	1050	283	10.75	TRA
255/70R22.5	16	140/137	M	7.50	2300	830	2500	830	930	255	10.75	TRA



Radial Truck Tire

APW-092

Suitable for the trailer axle of the trucks running on the high-grade road

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
385/65R22.5	18	158	K	11.75	—	—	4250	850	1072	389	16.5	ETRT0
385/65R22.5	20	160	J	11.75	—	—	4500	900	1072	389	16.5	ETRT0




Radial Truck Tire

APW-093

Suitable for the trailer axle of the trucks running on the multi road

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
425/65R22.5	18	162	K	12.25	---	---	4750	760	1124	422	17.5	TRA
425/65R22.5	20	165	J/K	12.25	---	---	5150	825	1124	422	17.5	ETRT0



Radial truck tire (Regional All position)

AW-09

Suitable for all position axle of buses and medium trucks

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
265/70R19.5	14	136/134	M	7.50	2120	725	2240	725	867	262	13.5	ETRT0
265/70R19.5	16	140/138	L	7.50	2300	775	2500	775	867	262	13.5	ETRT0
265/70R19.5	18	143/141	J	7.50	2575	850	2725	850	867	262	13.5	ETRT0
285/70R19.5	16	144/142	M	8.25	2650	800	2800	800	895	283	14.0	ETRT0
285/70R19.5	18	146/144	M	8.25	2800	900	3000	900	895	283	14.0	ETRT0
285/70R19.5	18	150/147	J	8.25	3075	900	3350	900	895	283	14.0	ETRT0
255/70R22.5	14	136/133	M	7.50	2060	700	2240	700	930	255	14.0	ETRT0
255/70R22.5	16	140/137	M	7.50	2300	830	2500	830	930	255	14.0	TRA
275/70R22.5	16	148/145	M	8.25	2900	900	3150	900	958	276	14.5	ETRT0
275/70R22.5	18	150/148	M	8.25	3150	900	3350	900	958	276	14.5	ETRT0



Radial Truck Tire

AP-09

Suitable for all position axle of buses and trucks

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
902.5	12	133/131	M	6.75	1950	720	2060	720	974	229	13.5	TRA
902.5	14	136/134	M	6.75	2120	830	2240	830	974	229	13.5	TRA
10R22.5	14	141/139	M	7.50	2430	790	2575	790	1019	254	14.0	TRA
10R22.5	14	144/142	L	7.50	2650	850	2800	850	1019	254	14.0	ETRT0
10R22.5	16	144/142	L	7.50	2650	900	2800	900	1019	254	14.0	GB



Radial Truck Tire

AP-800

Suitable for all position axle of trucks running on the multi road

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
12.00R24	18	156/153	K	8.50	3650	775	4000	775	1.226	313	17.0	ETRT0
12.00R24	20	160/156	K	8.50	4000	850	4500	850	1.226	313	17.0	ETRT0



Radial truck tire (Regional Drive)

DRV-OSIII

- ◀ New technology for tire to reduce the weight.
- ◀ Low eccentric wear.
- ◀ Low fuel consumption.
- ◀ Good braking and grip on the road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm		
					Dual	Single						
10.00R20	16	146/143	L	7.5	2725	830	3000	830	1054	278	17.5	TRA
10.00R20	18	149/146	K	7.5	3000	930	3250	930	1054	278	17.5	GB



Radial truck tire (Regional All position)

AP-100e+

- ◀ Good handling.
- ◀ Low fuel consumption.
- ◀ Certified by U.S.A SmartWay.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
11R22.5	14	144/142	M	8.25	2650	720	2800	720	1054	279	14.5	TRA
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1054	279	14.5	TRA
11R24.5	14	146/143	M	8.25	2725	720	3000	720	1104	279	14.5	TRA
11R24.5	16	149/146	M	8.25	3000	830	3250	830	1104	279	14.5	TRA
295/75R22.5	14	144/141	M	9.00	2575	760	2800	760	1014	298	14.5	TRA
295/75R22.5	16	146/143	M	9.00	2725	830	3000	830	1014	298	14.5	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1050	283	14.5	TRA
285/75R24.5	16	147/144	M	8.25	2800	830	3075	830	1050	283	14.5	TRA



Radial truck tire (Regional Trailer)

TR-09e+

- ◀ Low fuel consumption.
- ◀ Certified by U.S.A SmartWay.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
11R22.5	14	144/142	M	8.25	2650	720	2800	720	1054	279	10	TRA
11R22.5	16	146/143	M	8.25	2725	830	3000	830	1054	279	10	TRA
11R24.5	14	146/143	M	8.25	2725	720	3000	720	1104	279	10.75	TRA
11R24.5	16	149/146	M	8.25	3000	830	3250	830	1104	279	10.75	TRA
295/75R22.5	14	144/141	M	9.00	2575	760	2800	760	1014	298	10	TRA
295/75R22.5	16	146/143	M	9.00	2725	830	3000	830	1014	298	10	TRA



Radial Truck Tire(Regional)

STR-29e+

- ◀ Wide shoulder ribs reduce shoulder step wear.
- ◀ Each size is manufactured with a specially tread depth to meet a greater range of application.
- ◀ Optimized the footprint for long and even wear.
- ◀ Strong carcass materials help promote tire durability and provide tire retreadability.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
11R22.5	14	144/142	L	8.25	2650	720	2800	720	1056	279	18.3	TRA
11R22.5	16	146/143	L	8.25	2725	830	3000	830	1056	279	18.3	TRA
11R24.5	14	146/143	M	8.25	2725	720	3000	720	1106	279	18.3	TRA
11R24.5	16	149/146	L	8.25	3000	830	3250	830	1106	279	18.3	TRA
255/70R22.5	14	138/134	M	7.50	2120	760	2360	760	930	255	14.3	TRA
255/70R22.5	16	140/137	L	7.50	2300	830	2500	830	930	255	14.3	TRA
285/75R24.5	14	144/141	M	8.25	2575	760	2800	760	1057	283	18.3	TRA
285/75R24.5	16	147/144	L	8.25	2725	830	3000	830	1057	283	18.3	TRA
295/75R22.5	14	144/141	L	9.00	2575	760	2800	760	1017	298	18.3	TRA
295/75R22.5	16	146/143	L	9.00	2800	830	3075	830	1017	298	18.3	TRA



ON&OFF ROAD

AP-403 PAGE 61

DRV-403 PAGE 61

AP-09 I PAGE 62

AP-09 IV PAGE 62

DRV-OSVI PAGE 63

AT-08CC PAGE 63

AP-09III PAGE 64

DRV-960 PAGE 64

DRV-OSVIII PAGE 65

APW-095 PAGE 65

AT-08CCe+ PAGE 66





Radial Truck Tire (On&Off Road)

AP-403 NEW

Suitable for all position axle of trucks under all kinds of working conditions.

- Thick sidewall design protects against sidewall impacts and bruises.
- Stone rejection design protects groove bottom from stone puncture.
- HAT technology: Low heat generation

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
295/80R22.5	16	152/148	K	9.00	3150	850	3550	850	1044	298	15.0	ETRTO
295/80R22.5	18	152/149	K	9.00	3250	900	3550	900	1044	298	15.0	GB
12.00R24	18	156/153	K	8.50	3650	775	4000	775	1226	313	15.5	ETRTO
12.00R24	20	160/156	K	8.50	4000	850	4500	850	1226	313	15.5	ETRTO



Radial Truck Tire (On&Off Road)

DRV-403 NEW

Suitable for drive axle of trucks under all kinds of working conditions.

- Thick sidewall design protects against sidewall impacts and bruises.
- Stone rejection design protects groove bottom from stone puncture.
- HAT technology: Low heat generation.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
12.00R24	18	156/153	K	8.50	3650	775	4000	775	1226	313	19.0	ETRTO
12.00R24	20	160/156	K	8.50	4000	850	4500	850	1226	313	19.0	ETRTO
295/80R22.5	16	152/148	K	9.00	3150	850	3550	850	1044	298	18.5	ETRTO
295/80R22.5	18	152/149	K	9.00	3250	900	3550	900	1044	298	18.5	GB
12R22.5	16	152/148	K	9.00	3150	850	3550	850	1044	300	19.0	ETRTO
12R22.5	18	152/149	K	9.00	3250	930	3550	930	1085	300	19.0	GB



Radial Truck Tire (On&Off Road all position)

AP-09 I

- Pattern block design reduces shoulder heat.
- Wide running surface and higher saturation design improves the wear mileage.
- Powerful traction, grip and climbing performance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
10.00R20	18	149/146	K	7.5	3000	930	3250	930	1054	278	16.0	GB
11R22.5	16	146/143	J	8.25	2725	830	3000	830	1054	279	19.0	TRA
11R22.5	16	148/145	J	8.25	2900	850	3150	850	1050	279	19.0	ETRTO
325/95R24	22	162/160	K	9.00	4500	850	4750	850	1228	325	18	ETRTO



Radial Truck Tire (On&Off Road all position)

AP-09IV

- Wide and deep tread grooves for long tire life.
- Excellent cutting and chipping resistance.
- Robust tread and high traction on rough surfaces.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
325/95R24	22	162/160	K	9.00	4500	850	4750	850	1228	325	23.0	ETRTO



Radial Truck Tire (On/Off Road drive)

DRV-OSVI

- ▶ Good traction.
- ▶ Chip, cut and abrasion resistance tread compound.
- ▶ Deep tread depth increases mileage and service life.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Dual kPa	Single kg	Single kPa				
10.00R20	18	149/146	K	7.5	3000	930	3250	930	1054	278	16.0	GB



Radial Truck Tire (On/Off Road all position)

AT-08CC

- ▶ Typical combined pattern.
- ▶ Cut resistance compound.
- ▶ Good braking and grip.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Dual kPa	Single kg	Single kPa				
9.00R20	14	141/139	K	7.0	2430	790	2575	790	1019	259	15.0	TRA
9.00R20	16	144/142	K	7.0	2650	900	2800	900	1019	259	15.0	GB
10.00R20	16	146/143	K	7.5	2725	830	3000	830	1054	278	15.5	TRA
10.00R20	18	149/146	K	7.5	3000	930	3250	930	1054	278	15.5	GB
11.00R20	16	150/147	K	8.0	3075	850	3350	850	1085	293	16.5	GB
11.00R20	18	152/149	K	8.0	3250	930	3550	930	1085	293	16.5	GB
12.00R20	18	154/151	K	8.5	3450	830	3750	830	1125	315	17.0	TRA
12.00R24	18	156/153	K	8.50	3650	775	4000	775	1226	313	17.0	ETRTD
12.00R24	20	160/156	K	8.50	4000	850	4500	850	1226	313	17.0	ETRTD
11R22.5	14	144/142	K	8.25	2650	720	2800	720	1054	279	15.0	TRA
11R22.5	16	146/143	K	8.25	2725	830	3000	830	1054	279	15.0	TRA
11R22.5	16	148/145	K	8.25	2900	850	3150	850	1050	279	15.0	ETRTD
12R22.5	16	152/148	K	9.00	3150	850	3550	850	1084	300	17.0	ETRTD
11R24.5	14	146/143	K	8.25	2725	720	3000	720	1104	279	15.5	TRA
11R24.5	16	149/146	K	8.25	3000	830	3250	830	1104	279	15.5	TRA
12R24.5	16	152/149	K	9.00	3250	830	3550	830	1135	300	16.0	TRA
12R24.5	18	154/151	K	9.00	3450	930	3750	930	1135	300	16.0	GB
255/70R22.5	16	140/137	M	7.50	2300	830	2500	830	930	255	12.7	TRA
315/80R22.5	18	154/150	M	9.00	3350	825	3750	825	1076	312	17.5	ETRTD
315/80R22.5	20	156/150	L	9.00	3350	850	4000	850	1076	312	17.5	ETRTD
315/80R22.5	22	158/150	K	9.00	3350	900	4250	900	1076	312	17.5	ETRTD



Radial Truck Tire (On/Off Road all position)

AP-09III

- ▶ Typical combined pattern.
- ▶ Cut resistance compound.
- ▶ Good braking and grip.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Dual kPa	Single kg	Single kPa				
10.00R20	16	146/143	K	7.5	2725	830	3000	830	1054	278	17.5	TRA
10.00R20	18	149/146	K	7.5	3000	930	3250	930	1054	278	17.5	GB
13R22.5	18	156/150	K	9.75	3350	875	4000	875	1124	320	17.5	ETRTD
13R22.5	20	158/156	K	9.75	4000	900	4250	900	1124	320	17.5	ETRTD



Radial Truck Tire (On/Off Road drive)

DRV-960

- ▶ Deep and rigid block design for long life and good traction.
- ▶ Cut resistance compound.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Dual kPa	Single kg	Single kPa				
12.00R24	18	156/153	K	8.50	3650	775	4000	775	1226	313	21.0	ETRTD
12.00R24	20	160/156	K	8.50	4000	850	4500	850	1226	313	21.0	ETRTD



Radial Truck Tire (On&Off Road drive)

DRV-OSVIII

- ◀ Deep and rigid block design for long life and good traction.
- ◀ Cut resistance compound.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
12R22.5	16	152/148	K	9.00	3150	850	3550	850	1084	300	21.0	ETRT0
12R22.5	18	152/149	J	9.00	3250	930	3550	930	1085	300	21.0	GR
13R22.5	18	156/150	K	9.75	3350	875	4000	875	1124	320	21.0	ETRT0
9.5R17.5	14	129/127	K	6.75	1750	750	1850	750	842	240	16.0	ETRT0
9.5R17.5	18	143/141	K	6.75	2575	875	2725	875	842	240	16.0	ETRT0
265/70R19.5	16	140/138	K	7.50	2360	775	2500	775	867	262	15.5	ETRT0
265/70R19.5	18	143/141	K	7.50	2575	850	2725	850	867	262	15.5	ETRT0
295/80R22.5	16	152/148	K	9.00	3150	850	3550	850	1044	298	22.0	ETRT0
295/80R22.5	18	152/149	K	9.00	3350	900	3550	900	1044	298	22.0	GR
315/80R22.5	18	154/150	M	9.00	3350	825	3750	825	1076	312	21.0	ETRT0
315/80R22.5	20	156/150(154/150)	L(M)	9.00	3350	850	4000	850	1076	312	21.0	ETRT0



Radial Truck Tire (On&Off Road trailer)

APW-095

- ◀ Typical combined pattern.
- ◀ Cut resistance compound.
- ◀ Good braking and grip.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
385/65R22.5	18	158	K	11.75	---	---	4250	850	1072	389	16.5	ETRT0
385/65R22.5	20	160	J	11.75	---	---	4500	900	1072	389	16.5	ETRT0
425/65R22.5	18	162	K	12.25	---	---	4750	760	1124	422	17.5	TRA
425/65R22.5	20	165	J/K	12.25	---	---	5150	825	1124	422	17.5	ETRT0
445/65R22.5	20	168	J/K	13.00	---	---	5600	830	1150	444	18.0	TRA
445/65R22.5	20	169	J	13.00	---	---	5800	900	1150	444	18.0	ETRT0



Radial Truck Tire (On&Off Road all position)

AT-08CCe+

- ◀ Typical combined pattern.
- ◀ Cut resistance compound.
- ◀ Good braking and grip.
- ◀ Certified by U.S.A SmartWay.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
11R22.5	16	146/143	K	8.25	2725	830	3000	830	1054	279	15.0	TRA
11R24.5	16	149/146	K	8.25	3000	830	3250	830	1104	279	15.5	TRA





OFF ROAD

DRV986	PAGE 68	DRV-MIII	PAGE 69
DRV-MIV	PAGE 68	DRV-OS I	PAGE 70
DRV-M I	PAGE 69	DRV-950	PAGE 70



Radial Truck Tire (Off Road Drive)



DRV986

- Suitable for hilly area and mine etc., off road conditions
- ◀ Off-road pattern block ensures powerful traction and good self-cleaning ability.
 - ◀ Chip, cut and abrasion resistance tread compound.
 - ◀ Deep tread depth increases mileage and service life.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
315/80R22.5	18	154/150	F	9.00	3350	825	3750	850	1076	312	24.5	ETRTO
315/80R22.5	20	156/150	F	9.00	3350	850	4000	850	1076	312	24.5	ETRTO



Radial Truck Tire (Off Road Drive)



DRV-MIV

- Suitable for hilly area and mine etc., off road conditions
- ◀ Off-road pattern block ensures powerful traction and good self-cleaning ability.
 - ◀ Chip, cut and abrasion resistance tread compound.
 - ◀ Deep tread depth increases mileage and service life.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
12.00R24	18	156/153	F	8.50	3650	775	4000	775	1226	313	24.0	ETRTO
12.00R24	20	160/156	F	8.50	4000	850	4500	850	1226	313	24.0	ETRTO
295/80R22.5	16	152/148	F	9.00	3150	850	3550	850	1044	298	22.0	ETRTO
295/80R22.5	18	152/149	F	9.00	3250	900	3550	900	1050	298	22.0	GB



Radial Truck Tire(Off Road Drive)

DRV-M I

- ◀ Good traction resistance.
- ◀ Chip,cut and abrasion resistance tread compound.
- ◀ Deep tread depth increases mileage and service life.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Dual kPa	Single kg	Single kPa				
10.00R20	18	149/146	F	7.5	3000	930	3250	930	1065	278	20.0	GB
11R22.5	16	148/145	J	8.25	2900	850	3150	850	1050	279	20.0	ETRTO
275/80R22.5	16	149/146	J	8.25	3000	850	3250	850	1012	276	20.0	ETRTO
295/80R22.5	16	152/148	F	9.00	3150	850	3550	850	1044	290	20.0	ETRTO



Radial Truck Tire(Off Road Drive)

DRV-M III

- ◀ Good traction resistance.
- ◀ Chip,cut and abrasion resistance tread compound.
- ◀ Deep tread depth increases mileage and service life.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Dual kPa	Single kg	Single kPa				
11R22.5	16	148/145	J	8.25	2900	850	3150	850	1050	279	20.0	ETRTO
275/80R22.5	16	149/146	J	8.25	3000	850	3250	850	1012	276	20.0	ETRTO
295/80R22.5	16	152/148	F	9.00	3150	850	3550	850	1044	290	20.0	ETRTO



Radial Truck Tire(Off Road Drive)

DRV-OS I

- ◀ Good traction resistance.
- ◀ Chip,cut and abrasion resistance tread compound.
- ◀ Deep tread depth increases mileage and service life.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Dual kPa	Single kg	Single kPa				
10.00R20	16	146/143	J	7.5	2725	830	3000	830	1054	278	20.0	TRA
10.00R20	18	149/146	J	7.5	3000	930	3250	930	1054	278	20.0	GB
11.00R20	16	150/147	F	8.0	3075	830	3350	830	1085	293	20.0	GB
11.00R20	18	152/149	F	8.0	3250	930	3550	930	1085	293	20.0	GB
12.00R20	18	154/151	F	8.5	3450	830	3750	830	1125	315	21.0	TRA



Radial Truck Tire (Short Haul)

DRV-950

- ◀ Drive axle for on/off road conditions.
- ◀ Deep and rigid block design for good traction.
- ◀ Cut resistance compound.
- ◀ Used for logging conditions where high traction required.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Dual kPa	Single kg	Single kPa				
11R22.5	14	144/142	K	8.25	2650	720	2800	720	1065	279	23.0	TRA
11R22.5	16	146/143	K	8.25	2725	830	3000	830	1065	279	23.0	TRA
11R24.5	14	146/143	F/G	8.25	2725	720	3000	720	1116	279	25.0	TRA
11R24.5	16	149/146	F/G	8.25	3000	830	3250	830	1116	279	25.0	TRA
295/75R22.5	16	146/143	J	9.00	2725	830	3000	830	1026	298	23.0	TRA
285/75R24.5	16	147/144	J	8.25	2800	830	3075	830	1062	283	23.0	TRA



LIGHT TRUCK

AT651	PAGE 72	AP-09	PAGE 75
AP-100X	PAGE 72	DRV-OS V	PAGE 76
AP-09IV	PAGE 73	DRV-OSIX	PAGE 76
AP-100VIII	PAGE 73	AT-08CC	PAGE 77
AP-09II	PAGE 74	DRV-OSVII	PAGE 77
AW-09	PAGE 74	DRV-MV	PAGE 78
AP-09	PAGE 75	AP-100IV	PAGE 78



Radial Truck Tire (Regional)

AT651

- Suitable for all position axle of light trucks
- Thick sidewall design protects against sidewall impacts and bruises.
- Zig-zag grooves for excellent handling.
- HAT technology: low heat generation.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
7.50R16LT	12	120/116	M	6.00G	1250	670	1400	670	805	215	11.0	GB
7.50R16LT	14	122/118	M	6.00G	1320	770	1500	770	805	215	11.0	GB



Radial Truck Tire (Regional all position)

AP-100 X

- Extra wide tread design for high mileage and even wear.
- Zig-zag grooves for excellent handling.
- Optimize structure design.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
7.50R15LT	8	110/105	L	6.00G	925	460	1060	460	780	215	13.0	GB
7.50R15LT	10	115/110	L	6.00G	1060	560	1215	560	780	215	13.0	GB
7.50R16LT	12	120/116	M	6.00G	1250	670	1400	670	805	215	13.0	GB
7.50R16LT	14	122/118	M	6.00G	1320	770	1500	770	805	215	13.0	GB
215/75R17.5	14	126/124	M	6.00	1600	700	1700	700	767	211	14.5	ETRTO
215/75R17.5	16	130/133	J	6.00	2060	850	2180	850	767	211	14.5	ETRTO
235/75R17.5	14	132/130	M	6.75	1900	775	2000	775	797	233	14.5	ETRTO
235/75R17.5	16	141/140	J	6.75	2500	850	2575	850	797	233	14.5	ETRTO
235/75R17.5	18	143/141	J	6.75	2575	875	2725	875	797	233	14.5	ETRTO
225/80R17.5	14	123/122	L	6.75	1500	700	1550	700	805	226	16.0	JATMA



Radial Truck Tire (On/Off Road all position)

AP-09IV

- Wide and deep tread grooves for long tire life.
- Excellent cutting and chipping resistance.
- Robust tread and high traction on rough surfaces.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
7.50R16LT	14	122/118	F	6.00G	1320	770	1500	770	815	215	18.0	GB



Radial truck tire (Regional all position)

AP-100VIII

Suitable for small trucks running on the high-grade road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
7.00R16LT	12	115/110	M	5.50F	1060	670	1215	670	775	200	10.5	GB
7.00R16LT	14	118/114	L	5.50F	1180	770	1320	770	775	200	10.5	GB



Radial truck tire (Regional all position)

AP-09 II

Suitable for medium trucks running on the high-grade road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
7.50R16LT	12	120/116	M	6.00G	1250	670	1400	670	805	215	11.5	GB
7.50R16LT	14	122/118	M	6.00G	1320	770	1500	770	805	215	11.5	GB
8.25R16LT	12	123/119	M	6.50H	1360	560	1550	560	855	235	12.5	GB
8.25R16LT	14	126/122	L	6.50H	1500	670	1700	670	855	235	12.5	GB
8.25R16LT	16	128/124	L	6.50H	1600	770	1800	770	855	235	12.5	GB
9.5R17S	14	129/127	M	6.75	1750	750	1850	750	842	240	12.0	ETRTO
9.5R17S	18	143/141	M/J	6.75	2575	875	2725	875	842	240	12.0	ETRTO



Radial truck tire (Regional all position)

AW-09

Suitable for medium trucks running on the high-grade road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
205/75R17.5	14	124/122	M	6.00	1500	750	1600	750	753	204	12.5	ETRTO
225/70R19.5	12	125/123	M	6.75	1550	660	1650	660	811	226	12.5	TRA
225/70R19.5	14	128/126	M	6.75	1700	760	1800	760	811	226	12.5	TRA
245/70R19.5	12	129/127	M	7.50	1750	660	1850	660	839	248	13.0	TRA
245/70R19.5	14	133/131	M	7.50	1950	760	2060	760	839	248	13.0	TRA
245/70R19.5	14	133/131	M	7.50	1950	750	2060	750	839	248	13.0	ETRTO
245/70R19.5	16	136/134	L/M	7.50	2120	825	2240	825	839	248	13.0	ETRTO



Radial Truck Tire (Regional all position)

AP-09

Suitable for medium trucks running on the high-grade road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Single kPa				
215/75R17.5	14	126/124	L/M	6.00	1600	700	1700	767	211	12.5
215/75R17.5	16	135/133	J/L	6.00	2060	850	2180	850	767	12.5



Radial Truck Tire (Regional all position)

AP-09

Suitable for medium trucks running on the high-grade road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Single kPa				
235/75R17.5	14	132/130	L/M	6.75	1900	775	2000	775	797	13.0
235/75R17.5	16	141/140	J	6.75	2500	850	2575	850	797	13.0
235/75R17.5	18	143/141	J	6.75	2575	875	2725	875	797	13.0



Radial truck tire (Regional Drive)

DRV-OS V

- ◀ Suitable for medium trucks running on the high-grade road.
- ◀ Good braking and grip on wet road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Single kPa				
225/70R19.5	12	125/123	L	6.75	1550	660	1650	660	811	226
225/70R19.5	14	128/126	L	6.75	1700	760	1800	760	811	226
245/70R19.5	14	133/131	M	7.50	1950	760	2060	760	839	248
245/70R19.5	16	136/134	M	7.50	2120	825	2240	825	839	248
215/75R17.5	12	124/123	M	6.00	1550	675	1600	675	767	211
215/75R17.5	14	126/124	L/M	6.00	1600	700	1700	700	767	211
215/75R17.5	16	135/133	J/L	6.00	2060	850	2180	850	767	211
235/75R17.5	14	132/130	L/M	6.75	1900	775	2000	775	797	233
235/75R17.5	16	141/140	J	6.75	2500	850	2575	850	797	233
235/75R17.5	18	143/141	J	6.75	2575	875	2725	875	797	233



Radial truck tire (On&Off Road Drive)

DRV-OSIX

- ◀ Suitable for medium trucks running on the normal road.
- ◀ Good braking and grip on wet road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	Single kPa				
7.50R16LT	12	120/116	M	6.00G	1250	670	1400	670	805	215
7.50R16LT	14	122/118	M	6.00G	1320	770	1500	770	805	215
245/70R19.5	14	133/131	M	7.50	1950	760	2060	760	839	248
245/70R19.5	16	136/134	L	7.50	2120	825	2240	825	839	248



Radial Truck Tire (On/Off Road all position)

AT-08CC

- ◀ Suitable for medium trucks running on the normal road.
- ◀ Typical combined pattern.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
700R16LT	12	115/110	M	5.50F	1060	670	1215	670	775	200	11.5	GB
700R16LT	14	118/114	L	5.50F	1180	770	1320	770	775	200	11.5	GB
750R16LT	12	120/116	M	6.00G	1250	670	1400	670	805	215	12.5	GB
750R16LT	14	123/118	M	6.00G	1320	770	1500	770	805	215	12.5	GB
8.25R16LT	14	126/122	L	6.50H	1500	670	1700	670	855	235	13.5	GB
8.25R16LT	16	128/124	L	6.50H	1600	770	1800	770	855	235	13.5	GB



Radial Truck Tire (On/Off Road Drive)

DRV-OSVII

- ◀ Suitable for medium trucks running on the normal road.
- ◀ Typical combined pattern.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
7.50R16LT	12	120/116	M	6.00G	1250	670	1400	670	805	215	13.5	GB
7.50R16LT	14	122/118	M	6.00G	1320	770	1500	770	805	215	13.5	GB
8.25R16LT	14	126/122	K	6.50H	1500	670	1700	670	855	235	14.5	GB
8.25R16LT	16	128/124	K	6.50H	1600	770	1800	770	855	235	14.5	GB



Radial Truck Tire (Off Road all position)

DRV-M V

- ◀ Off-road pattern block ensures powerful traction and good self-cleaning ability.
- ◀ Chip, cut and abrasion resistance tread compound.
- ◀ Deep tread depth increases mileage and service life.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
8.25R16LT	16	128/124	F	6.50H	1600	770	1800	770	865	235	18.0	GB



Radial Truck Tire (Regional all position)

AP-100IV

- ◀ Extra wide tread design for high mileage and even wear.
- ◀ Zig-zag grooves for excellent handling.
- ◀ Optimize structure design.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
225/80R17.5	14	123/122	L	6.75	1500	700	1550	700	805	226	15.0	JATMA

COACH&URBAN

LAU609 PAGE 80

AP-200 PAGE 80

AP-100 X PAGE 81

APU-02 PAGE 81



Radial bus tire (Urban all position)



LAU609

- ◀ Enhanced sidewall ensures high safety.
- ◀ Tire strength is increased by 35%, with application of ST steel cord.
- ◀ Tire bead cracking is prevented, with application fiber layer in bead area.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
275/70R22.5	16	148/146	J	8.25	2900	900	3150	900	958	276	21	ETRT0
275/70R22.5	16	148/146 (152/148)	J(E)	8.25	2900	900	3150	900	958	276	21.0	ETRT0
275/70R22.5	18	150/148(152/148)	J(E)	8.25	3150	900	3350	900	958	276	21.0	ETRT0



Radial bus tire (Coach all position)



AP-200

- ◀ Suitable for all axle of bus riding on highway.
- ◀ Long life.
- ◀ Good grip performance.
- ◀ low eccentric wear.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	17.0	ETRT0
295/80R22.5	18	152/149	M	9.00	3250	900	3550	900	1044	298	17.0	GB



Radial bus tire (small bus all position)

AP-100 X

- ◀ Extra wide tread design for high mileage and even wear.
- ◀ Zig-zag grooves for excellent handling.
- ◀ Optimize structure design.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
75.0R15LT	8	110/105	L	6.00G	925	460	1060	460	780	215	13.0	GB
75.0R15LT	10	115/110	L	6.00G	1060	560	1215	560	780	215	13.0	GB
75.0R16LT	12	120/116	M	6.00G	1250	670	1400	670	805	215	13.0	GB
75.0R16LT	14	123/118	M	6.00G	1320	770	1500	770	805	215	13.0	GB
215/75R17.5	14	126/124	M	6.00	1600	700	1700	700	767	211	14.5	ETRTO
215/75R17.5	16	135/133	J	6.00	2060	850	2180	850	767	211	14.5	ETRTO
235/75R17.5	14	132/130	M	6.75	1900	775	2000	775	797	233	14.5	ETRTO
235/75R17.5	16	141/140	J	6.75	2500	850	2575	850	797	233	14.5	ETRTO
235/75R17.5	18	143/141	J	6.75	2575	875	2725	875	797	233	14.5	ETRTO
225/80R17.5	14	123/122	L	6.75	1500	700	1550	700	805	226	16.0	JATMA



Radial bus tire (Urban all position)

APU-02

- ◀ Enhanced sidewall ensures high safety.
- ◀ Long service life.
- ◀ Typical used for urban bus.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kPa	kg	kPa				
215/75R17.5	14	126/124	J	6.00	1600	700	1700	700	767	211	14.5	ETRTO
215/75R17.5	16	127/124	J	6.00	1600	830	1750	830	767	211	14.5	GB
215/75R17.5	18	135/133	J	6.00	2060	850	2180	850	767	211	14.5	ETRTO



