



PRODUCT CATALOG 2023

Tire Direct 
La nueva generación





Forceland is a tire supplier specializing in UHP and On/Off Road Light Truck segments, providing the most cost effective UHP, A/T, R/T tires as well as the most valuable services.



Tire Direct
La nueva generación



Table of Content

01 VITALITY F22P1-P6

02 VITALITY H/TP7-P9

03 VINTEK F35P10-P11

04 REBEL HAWK A/TP12-P14

05 REBEL HAWK R/TP15-P16

VITALITY F22

- Luxury & Comfort
- Asymmetric UHP Tread Pattern Design
- Advanced Silica & Fuel-Eco Compound
- Computer Optimized Pitches For Noise Reduction
- Excel Performance On Wet & Dry roads
- Precise Control With High Speed Confidence



VITALITY F22


SAFETY



HANDLING



COMFORT



RESISTANCE



SILENCE

INCH	SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
13	175/70R13	82T	5.0J	4.5J—6.0J	7.0	475	300
	165/55R14	72H	5.0J	4.5J—6.0J	6.5	355	300
	165/60R14	75H	5.0J	4.5J—6.0J	7.3	387	300
14	185/60R14	82H	5.5J	5.0J—6.5J	7.3	475	300
	155/65R14	75T	5.0J	4.5J—5.5J	7.3	387	300
	165/65R14	79T	5.0J	4.5J—6.0J	7.3	437	300
	175/65R14	82H	5.0J	5.0J—6.0J	7.0	475	300
	185/65R14	86H	5.5J	5.0J—6.5J	7.3	530	300
	165/70R14	81T	5.0J	4.0J—5.5J	7.3	462	300
	175/70R14	84T	5.0J	4.5J—6.0J	7.3	500	300
	185/70R14	88T	5.5J	4.5J—6.0J	7.3	560	300
	165/50R15	76V XL	5.0J	4.5J—6.0J	6.5	400	350
	195/50R15	82V	6.0J	5.5J—7.0J	7.0	475	300
15	165/55R15	75H	5.0J	4.5J—6.0J	6.5	387	300
	185/55R15	82V	6.0J	5.0J—6.5J	7.3	475	300
	195/55R15	85V	6.0J	5.5J—7.0J	7.3	515	300
	185/60R15	84H	5.5J	5.0J—6.5J	7.3	500	300
	195/60R15	88V	6.0J	5.5J—7.0J	7.7	560	300
	175/65R15	84H	5.0J	5.0J—6.0J	7.3	500	300
	185/65R15	88H	5.5J	5.0J—6.5J	7.3	560	300
	195/65R15	91V	6.0J	5.5J—7.0J	7.3	615	300
	205/65R15	94V	6.0J	5.5J—7.5J	7.7	670	300
	* 215/40R16	86W XL	7.5J	7.0J—8.5J	7.7	530	350
16	165/45R16	74V XL	5.5J	5.0J—6.0J	6.5	375	350
	195/45R16	87V XL	6.5J	6.0J—7.5J	7.7	500	350
	205/45ZR16	86W XL	7.0J	6.5J—7.5J	7.7	545	350
	165/50R16	77V XL	5.0J	4.5J—6.0J	6.5	412	350
	* 185/50R16	81V	6.0J	5.0J—6.5J	7.3	462	300
	195/50R16	88V XL	6.0J	5.5J—7.0J	7.7	560	350
	205/50R16	87V	6.5J	5.5J—7.5J	7.7	545	300
	185/55R16	83V	6.0J	5.0J—6.5J	7.3	487	300
	195/55R16	87V	6.0J	5.5J—7.0J	7.3	545	300
	205/55R16	91V	6.5J	5.5J—7.5J	7.3	615	300
	205/55R16	94V XL	6.5J	5.5J—7.5J	7.3	670	350
	215/55ZR16	97V XL	7.0J	6.0J—7.5J	7.7	730	350
	225/55ZR16	95W	7.0J	6.0J—8.0J	7.7	690	300
	205/60R16	92H	6.0J	5.5J—7.5J	7.7	630	300
	215/60R16	95H	6.5J	6.0J—7.5J	7.7	690	300
	215/60R16	99V XL	6.5J	6.0J—7.5J	7.7	775	350
	* 195/65R16	92H	6.5J	5.0J—7.5J	7.7	630	300

Size with "*" is under developing, will be available soon.
 Data can be changed by manufacturer without prior notice.

VITALITY F22



SAFETY



HANDLING



COMFORT



RESISTANCE



SILENCE

INCH	SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
17	205/40RZ17	84W XL	7.5J	7.0J—8.0J	7.7	500	350
	* 215/40R17	87W XL	7.5J	7.0J—8.5J	7.7	545	350
	* 255/40R17	94W	9.0J	8.5J—10.0J	7.7	670	300
	195/45ZR17	85W XL	6.5J	6.0J—7.5J	7.7	515	350
	205/45ZR17	88W XL	7.0J	6.5J—7.5J	7.7	560	350
	215/45ZR17	91W XL	7.0J	7.0J—8.0J	7.7	615	350
	225/45ZR17	94Y XL	7.5J	7.0J—8.5J	7.7	670	350
	235/45ZR17	97W XL	8.0J	7.5J—9.0J	7.7	730	350
	245/45ZR17	95W	8.0J	7.5J—9.0J	7.7	690	300
	* 255/45R17	102W XL	8.5J	8.0J—9.5J	7.7	850	350
	205/50ZR17	93W XL	6.5J	5.5J—7.0J	7.7	650	350
	215/50ZR17	95W XL	7.0J	6.0J—7.5J	7.7	690	350
	225/50ZR17	98W XL	7.0J	6.0J—8.0J	7.7	750	350
	235/50ZR17	96W	7.5J	6.5J—8.5J	7.7	710	300
	205/55ZR17	95W XL	6.5J	5.5J—7.5J	7.7	690	350
	215/55ZR17	98W XL	7.0J	6.0J—7.5J	7.7	750	350
	225/55ZR17	101W XL	7.0J	6.0J—8.0J	7.7	825	350
	235/55ZR17	103W XL	7.5J	6.5J—8.5J	7.7	875	350
	215/60R17	96V	6.5J	6.0J—7.5J	7.7	710	300
18	* 245/35R18	92W XL	8.5J	8.0J—9.5J	7.7	630	350
	* 255/35R18	94W XL	9.0J	8.5J—10.0J	7.7	670	350
	* 265/35R18	97W XL	9.5J	9.0J—10.5J	7.7	730	350
	* 275/35R18	99W XL	9.5J	9.0J—11.0J	7.7	775	350
	* 285/35R18	101W XL	10.0J	9.5J—11.0J	7.7	825	350
	215/40ZR18	89W XL	7.5J	7.0J—8.5J	7.7	580	350
	225/40ZR18	92Y XL	8.0J	7.5J—9.0J	7.7	630	350
	235/40ZR18	95W XL	8.5J	8.0J—9.5J	7.7	690	350
	245/40ZR18	97W XL	8.5J	8.0J—9.5J	7.7	730	350
	* 265/40R18	101W XL	9.5J	9.0J—10.5J	7.7	825	350
	* 275/40R18	103W XL	9.5J	9.0J—11.0J	7.7	875	350
	215/45ZR18	93W XL	7.0J	7.0J—8.0J	7.7	650	350
	225/45ZR18	95W XL	7.5J	7.0J—8.5J	7.7	690	350
	235/45ZR18	98W XL	8.0J	7.5J—9.0J	7.7	750	350
	245/45ZR18	100Y XL	8.0J	7.5J—9.0J	7.7	800	350
	* 255/45R18	103W XL	8.5J	8.0J—9.5J	7.7	875	350
	* 275/45R18	107W XL	9.0J	8.5J—10.5J	7.7	975	350
	225/50ZR18	95W	7.0J	6.0J—8.0J	7.7	690	300
	235/50ZR18	101W XL	7.5J	6.5J—8.5J	7.7	825	350

Size with *** is under developing, will be available soon.
Data can be changed by manufacturer without prior notice.

VITALITY F22


SAFETY



HARDLINE



COMFORT



RESISTANCE



SILENCE

INCH	SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
18	* 245/50R18	104W XL	7.5J	7.0J—8.5J	7.7	900	350
	215/55R18	95V	7.0J	6.0J—7.5J	7.7	690	300
	225/55R18	98V	7.0J	6.0J—8.0J	7.7	750	300
	235/55R18	104V XL	7.5J	6.5J—8.5J	7.7	900	350
	* 255/55R18	109V XL	8.0J	7.0J—9.0J	7.7	1030	350
	* 235/60R18	107V XL	7.0J	6.5J—8.5J	7.7	975	350
19	* 265/30R19	93W XL	9.5J	9.0J—10.0J	7.7	650	350
	* 275/30R19	96W XL	9.5J	9.0J—10.0J	7.7	710	350
	215/35ZR19	85W XL	7.5J	7.0J—8.5J	7.7	515	350
	225/35ZR19	88W XL	8.0J	7.5J—9.0J	7.7	560	350
	235/35ZR19	91W XL	8.5J	8.0J—9.5J	7.7	615	350
	245/35ZR19	93W XL	8.5J	8.0J—9.5J	7.7	650	350
	255/35ZR19	96W XL	9.0J	8.5J—10.0J	7.7	710	350
	* 265/35R19	98W XL	9.5J	9.0J—10.5J	7.7	750	350
	275/35ZR19	100W XL	9.5J	9.0J—11.0J	7.7	800	350
	225/40ZR19	93W XL	8.0J	7.5J—9.0J	7.7	650	350
	* 235/40R19	96W XL	8.5J	8.0J—9.5J	7.7	710	350
	245/40ZR19	98W XL	8.5J	8.0J—9.5J	7.7	750	350
	* 255/40R19	100W XL	9.0J	8.5J—10.0J	7.7	800	350
	* 265/40R19	102W XL	9.5J	9.0J—10.5J	7.7	850	350
	* 275/40R19	101W	9.5J	9.0J—11.0J	7.7	825	300
	225/45ZR19	96W XL	7.5J	7.0J—8.5J	7.7	710	350
	* 235/45R19	99W XL	8.0J	7.5J—9.0J	7.7	775	350
	245/45ZR19	102W XL	8.0J	7.5J—9.0J	7.7	850	350
	* 255/45R19	104W XL	8.5J	8.0J—9.5J	7.7	900	350
	* 275/45R19	108W XL	9.0J	8.5J—10.5J	7.7	1000	350
	* 235/50R19	103W XL	7.5J	6.5J—8.5J	7.7	875	350
	* 255/50R19	107V XL	8.0J	7.0J—9.0J	7.7	975	350
	225/55R19	99V	7.0J	6.0J—8.0J	7.7	775	300
	235/55ZR19	105W XL	7.5J	6.5J—8.5J	7.7	925	350
	* 245/55R19	103W	7.5J	7.0J—8.5J	7.7	875	300
	* 255/55R19	111W XL	8.0J	7.0J—9.0J	7.7	1090	350
	* 275/55R19	111W	8.5J	7.5J—9.5J	7.7	1090	300
20	245/30ZR20	95W XL	8.5J	8.0J—9.0J	7.7	690	350
	* 255/30R20	92W XL	9.0J	8.5J—9.5J	7.7	630	350
	275/30ZR20	97W XL	9.5J	9.0J—10.0J	7.7	730	350
	225/35ZR20	93W XL	8.0J	7.5J—9.0J	7.7	650	350
	245/35ZR20	95W XL	8.5J	8.0J—9.5J	7.7	690	350

Size with *** is under developing, will be available soon.
 Data can be changed by manufacturer without prior notice.

VITALITY F22



SAFETY



HANDLING



COMFORT



RESISTANCE



SILENCE

INCH	SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
20	255/35ZR20	102W XL	9.0J	8.5J—10.0J	7.7	850	350
	* 265/35R20	99W XL	9.5J	9.0J—10.5J	7.7	775	350
	275/35ZR20	102W XL	9.5J	9.0J—11.0J	7.7	850	350
	245/40ZR20	99W XL	8.5J	8.0J—9.5J	7.7	775	350
	* 255/40R20	101W XL	9.0J	8.5J—10.0J	7.7	825	350
	* 265/40R20	104W XL	9.5J	9.0J—10.5J	7.7	900	350
	275/40ZR20	106W XL	9.5J	9.0J—11.0J	7.7	950	350
	* 235/45R20	100W XL	8.0J	7.5J—9.0J	7.7	800	350
	245/45ZR20	103W XL	8.0J	7.5J—9.0J	7.7	875	350
	255/45ZR20	105W XL	8.5J	8.0J—9.5J	7.7	925	350
	* 265/45R20	108W XL	9.0J	8.5J—10.0J	7.7	1000	350
	275/45ZR20	110W XL	9.0J	8.5J—10.5J	7.7	1060	350
	* 285/45R20	112W XL	9.5J	9.0J—10.5J	7.7	1120	350
	* 235/50R20	104W XL	7.5J	6.5J—8.5J	7.7	900	350
	245/50ZR20	105W XL	7.5J	7.0J—8.5J	7.7	925	350
	* 255/50R20	109W XL	8.0J	7.0J—9.0J	7.7	1030	350
	* 275/50R20	113W XL	8.5J	7.5J—9.5J	7.7	1150	350
	* 235/55R20	105W XL	7.5J	6.5J—8.5J	7.7	925	350
	* 255/55R20	110W XL	8.0J	7.0J—9.0J	7.7	1060	350
21	* 275/30R21	98W XL	9.5J	9.0J—10.0J	7.7	750	350
	* 285/30R21	100W XL	10.0J	9.5J—10.5J	7.7	800	350
	* 305/30R21	104W XL	11.0J	10.5J—11.5J	7.7	900	350
	* 315/30R21	105W XL	11.0J	10.5J—11.5J	7.7	925	350
	* 325/30R21	108W XL	11.5J	11.0J—12.0J	7.7	1000	350
	245/35ZR21	96Y XL	8.5J	8.0J—9.5J	7.7	710	350
	255/35ZR21	98Y XL	9.0J	8.5J—10.0J	7.7	750	350
	275/35ZR21	103Y XL	9.5J	9.0J—11.0J	7.7	875	350
	295/35ZR21	107Y XL	10.5J	10.0J—11.5J	7.7	975	350
	315/35ZR21	111Y XL	11.0J	10.5J—12.5J	7.7	1090	350
	* 265/35R21	101W XL	9.5J	9.0J—10.5J	7.7	825	350
	* 285/35R21	105W XL	10.0J	9.5J—11.0J	7.7	925	350
	* 245/40R21	100W XL	8.5J	8.0J—9.5J	7.7	800	350
	* 255/40R21	102W XL	9.0J	8.5J—10.0J	7.7	850	350
	* 265/40R21	105W XL	9.5J	9.0J—10.5J	7.7	925	350
	275/40ZR21	107Y XL	9.5J	9.0J—11.0J	7.7	975	350
	* 285/40R21	109W XL	10.0J	9.5J—11.0J	7.7	1030	350
	* 295/40R21	111W XL	10.5J	10.0J—11.5J	7.7	1090	350
	* 265/45R21	104W	9.0J	8.5J—10.0J	7.7	900	300

Size with *** is under developing, will be available soon.
Data can be changed by manufacturer without prior notice.

VITALITY F22


SAFETY



HANDLING



COMFORT



RESISTANCE



SILENCE

INCH		SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
21	*	275/45R21	110W XL	9.0J	8.5J—10.5J	7.7	1060	350
	*	275/50R21	113W XL	8.5J	7.5J—9.5J	7.7	1150	350
22	*	245/30R22	95W XL	8.5J	8.0J—9.0J	7.7	690	350
	*	265/30R22	97W XL	9.5J	9.0J—10.0J	7.7	730	350
		265/35ZR22	102Y XL	9.5J	9.0J—10.5J	7.7	850	350
		285/35ZR22	106Y XL	10.0J	9.5J—11.0J	7.7	950	350
		275/40ZR22	107Y XL	9.5J	9.0J—11.0J	7.7	975	350
		285/40ZR22	110Y XL	10.0J	9.5J—11.0J	7.7	1060	350
	*	265/40R22	106W XL	9.5J	9.0J—10.5J	7.7	950	350
	*	275/45R22	112W XL	9.0J	8.5J—10.5J	7.7	1120	350
	*	285/45R22	114V XL	9.5J	9.0J—10.5J	7.7	1180	350

Size with "*" is under developing, will be available soon.
 Data can be changed by manufacturer without prior notice.

VITALITY H/T

- Design For Urban Crossover Vehicle
- Excellence For Wet And Dry Conditions
- Extra Grip On Hard Turns
- Fuel-Eco Tread Compound
- Excel Handling Control



VITALITY H/T



INCH	SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
15	* 205/70R15	96H	6.0J	5.0J—7.0J	8.5	710	300
	* 235/75R15	109T XL	6.5J	6.0J—8.0J	8.5	1030	350
	235/60R16	100H	7.0J	6.5J—8.5J	8.5	800	300
	215/65R16	98H	6.5J	6.0J—7.5J	8.5	750	300
	* 215/70R16	100T	6.5J	5.5J—7.0J	8.5	800	300
	235/70R16	106H	7.0J	6.0J—8.0J	8.5	950	300
16	* 245/70R16	111T XL	7.0J	6.5J—8.0J	8.5	1090	350
	* 265/70R16	112H	8.0J	7.0J—9.0J	8.5	1120	300
	* 275/70R16	114T	8.0J	7.0J—9.0J	8.5	1180	300
	* 245/75R16	111T	7.0J	6.5J—8.0J	8.5	1090	300
	* 265/75R16	116T	7.5J	7.0J—9.0J	8.5	1250	300
	* 225/60R17	99V	6.5J	6.0J—8.0J	8.5	775	300
	235/60R17	102H	7.0J	6.5J—8.5J	8.5	850	300
	* 255/60R17	106H	7.5J	7.0J—9.0J	8.5	950	300
17	225/65R17	102H	6.5J	6.0J—8.0J	8.5	850	300
	235/65R17	108H XL	7.0J	6.5J—8.5J	8.5	1000	350
	245/65R17	111H XL	7.0J	7.0J—8.5J	8.5	1090	350
	* 265/65R17	112H	8.0J	7.5J—9.5J	8.5	1120	300
	* 245/70R17	110T	7.0J	6.5J—8.0J	8.5	1060	300
	* 265/70R17	115T	8.0J	7.0J—9.0J	8.5	1215	300
	* 225/60R18	104V XL	6.5J	6.0J—8.0J	8.5	900	350
	235/60R18	107V XL	7.0J	6.5J—8.5J	8.5	975	350
18	245/60R18	105H	7.0J	7.0J—8.5J	8.5	925	300
	* 225/65R18	103H	6.5J	6.0J—8.0J	8.5	875	300
	235/65R18	106H	7.0J	6.5J—8.5J	8.5	950	300
	* 255/55R18	109V XL	8.0J	7.0J—9.0J	8.5	1030	350
	* 265/60R18	110H	8.0J	7.5J—9.5J	8.5	1060	300
	* 285/60R18	116H	8.5J	8.0J—10.0J	8.5	1250	300
	* 265/65R18	114H	8.0J	7.5J—9.5J	8.5	1180	300
	* 275/65R18	116H	8.0J	7.5J—9.5J	8.5	1250	300
19	* 265/70R18	116T	8.0J	7.0J—9.0J	8.5	1250	300
	* 265/50R19	110V XL	8.5J	7.5J—9.5J	8.5	1060	350
	* 245/55R19	103V	7.5J	7.0J—8.5J	8.5	875	300
	* 255/55R19	111V XL	8.0J	7.0J—9.0J	8.5	1090	350
	* 255/60R19	109H	7.5J	7.0J—9.0J	8.5	1030	300
20	* 245/50R20	102V	7.5J	7.0J—8.5J	8.5	850	300
	* 255/50R20	109V XL	8.0J	7.0J—9.0J	8.5	1030	350
	* 265/50R20	111V XL	8.5J	7.5J—9.5J	8.5	1090	350

Size with *** is under developing, will be available soon.
Data can be changed by manufacturer without prior notice.

VITALITY H/T



INCH		SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
20	*	275/50R20	113V XL	8.5J	7.5J—9.5J	8.5	1150	350
	*	235/55R20	102V	7.5J	6.5J—8.5J	8.5	850	300
	*	255/55R20	110V XL	8.0J	7.0J—9.0J	8.5	1060	350
	*	275/55R20	117V XL	8.5J	7.5J—9.5J	8.5	1285	350
	*	275/60R20	115H	8.0J	7.5J—9.5J	8.5	1215	300
15	*	LT235/75R15 C	104/101S	6.5J	6.0J—8.0J	9.2	900/825	350
	*	LT225/75R16 E	115/112S	6.0J	6.0J—7.5J	9.2	1215/1120	550
16	*	LT245/75R16 E	120/116S	7.0J	6.5J—8.0J	9.2	1380/1260	550
	*	LT265/75R16 E	123/120S	7.5J	7.0J—9.0J	9.2	1550/1400	550
17	*	LT245/75R17 E	121/118S	7.0J	6.5J—7.5J	9.2	1450/1320	550

Size with *** is under developing, will be available soon.
Data can be changed by manufacturer without prior notice.

VINTEK F35

- 3 wide grooves designed for higher water clearance on wet roads.
- Optimized void pitch to low tread pattern noise.
- High rigidity and proper shoulder design to resist uneven wear.
- Advanced rubber compound provides longer longevity.



VINTEK F35


SAFETY



ECO



COMFORT



WEAR RESISTANCE



SILENCE

INCH	SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
14	* 175/70R14C C	95/93T	5.0J	4.5J—5.5J	8.8	690/650	375
	* 175/65R14C C	90/88T	5.0J	5.0J—5.5J	8.8	600/560	375
	195R14C D	106/104R	5.5J	5.0J—6.0J	8.8	950/900	450
15	195R15C D	107/105R	5.5J	5.0J—6.0J	8.8	975/925	450
	* 195/65R15C C	98/96T	6.0J	5.5J—6.0J	8.8	750/710	375
	* 215/65R15C C	104/102R	6.5J	6.0J—7.0J	8.8	900/850	375
	* 195/70R15C D	104/102R	6.0J	5.0J—6.0J	8.8	900/850	450
	* 215/70R15C D	109/107R	6.5J	5.5J—7.0J	8.8	1030/975	450
	205/70R15C D	106/104T	6.0J	5.5J—6.5J	8.8	950/900	450
	225/70R15C D	112/110T	6.5J	6.0J—7.0J	8.8	1120/1060	450
	* 195/60R16C C	99/97H	6.0J	5.5J—6.5J	8.8	775/730	375
16	* 215/60R16C D	108/106T	6.5J	6.0J—7.0J	8.8	1000/950	475
	215/65R16C D	109/107T	6.5J	6.0J—7.0J	8.8	1030/975	475
	* 195/65R16C C	100/98T	6.0J	5.5J—6.0J	8.8	800/750	375
	* 205/65R16C D	107/105T	6.0J	5.5J—6.5J	8.8	975/925	475
	* 225/65R16C D	112/110T	6.5J	6.0J—7.0J	8.8	1120/1060	475
	* 235/65R16C D	115/113T	7.0J	6.5J—7.5J	8.8	1215/1150	475
	215/70R16C C	108/106T	6.5J	5.5J—7.0J	8.8	1000/950	375
	* 215/75R16C D	113/111R	6.0J	5.5J—7.0J	8.8	1150/1090	475
	225/75R16C E	121/120T	6.0J	6.0J—7.0J	8.8	1450/1400	575

Size with *** is under developing, will be available soon.
 Data can be changed by manufacturer without prior notice.

- The design is inspired by hawk's morphology.
- Tread center with staggered design to increase the force of the contact patch and satisfied all-terrain traction.
- Special design of the circumferential 2 straight and 2 curvy grooves improve grip on soft and slushy ground, and the strong shoulder out blocks secure the tire's hard turning performance .
- Strong carcass construction provides excellent high speed control.
- Aggressive sidewall design improves great traction in all conditions and increases puncture resistance.
- Proven compound for optimum performance across dry, wet, slushy and on / off-road surfaces.

REBEL HAWK A/T

Wet Performance							
Dry Performance							
Off-Road Performance							
Ride Comfort							
Quietness							

REBEL HAWK A/T



INCH	SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
15	* 31X10.5R15LT C	109S	8.5J	7.0J—9.0J	11.5	1030	350
	* 265/70R15	112T	8.0J	7.0J—9.0J	10.0	1120	300
	* 215/75R15	100T	6.0J	5.5J—7.0J	9.5	800	300
	* 235/75R15	109T XL	6.5J	6.0J—8.0J	9.5	1030	350
16	* 205/60R16	92H	6.0J	5.5J—7.5J	9.5	630	300
	* 215/70R16	100T	6.5J	5.5J—7.0J	9.5	800	300
	* 245/70R16	111T XL	7.0J	6.5J—8.0J	10.0	1090	350
	* 255/70R16	111T	7.5J	6.5J—8.5J	10.0	1090	300
	* 265/70R16	112T	8.0J	7.0J—9.0J	10.0	1120	300
17	* 235/60R17	102H	7.0J	6.5J—8.5J	9.5	850	300
	* 225/65R17	102T	6.5J	6.0J—8.0J	9.5	850	300
	* 235/65R17	104T	7.0J	6.5J—8.5J	9.5	900	300
	* 245/65R17	111T XL	7.0J	7.0J—8.5J	10.0	1090	350
	* 265/65R17	112T	8.0J	7.5J—9.5J	10.0	1120	300
	* 245/70R17	110T	7.0J	6.5J—8.0J	10.0	1060	300
	* 265/70R17	115T	8.0J	7.0J—9.0J	10.0	1215	300
18	* 255/55R18	109H XL	8.0J	7.0J—9.0J	10.0	1030	350
	* 235/60R18	107H XL	7.0J	6.5J—8.5J	9.5	975	350
	* 255/60R18	112H XL	7.5J	7.0J—9.0J	10.0	1120	350
	* 265/60R18	110H	8.0J	7.5J—9.5J	10.0	1060	300
	* 285/60R18	116H	8.5J	8.0J—10.0J	10.0	1250	300
	* 265/65R18	114T	8.0J	7.5J—9.5J	10.0	1180	300
	* 275/65R18	116T	8.0J	7.5J—9.5J	10.0	1250	300
	* 265/70R18	116T	8.0J	7.0J—9.0J	10.0	1250	300
19	* 255/55R19	111V XL	8.0J	7.0J—9.0J	10.0	1090	350
	* 275/45R20	110V XL	9.0J	8.5J—10.5J	10.0	1060	350
	* 265/50R20	111V XL	8.5J	7.5J—9.5J	10.0	1090	350
	* 285/50R20	116V XL	9.0J	8.0J—10.0J	10.0	1250	350
20	* 275/55R20	117H XL	8.5J	7.5J—9.5J	10.0	1285	350
	* 275/60R20	115T	8.0J	7.5J—9.5J	10.0	1215	300
15	* LT215/75R15 D	106/103S	6.0J	5.5J—7.0J	11.0	950/875	450
	* LT225/75R15 D	108/104S	6.0J	6.0J—7.5J	11.0	1000/900	450
	* LT235/75R15 D	110/107S	6.5J	6.0J—8.0J	11.0	1060/975	450

Size with *** is under developing, will be available soon.
Data can be changed by manufacturer without prior notice.

REBEL HAWK A/T


INCH	SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
16	* LT245/75R16 E	120/116S	7.0J	6.5J—8.0J	11.5	1380/1260	550
	* LT215/85R16 D	110/107Q	6.0J	5.5J—7.0J	11.0	1060/975	450
	* LT235/85R16 E	120/116S	6.5J	6.0J—7.5J	11.0	1380/1260	550
	* LT225/75R16 E	115/112S	6.0J	6.0J—7.5J	11.0	1215/1120	550
	* LT265/75R16 E	123/120S	7.5J	7.0J—9.0J	11.5	1550/1400	550
	* LT285/75R16 E	126/123S	8.0J	7.5J—9.5J	11.5	1700/1550	550
17	* LT265/70R17 E	121/118S	8.0J	7.0J—9.0J	11.5	1450/1320	550
	* LT275/70R17 E	121/118S	8.0J	7.0J—9.0J	11.5	1450/1320	550
	* LT285/70R17 E	121/118S	8.5J	7.5J—9.5J	11.5	1450/1320	550
	* LT245/75R17 E	121/118S	7.0J	6.5J—8.0J	11.5	1450/1320	550
18	* LT275/70R18 E	125/122S	8.0J	7.0J—9.0J	11.5	1650/1500	550

Size with *** is under developing, will be available soon.
 Data can be changed by manufacturer without prior notice.

REBEL HAWK R/T

- The design is inspired by hawk claw.
- Dual Sidewall design, one more choice for user to select favorite sidewall.
- Each tread blocks designed with computer optimized sipes. It's not only to offer driving comfort by reducing tire noises, but also provide great grip performance on wet surface.
- Central tread circumferential grooves provide excellent wet grip, while oblique grooves increase aquaplaning resistance
- Stone Ejector prevented damage to groove bottom.
- Proven Compound contribute to longer mileage, increase cut and chipping resistance

Wet Performance						
Dry Performance						
Off-Road Performance						
Ride Comfort						
Quietness						

REBEL HAWK R/T


INCH	SIZE	LI/SS	RIM WIDTH Inch	APPROVED RIM WIDTH Inch	TREAD DEPTH mm	MAX LOAD kg	MAX.INFL. PRESSURE kpa
15	31X10.50R15LT C	109Q	8.5J	7.0J—9.0J	12.5	1030	350
16	245/70R16	111S XL	7.0J	6.5J—8.0J	10.0	1090	350
	265/70R16	112S	8.0J	7.0J—9.0J	8.5	1120	300
17	265/65R17	112T	8.0J	7.5J—9.5J	8.5	1120	300
18	265/60R18	110T	8.0J	7.5J—9.5J	10.0	1060	300
	* 265/65R18	114T	8.0J	7.5J—9.5J	10.0	1180	300
20	265/50R20	111T XL	8.5J	7.5J—9.5J	10.0	1090	350
	285/50R20	116T XL	9.0J	8.0J—10.0J	8.5	1250	350
	* 275/55R20	117T XL	8.5J	7.5J—9.5J	10.0	1285	350
	* 305/55R20	116Q	9.5J	8.5J—11.0J	10.0	1250	300
	* 275/60R20	115T	8.0J	7.5J—9.5J	10.0	1215	300
16	LT245/75R16 E	120/116R	7.0J	6.5J—8.0J	12.5	1380/1260	550
	* LT265/75R16 C	112/109Q	7.5J	7.0J—9.0J	12.5	1120/1030	350
	* LT285/75R16 E	126/123N	8.0J	7.5J—9.5J	12.5	1700/1550	550
	* LT265/70R16 D	117/114Q	8.0J	7.0J—9.0J	12.5	1285/1180	450
17	LT265/70R17 E	121/118R	8.0J	7.0J—9.0J	12.5	1450/1320	550
	* LT285/70R17 E	121/118Q	8.5J	7.5J—9.5J	12.5	1450/1320	550
	* LT315/70R17 C	113/110S	9.5J	8.0J—10.5J	12.5	1150/1060	250
	* LT285/75R17 D	121/118Q	8.0J	7.5J—9.5J	12.5	1450/1320	450
18	* LT265/60R18 E	119/116Q	8.0J	8.0J—9.5J	12.5	1360/1250	550
	* LT285/60R18 E	122/119Q	8.5J	8.5J—10.0J	12.5	1500/1360	550
	* LT275/65R18 E	123/120Q	8.0J	8.0J—9.5J	12.5	1550/1400	550
	* LT275/70R18 E	125/122Q	8.0J	7.0J—9.0J	12.5	1650/1500	550

Size with *** is under developing, will be available soon.
 Data can be changed by manufacturer without prior notice.



Tire Direct 
La nueva generación



www.tiredirect.com.mx