

F FULLRUN

HECHO EN MALASIA



Tire Direct
La nueva generación

www.tiredirect.com.mx



TIRE DIRECT



/TIRE_DIRECT



/TIREDIRECTMX



TIRE DIRECT



FULLRUN's high performance radial, assymetrical F2000, is designed to provide high performance and all season versatility by blending traction on dry & wet roads.

- * On the outside tread, high-stiffness pattern design increases the cornering force and improving steering capability, showing excellent dry performance.
- * On the inside tread, high void ratio and flexible tread blocks provide excellent wet performance, while enhancing driving comfort.
- * Optimized 5-pitch alignment reduces perceived road noise for a more comfortable ride.
- * Unique compound formula on the tread can not only increase the grip on the wet ground, but also reduce rolling resistance.

Sizes & Specifications

F2000 UTQG:380AA

Item Code	Tire Size		STD. Rim	Tread Depth		Section Width	Overall Dia.	Max. Load		Max. Pressure	
			In.	mm	1/32 In.	mm	mm	Kg	lbs.	KPa	PSI
17 In.											
F20001701	215/60R17	96H	6.5J	8.0	10.1	221	690	710	1565	300	44
F20001702	235/60R17	106H XL	7.0J	8.0	10.1	240	714	950	2094	340	49

"XL" indicates Extra Load.



F6000 is a performance summer tire with stylish asymmetric tread pattern.

- * Continuous tread elements, the shoulders strengthened by solid ribs and tire's internal structure improve durability and to minimize distortion at high speeds and temperatures.
- * Larger shoulder tread blocks make sure crisp cornering;
- * 4-wide longitudinal grooves evacuate water from contact area quickly.
- * 3-D groove design reduces the "pumping" noise taking place while not comprising the rigidity of tread blocks.
- * Variable pitch alignment largely improve the ride comfort.

Sizes & Specifications

F6000 UTQG:380AA

Item Code	Tire Size		STD. Rim	Tread Depth		Section Width	Overall Dia.	Max. Load		Max. Pressure	
			In.	mm	1/32 In.	mm	mm	Kg	lbs.	KPa	PSI
15 In.											
F60001501	195/50R15	82V	6.0J	8.0	10.0	201	577	475	1047	300	44
F60001502	195/55R15	85V	6.0J	8.0	10.0	201	595	515	1135	300	44
F60001503	185/60R15	84H	5.5J	8.0	10.0	189	603	500	1102	300	44
16 In.											
F60001601	195/55R16	91V XL	6.0J	8.0	10.1	201	620	615	1356	340	49
F60001602	205/55R16	91V	6.5J	8.0	10.1	214	632	615	1356	300	44
F60001603	215/55ZR16	97W XL	7.0J	8.0	10.0	226	642	730	1609	340	49
17 In.											
F60001701	225/45ZR17	94W XL	7.5J	8.0	10.0	225	634	670	1477	340	49
F60001702	235/45ZR17	97W XL	8.0J	8.0	10.0	236	644	730	1609	340	49
F60001703	205/50ZR17	93W XL	6.5J	8.0	10.0	214	638	650	1433	340	49
F60001704	225/55ZR17	101W XL	7.0J	8.0	10.0	233	680	825	1819	340	49

"XL" indicates Extra Load.





The asymmetric F7000 is an advanced hi-tech performance tire and provides ultimate grip on wet and dry surfaces.

- * Outsider is for lateral stability and crisp response especially on twisting road. Insider possesses blocked bands and wide grooves for enough grip in wet street.
- * Optimized footprint, sipes/grooves angle and density arrangement for exceptional performance on dry and wet road.
- * 4-wide-longitudinal groove design ensures evacuating water from rolling contact patch efficiently.
- * Computer simulated block array, inner and outer lateral channels minimize road/tire noise, and enhancing driving comfort.

Sizes & Specifications

F7000 UTQG:380AA

Item Code	Tire Size		STD. Rim	Tread Depth		Section Width	Overall Dia.	Max. Load		Max. Pressure	
			In.	mm	1/32 In.	mm	mm	Kg	lbs.	KPa	PSI
14 In.											
F70001401	175/65R14	82H	5.0J	7.8	9.8	177	584	475	1047	300	44
F70001402	175/70R14	84H	5.0J	7.8	9.8	177	602	500	1102	300	44
15 In.											
F70001501	195/60R15	88H	6.0J	8.3	10.5	201	615	560	1235	300	44
F70001502	185/65R15	88H	5.5J	8.0	10.1	189	621	560	1235	300	44
F70001503	195/65R15	91H	6.0J	8.3	10.5	201	635	615	1356	300	44
F70001505	205/70R15	96H	6.0J	7.8	9.8	209	669	710	1565	300	44
F70001506	215/70R15	98H	6.5J	7.8	9.8	221	683	750	1653	300	44
16 In.											
F70001601	205/60R16	92V	6.0J	8.0	10.1	209	652	630	1389	300	44
F70001602	215/60R16	99V XL	6.5J	8.0	10.1	221	664	775	1709	340	49
F70001603	225/60R16	98H	6.5J	8.0	10.1	228	676	750	1653	300	44
F70001604	205/60R16	92H	6.0J	8.0	10.1	209	652	630	1389	300	44
17 In.											
F70001701	215/45ZR17	91W XL	7.0J	8.0	10.1	213	626	615	1356	340	49
F70001702	215/50ZR17	95W XL	7.0J	8.0	10.1	226	648	690	1521	340	49
F70001703	225/50ZR17	98W XL	7.0J	8.0	10.1	233	658	750	1653	340	49
F70001704	215/55ZR17	98W XL	7.0J	8.0	10.1	226	668	750	1653	340	49
F70001705	235/55ZR17	103W XL	7.5J	8.0	10.1	245	690	875	1929	340	49
18 In.											
F70001801	225/40ZR18	92W XL	8.0J	8.0	10.1	230	637	630	1389	340	49
F70001802	245/40ZR18	97W XL	8.5J	8.0	10.1	248	653	730	1609	340	49
F70001803	225/45ZR18	95W XL	7.5J	8.0	10.1	225	659	630	1389	340	49
F70001804	245/45ZR18	100W XL	8.0J	8.0	10.1	243	677	800	1764	340	49
F70001805	235/45ZR18	98W XL	8.0J	8.0	10.1	236	669	750	1653	340	49
F70001806	215/35ZR18	84W XL	7.5J	8.0	10.1	218	607	500	1102	340	49
F70001807	235/40ZR18	95W XL	8.5J	8.0	10.1	241	645	690	1521	340	49
F70001808	235/55R18	104W XL	7.5J	8.0	10.1	245	715	900	1984	340	49
F70001809	235/50ZR18	101W XL	7.5J	8.0	10.1	245	693	825	1819	340	49
F70001810	235/65R18	106H	7.0J	8.0	10.1	240	763	950	2094	300	49
19 In.											
F70001901	235/35ZR19	92W XL	8.5J	8.0	10.1	241	647	630	1389	340	49
F70001902	235/40ZR19	96W XL	8.5J	8.0	10.1	241	671	710	1565	340	49
F70001903	245/40ZR19	98W XL	8.5J	8.0	10.1	248	679	750	1653	340	49
F70001904	235/55R19	105V XL	7.5J	8.0	10.1	245	741	925	2039	340	49
F70001905	275/30ZR19	96W XL	9.5J	8.0	10.1	278	649	710	1565	340	49
F70001906	215/35ZR19	85W XL	7.5J	8.0	10.1	218	633	515	1135	340	49
F70001907	225/35ZR19	88W XL	8.0J	8.0	10.1	230	641	560	1235	340	49
F70001908	245/35ZR19	93W XL	8.5J	8.0	10.1	248	655	650	1433	340	49
F70001909	265/30ZR19	93W XL	9.5J	8.0	10.1	271	643	650	1433	340	49
20 In.											
F70002001	225/30ZR20	85W XL	8.0J	8.0	10.1	230	644	515	1135	340	49
F70002002	225/35ZR20	93W XL	8.0J	8.0	10.1	230	666	650	1433	340	49
F70002003	245/35ZR20	95W XL	8.5J	8.0	10.1	248	680	690	1521	340	49
F70002004	245/45ZR20	103W XL	8.0J	8.0	10.1	243	728	875	1929	340	49
F70002005	275/40R20	106V XL	9.5J	8.0	10.1	278	728	950	2094	340	49
F70002006	255/35ZR20	97W XL	9.0J	8.0	10.1	260	686	730	1609	340	49
F70002007	315/35ZR20	110W XL	11.0J	8.0	10.1	320	728	1060	2337	340	49
F70002008	275/30ZR20	97W XL	9.5J	8.0	10.1	278	674	730	1609	340	49
F70002009	245/30ZR20	95W XL	8.5J	8.0	10.1	248	656	600	1323	340	49
22 In.											
F70002201	225/30ZR22	86W XL	8.0J	8	10.1	230	695	530	1168	340	49
F70002202	235/30ZR22	90W XL	8.5J	8.0	10.1	242	701	600	1323	340	49
F70002203	245/30ZR22	92W XL	8.5J	8.0	10.1	248	707	630	1389	340	49
F70002204	255/30ZR22	95W XL	9.0J	8.0	10.1	260	713	690	1521	340	49
F70002205	265/30ZR22	97W XL	9.5J	8.0	10.1	271	719	730	1609	340	49
F70002206	295/25ZR22	97W XL	10.5J	8.0	10.1	301	707	730	1609	340	49
F70002207	275/35ZR22	104W XL	9.5J	8.0	10.1	278	751	900	1984	340	49
F70002208	305/35ZR22	110W XL	11.0J	8.0	10.1	313	773	1060	2337	340	49
F70002209	295/30ZR22	103W XL	10.5J	8.0	10.1	301	737	875	1929	340	49
24 In.											
F70002401	245/30ZR24	94W XL	8.5J	8.0	10.1	248	758	670	1477	340	49
F70002402	255/30ZR24	97W XL	9.0J	8.0	10.1	260	764	730	1609	340	49
F70002403	275/25ZR24	96W XL	10.0J	8.0	10.1	283	748	710	1565	340	49
F70002404	275/30ZR24	101W XL	9.5J	8.0	10.1	278	776	825	1819	340	49
F70002405	295/35R24	110V XL	10.5J	8.0	10.1	301	816	1060	2337	340	49
F70002406	315/35R24	114V XL	11.0J	8.0	10.1	320	830	1180	2601	340	49
F70002407	295/30R24	105V XL	10.5J	8.0	10.1	301	788	925	2039	340	49
F70002408	305/35R24	112V XL	10.0J	8.0	10.1	313	824	1120	2469	340	49

"XL" indicates Extra Load.



All season tire passenger cars. It provides perfect control, driving comfort and sufficient traction with its optimized profile, structure and sipe density for all weather conditions in mild climate.

- * Circumferential rib on the tread center improves handling, and braking performance.
- * Better grip and traction on wet surface with optimized sipe density.
- * High tech construction, jointless mono strand bead wire and hard bead filler improve lateral stability in high speed cornering and uniformity for smoother ride.
- * Four longitudinal grooves channel water from contact patch efficiently.
- * Tread compound is designed to better all-season grip, lower rolling resistance and longer mileage.

Sizes & Specifications

PC388 UTQG:400AA

Item Code	Tire Size		STD. Rim	Tread Depth		Section Width	Overall Dia.	Max. Load		Max. Pressure	
			In.	mm	1/32 In.	mm	mm	Kg	lbs.	KPa	PSI
14 In.											
PC3881403	195/70R14	91T	6.0J	8.0	10.1	201	630	615	1356	300	44
15 In.											
PC3881501	185/65R15	88H	5.5J	8.0	10.1	189	621	560	1235	300	44
PC3881502	195/60R15	88H	6.0J	8.0	10.5	201	615	560	1235	300	44
PC3881503	195/65R15	91H	6.0J	8.0	10.5	201	635	615	1356	300	44
PC3881504	205/65R15	94H	6.0J	8.0	10.5	209	647	670	1477	300	44
16 In.											
PC3881603	205/65R16	95H	6.0J	8.0	10.1	209	672	690	1521	300	44
PC3881604	215/65R16	98H	6.5J	8.0	10.1	221	686	750	1653	300	44
PC3881605	215/60R16	99V XL	6.5J	8.0	10.1	221	664	775	1709	340	49
PC3881606	215/60R16	99H XL	6.5J	8.0	10.1	221	664	775	1709	340	49
17 In.											
PC3881705	215/65R17	99H	6.5J	8.0	10.5	221	712	775	1709	300	44
PC3881706	225/60R17	99H	6.5J	8.0	10.5	228	702	775	1709	300	44
PC3881707	225/65R17	102H	6.5J	8.0	10.5	228	724	850	1874	300	44

"XL" indicates Extra Load.





Directional and aggressive HS299 with applying hawkish bionics provides superb traction and strong passing-by performance .

- * Twin-wide longitudinal grooves and laterally biased groove design drain water from the contact efficiently.
- * Internally, 2 layers of specialized high-tensile steel belts reinforced by nylon and 2 layers of HMLS polyester bodyplies to stabilize the tread area and enhance handling as well as high-speed capability.
- * The wide rolling tread width is specialized for high-speed stability, confident cornering, superior traction, helped by stiff bead filler and semi-continuous center rib.
- * Exclusive compound creates a confident-grip to maintain control on serious roads without sacrificing durability.

Sizes & Specifications

HS299 UTQG:420AA

Item Code	Tire Size		STD. Rim	Tread Depth		Section Width	Overall Dia.	Max. Load		Max. Pressure	
			In.	mm	1/32 In.	mm	mm	Kg	lbs.	KPa	PSI
20 In.											
HS2992001	275/40R20	106V XL	9.5J	9.0	11.3	278	728	950	2094	340	49
HS2992002	275/45R20	110H XL	9.0J	9.0	11.3	273	756	1060	2337	340	49
HS2992003	285/50R20	116H XL	9.0J	9.0	11.3	297	794	1250	2756	340	49
HS2992004	275/55R20	117H XL	8.5J	9.0	11.3	284	810	1285	2833	340	49
HS2992005	275/60R20	119H XL	8.0J	9.0	11.3	279	838	1360	2998	340	49
22 In.											
HS2992201	265/35R22	102V XL	9.5J	9.0	11.3	271	745	850	1874	340	49
HS2992202	305/40R22	114V XL	11.0J	9.0	11.3	313	803	1180	2601	340	49
HS2992203	305/45R22	118V XL	10.0J	9.0	11.3	303	833	1320	2910	340	49
HS2992204	285/45R22	114V XL	9.5J	9.0	11.3	285	815	1180	2601	340	49
HS2992205	265/40R22	106V XL	9.5J	9.0	11.3	271	771	950	2094	340	49
HS2992206	295/30ZR22	103W XL	10.5J	9.0	11.3	301	737	875	1929	340	49
24 In.											
HS2992401	285/40R24	112V XL	10.0J	9.0	11.3	290	838	1120	2469	340	49
HS2992402	295/35R24	110V XL	10.5J	9.0	11.3	301	816	1060	2337	340	49
HS2992403	305/35R24	112V XL	11.0J	9.0	11.3	313	824	1120	2469	340	49
HS2992404	295/30R24	105V XL	10.5J	9.0	11.3	301	788	925	2039	340	49
HS2992405	295/40R24	114V XL	10.5J	9.0	11.3	301	846	1180	2601	340	49

"XL" indicates Extra Load.

