

HAPPYROAD
HIGH-PERFORMANCE TYRES

**HIGH PERFORMANCE TRUCK
& BUS ALL STEEL RADIAL TYRE**

CATALOG 2023



Tire Direct
La nueva generación



TIRE DIRECT



/TIRE_DIRECT



/TIREDIRECTMX



TIRE DIRECT

Tire Direct
La nueva generación

HAPPYROAD
HIGH PERFORMANCE TYRES

HAPPYROAD
HIGH PERFORMANCE TYRES

Y202

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	17mm	240mm	300	1085	930	930	3550	3250



Y226

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
11R22.5-16PR	8.25	146/143M	14.50mm	210mm	279	1054	830	830	3000	2725
11R24.5-16PR	8.25	149/146M	14.50mm	210mm	279	1104	830	830	3250	3000
295/75R22.5-16PR	9.00	146/143M	14.50mm	220mm	298	1104	830	830	3000	2725
315/80R22.5-20PR	9.00	156/150L	15.50mm	236mm	312	1076	875	875	4000	3350
385/65R22.5-20PR	11.75	160L	15.50mm	290mm	389	1072	900	-	4500	-



Y256

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	17mm	240mm	300	1085	930	930	3550	3250



Y300

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	17mm	240mm	300	1085	930	930	3550	3250



HAPPYROAD
HIGH-PERFORMANCE TYRES

HAPPYROAD
HIGH-PERFORMANCE TYRES

Y306

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
10.00R20-18PR	7.5	152/149M	16mm	210mm	278	1054	930	930	3250	3000
11.00R20-18PR	8.0	152/149J	16mm	223mm	293	1085	930	930	3550	3250
12.00R20-20PR	8.5	156/153J	16.50mm	230mm	315	1125	900	900	4000	3650
12.00R24-20PR	8.5	160/157K	15mm	238mm	315	1226	900	900	4500	4125
11R22.5-16PR	8.25	146/143M	14.50mm	210mm	279	1054	830	830	3000	2725
11R24.5-16PR	8.25	149/146M	14.50mm	210mm	279	1104	830	830	3250	3000
12R24.5-18PR		154/151K	16mm	220mm			930	930	3750	3450
13R22.5-20PR	9.75	156/150L	15.30mm	240mm	320	1124	875	875	4000	3350
315/80R22.5-20PR	9.00	156/150L	14mm	230mm	312	1076	875	875	4000	3350
315/80R22.5-20PR	9.00	156/150L	16mm	236mm	312	1076	875	875	4000	3350



Y316

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
11.00R20-18PR	8.0	152/149J	16mm	228mm	293	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	16mm	240mm	300	1085	930	930	3550	3250
13R22.5-20PR	9.75	156/150L	16mm	240mm	320	1124	875	875	4000	3350



Y308

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
9.00R20-16PR	7.0	144/142K	15mm	200mm	259	1019	900	900	2800	2650
10.00R20-18PR	7.5	149/146K	16.50mm	214mm	278	1054	930	930	3250	3000
11.00R20-18PR	8.0	152/149J	18.50mm	228mm	293	1085	930	930	3550	3250
12.00R20-20PR	8.5	156/153J	20mm	234mm	315	1125	900	900	4000	3650



Y326

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	17mm	240mm	300	1085	930	930	3550	3250
13R22.5-20PR	9.75	156/150L	17.50mm	250mm	320	1124	875	875	4000	3350



HAPPYROAD
HIGH PERFORMANCE TYRES

HAPPYROAD
HIGH PERFORMANCE TYRES

Y328

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
1100R20-18PR	8.0	152/149J	20mm	228mm	293	1085	930	930	3550	3250
1200R20-20PR	8.5	156/153K	21mm	240mm	315	1125	900	900	4000	3650
13R22.5-20PR	9.75	156/150L	19mm	250mm	320	1124	875	875	4000	3350



Y726

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	20mm	240mm	300	1085	930	930	3550	3250



Y706

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
11R22.5-18PR	8.25	149/146M	16.50mm	220mm	279	1054	930	930	3250	3000
295/80R22.5-18PR	9.00	152/149M	17mm	236mm	298	1044	900	900	3550	3250
315/80R22.5-20PR	9.00	156/150L	18mm	240mm	312	1076	875	875	4000	3350



HAPPYROAD
HIGH-PERFORMANCE TYRES

HAPPYROAD
HIGH-PERFORMANCE TYRES

Y216

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
11R22.5-16PR	8.25	146/143M	14.50mm	210mm	279	1054	830	830	3000	2725
295/80R22.5-18PR	9.00	152/149M	14.50mm	236mm	298	1044	900	900	3550	3250



Y266

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
315/80R22.5-20PR	9.00	156/150L	14mm	230mm	312	1076	875	875	4000	3350



Y302

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	16mm	240mm	300	1085	930	930	3550	3250



Y311

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	17.50mm	240mm	300	1085	930	930	3550	3250



Y318

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12.00R20-20PR	8.5	156/153J	20mm	240mm	315	1125	900	900	4000	3650



Y336

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
9.00R20-16PR	7.0	144/142K	15mm	200mm	259	1019	900	900	2800	2650
10.00R20-18PR	7.5	149/146K	16mm	214mm	278	1054	930	930	3250	3000
11.00R20-18PR	8.0	152/149J	16mm	228mm	293	1085	930	930	3550	3250
12.00R20-20PR	8.5	156/153K	16.50mm	230mm	315	1125	900	900	4000	3650
12.00R24-20PR	8.5	160/157K	15mm	238mm	315	1226	900	900	4500	4125



HAPPYROAD
HIGH-PERFORMANCE TYRES

HAPPYROAD
HIGH-PERFORMANCE TYRES

Y506

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
385/65R22.5-20PR	11.75	160L	15.50mm	290mm	389	1072	900	-	4500	-



Y516

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
385/65R22.5-20PR	11.75	160L	15.50mm	290mm	389	1072	900	-	4500	-



Y709+

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
11.00R20-18PR	8.0	152/149G	22.50mm	228mm	293	1085	930	930	3550	3250
12.00R20-20PR	8.5	156/153G	24.50mm	240mm	315	1125	900	900	4000	3650



Y716

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
295/80R22.5-18PR	9.00	152/149M	18mm	236mm	298	1044	900	900	3550	3250



Y727

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
13R22.5-20PR	9.75	156/150L	15.30mm	240mm	320	1124	875	875	4000	3350



Y736

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
9.00R20-18PR	7.0	144/142K	15mm	200mm	259	1019	900	900	2800	2650
12R22.5-18PR	9.00	152/149M	18mm	240mm	300	1085	930	930	3550	3250



HAPPYROAD
HIGH-PERFORMANCE TYRES

Y746

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
11R22.5-16PR	8.25	146/143M	20mm	215mm	279	1054	930	930	3250	3000
11R24.5-16PR	8.25	149/146M	20mm	215mm	279	1104	830	830	3250	3000
295/75R22.5-16PR	9.00	146/143M	20mm	215mm	298	1014	830	830	3000	2725

Y751

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	22mm	240mm	300	1085	930	930	3550	3250

Y756

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	20mm	240mm	300	1085	930	930	3550	3250

Y766

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
315/80R22.5-20PR	9.00	156/150L	19mm	230mm	312	1076	875	875	4000	3350

Y778

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	20mm	240mm	300	1085	930	930	3550	3250

Y779

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
11R22.5-16PR	8.25	146/143J	23mm	215mm	279	1054	930	930	3250	3000
11R24.5-16PR	8.25	149/146J	23mm	215mm	279	1104	830	830	3250	3000

HAPPYROAD
HIGH-PERFORMANCE TYRES



HAPPYROAD EXPLOSION-PROOF TYRE

HAPPYROAD
HIGH-PERFORMANCE TYRES



YF701D

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12.00R20-20PR	8.5	156/153B	24.5	250	315	1125	900	900	4000	3650
12.00R20-20PR+	8.5	156/153B	25	250	315	1125	900	900	4000	3650
12.00R20-20PR++	8.5	156/153B	30	260	315	1125	900	900	4000	3650

YF702D

SIZE	standard rim	LOAD INDEX & SPEED GRAND	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					section width	overall diameter	single	double	single	double
12.00R20-20PR	8.5	156/153B	24.5	250	315	1125	900	900	4000	3650
12.00R20-20PR+	8.5	156/153B	25	250	315	1125	900	900	4000	3650
12.00R20-20PR++	8.5	156/153B	30	260	315	1125	900	900	4000	3650



HAPPYROAD
HIGH PERFORMANCE TYRES

HAPPYROAD
HIGH PERFORMANCE TYRES

YF703D

Table with 12 columns: SIZE, standard rim, LOAD INDEX & SPEED GRAND, TREAD DEPTH, TREAD WIDTH, NEW TYRE INFORMATION (mm), inflation pressure (Kpa), maximum load (kg). Rows include 12.00R20-20PR, 12.00R20-20PR+, and 12.00R20-20PR++.



YF708D

Table with 12 columns: SIZE, standard rim, LOAD INDEX & SPEED GRAND, TREAD DEPTH, TREAD WIDTH, NEW TYRE INFORMATION (mm), inflation pressure (Kpa), maximum load (kg). Rows include 12.00R20-20PR, 12.00R20-20PR+, and 12.00R20-20PR++.



YF706D

Table with 12 columns: SIZE, standard rim, LOAD INDEX & SPEED GRAND, TREAD DEPTH, TREAD WIDTH, NEW TYRE INFORMATION (mm), inflation pressure (Kpa), maximum load (kg). Rows include 12.00R20-20PR, 12.00R20-20PR+, and 12.00R20-20PR++.



HAPPYROAD PRODUCT DATA SHEET

HAPPYROAD PRODUCT DATA SHEET

SIZE	standard rim	LOAD INDEX & SPEED GRAND	PATTERN	POSITION	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					mm	mm	section width	overall diameter	single	double	single	double
9.00R20-16PR	7.0	144/142K	Y308	Drive	15	200	259	1019	900	900	2800	2650
9.00R20-16PR	7.0	144/142K	Y336	All	15	200	259	1019	900	900	2800	2650
9.00R20-16PR	7.0	144/142K	Y736	Drive	15	200	259	1019	900	900	2800	2650
10.00R20-18PR	7.5	149/146K	Y308	Drive	16.50	214	278	1054	930	930	3250	3000
10.00R20-18PR	7.5	149/146K	Y336	All	16	214	278	1054	930	930	3250	3000
10.00R20-18PR	7.5	149/146K	Y306	All	16	210	278	1054	930	930	3250	3000
11.00R20-18PR	8.0	152/149J	Y306	All	16	223	293	1085	930	930	3550	3250
11.00R20-18PR	8.0	152/149J	Y308	Drive	18.50	228	293	1085	930	930	3550	3250
11.00R20-18PR	8.0	152/149J	Y316	All	16	228	293	1085	930	930	3550	3250
11.00R20-18PR	8.0	152/149J	Y336	All	16	228	293	1085	930	930	3550	3250
11.00R20-18PR	8.0	152/149J	Y328	Drive	20	228	293	1085	930	930	3550	3250
11.00R20-18PR	8.0	152/149G	Y709+	Drive	22.50	228	293	1085	930	930	3550	3250
12.00R20-20PR	8.5	156/153K	Y300	All	17.50	240	315	1125	900	900	4000	3650
12.00R20-20PR	8.5	156/153J	Y306	All	16.50	230	315	1125	900	900	4000	3650
12.00R20-20PR	8.5	156/153K	Y336	All	16.50	230	315	1125	900	900	4000	3650
12.00R20-20PR	8.5	156/153J	Y308	Drive	20	234	315	1125	900	900	4000	3650
12.00R20-20PR	8.5	156/153J	Y318	Drive	20	240	315	1125	900	900	4000	3650
12.00R20-20PR	8.5	156/153K	Y328	Drive	21	240	315	1125	900	900	4000	3650
12.00R20-20PR	8.5	156/153G	Y709+	Drive	24.50	240	315	1125	900	900	4000	3650
12.00R24-20PR	8.5	160/157K	Y306	All	15	238	315	1226	900	900	4500	4125
12.00R24-20PR	8.5	160/157K	Y336	All	15	238	315	1226	900	900	4500	4125
11R22.5-16PR	8.25	146/143M	Y216	Steer	14.50	210	279	1054	830	830	3000	2725
11R22.5-16PR	8.25	146/143M	Y226	Steer	14.50	210	279	1054	830	830	3000	2725
11R22.5-16PR	8.25	146/143M	Y306	All	14.50	210	279	1054	830	830	3000	2725
11R22.5-18PR	8.25	149/146M	Y706	Drive	16.50	220	279	1054	930	930	3250	3000
11R22.5-16PR	8.25	146/143M	Y746	Drive	20	215	279	1054	930	930	3250	3000
11R22.5-16PR	8.25	146/143J	Y779	Drive	23	215	279	1054	930	930	3250	3000
11R24.5-16PR	8.25	149/146M	Y226	Steer	14.50	210	279	1104	830	830	3250	3000
11R24.5-16PR	8.25	149/146M	Y306	All	14.50	210	279	1104	830	830	3250	3000
11R24.5-16PR	8.25	149/146M	Y746	Drive	20	215	279	1104	830	830	3250	3000
11R24.5-16PR	8.25	149/146J	Y779	Drive	23	215	279	1104	830	830	3250	3000

SIZE	standard rim	LOAD INDEX & SPEED GRAND	PATTERN	POSITION	TREAD DEPTH	TREAD WIDTH	NEW TYRE INFORMATION (mm)		inflation pressure (Kpa)		maximum load (kg)	
					mm	mm	section width	overall diameter	single	double	single	double
12R22.5-18PR	9.00	152/149M	Y202	Steer	17	240	300	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	Y302	All	16	240	300	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	Y311	All	17.50	240	300	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	Y256	Steer	17	240	300	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	Y316	All	16	240	300	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	Y326	All	17	240	300	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	Y726	Drive	20	240	300	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	Y736+	Drive	18	240	300	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	Y751	Drive	22	240	300	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	Y756	Drive	20	240	300	1085	930	930	3550	3250
12R22.5-18PR	9.00	152/149M	Y778	Drive	20	240	300	1085	930	930	3550	3250
12R24.5-18PR		154/151K	Y306	All	16	220			930	930	3750	3450
13R22.5-20PR	9.75	156/150L	Y306	All	15.30	240	320	1124	875	875	4000	3350
13R22.5-20PR	9.75	156/150L	Y316	All	16	240	320	1124	875	875	4000	3350
13R22.5-20PR	9.75	156/150L	Y326	All	17.50	250	320	1124	875	875	4000	3350
13R22.5-20PR	9.75	156/150L	Y328	Drive	19	250	320	1124	875	875	4000	3350
13R22.5-20PR	9.75	156/150L	Y727	Drive	15.30	240	320	1124	875	875	4000	3350
295/75R22.5-16PR	9.00	146/143M	Y226	Steer	14.50	220	298	1014	830	830	3000	2725
295/75R22.5-16PR	9.00	146/143M	Y746	Drive	20	215	298	1014	830	830	3000	2725
295/80R22.5-18PR	9.00	152/149M	Y216	Steer	14.50	236	298	1044	900	900	3550	3250
295/80R22.5-18PR	9.00	152/149M	Y706	Drive	17	236	298	1044	900	900	3550	3250
295/80R22.5-18PR	9.00	152/149M	Y716	Drive	18	236	298	1044	900	900	3550	3250
315/80R22.5-20PR	9.00	156/150L	Y306	All	14	230	312	1076	875	875	4000	3350
315/80R22.5-20PR	9.00	156/150L	Y266	Steer	14	230	312	1076	875	875	4000	3350
315/80R22.5-20PR	9.00	156/150L	Y766	Drive	19	230	312	1076	875	875	4000	3350
315/80R22.5-20PR	9.00	156/150L	Y306	All	16	236	312	1076	875	875	4000	3350
315/80R22.5-20PR	9.00	156/150L	Y226	Steer	15.50	236	312	1076	875	875	4000	3350
315/80R22.5-20PR	9.00	156/150L	Y706	Drive	18mm	240	312	1076	875	875	4000	3350
385/65R22.5-20PR	11.75	160L	Y226	Steer	15.50	290	389	1072	900	-	4500	-
385/65R22.5-20PR	11.75	160L	Y506	Steer	15.50	290	389	1072	900	-	4500	-
385/65R22.5-20PR	11.75	160L	Y516	Steer	15.50	290	389	1072	900	-	4500	-