

LINK

PCR TIRE CATALOGUE

Tire Direct
La nueva generación



TIRE DIRECT



/TIRE_DIRECT



/TIREDIRECTMX



TIRE DIRECT

ALWAYS WITH YOU

Tire Direct
La nueva generación



iLINK

CHOOSE YOUR I LINK TIRE

Choose your tires based on your vehicle - - - - -

L-GRIP 16 PASSENGER CAR TIRE P---01 HP	L-COMFORT 68 PASSENGER CAR TIRE P---03 HP	L-GRIP 66 PASSENGER CAR TIRE P---05 HP	L-GRIP 55 PASSENGER CAR TIRE P---09 HP	POWERCITY 77 HIGHWAY TERRAIN TIRE P---39 H/T	L-FINDER 78 HIGHWAY TERRAIN TIRE P---41 H/T	POWERCITY 79 HIGHWAY TERRAIN TIRE P---43 H/T	TERRAMAX LSR1 A/T ALL TERRAIN TIRE P---45 A/T
L-ZEAL 56 PASSENGER CAR TIRE P---11 UHP	SPEEDKING 07 PASSENGER CAR TIRE P---15 UHP	THUNDER U09 PASSENGER CAR TIRE P---17 UHP	L-ZEAL 56 PASSENGER CAR TIRE P---21 RFT NEW	TERRAMAX LSR2 A/T ALL TERRAIN TIRE P---47 A/T	PENTERRA R/T RUGGED TERRAIN TIRE P---49 R/T NEW	WILDWOLF M/T MUD TERRAIN TIRE P---51 M/T	TOPFORCE M/T MUD TERRAIN TIRE P---53 M/T
MULTIMATCH A/S ALL SEASON TIRE P---23 A/S	MULTIMILE A/S ALL SEASON TIRE P---27 A/S	X-MASTER EV EV TIRE P---29 EV NEW		SNOWGRIPPER I WINTER TIRE P---55 HP	SNOWGRIPPER II WINTER TIRE P---59 HP	WINTER IL868 WINTER TIRE P---61 UHP	WINTER IL989 WINTER TIRE P---63 VAN
L-MAX 9 VAN TIRE P---31 VAN	L-STRONG 36 VAN TIRE P---33 VAN	L-POWER 28 VAN TIRE P---35 VAN	TOURWAYS 52 VAN TIRE P---37 VAN	WINTERVORHUT STUD I STUDDED TIRE P---65 HP NEW	WINTERVORHUT STUD II STUDDED TIRE P---67 UHP NEW	WINTERVORHUT STUD III STUDDED TIRE P---69 SUV NEW	L-TRAVEL18 PASSENGER CAR TIRE P---71 S/T

1CR

HP

UHP



UTQG: 380/A/A

Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Streamlined grooves

Streamlined horizontal grooves design, improve smooth and high-speed ability, provide low-noise and comfort ride.

Shoulder design

Big block design on shoulder ultra-big block design on shoulder improve handling ability, open horizontal grooves provide great wetland drainage.

Louver design

Louver design on shoulder. Staged louvers on shoulder improve driving safety, semi Through slips reduce noise.

Anti-slip grooves

Four wide vertical drainage grooves. Four wide vertical drainage grooves provide great wetland grip ability, preventing lateral slip on wetland.

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
155/70R12	73T	4.5	157	523	365	805	300/44	380/A/A	BSW	-	-	-
175/60R15	81H	5J	177	591	462	1019	300/44	380/A/A	BSW	✓	✓	✓
175/65R14	82H	6J	177	584	475	1047	300/44	380/A/A	BSW	✓	✓	✓
175/65R15	84H	5 1/2J	177	609	500	1102	300/44	380/A/A	BSW	✓	✓	✓
185/50R16	81V	5 1/2J	194	592	462	1018	300/44	380/A/A	BSW	✓	✓	✓
185/55R14	80H	6 1/2J	194	560	450	992	300/44	380/A/A	BSW	✓	✓	✓
185/55R15	82V	5J	194	585	475	1047	300/44	380/A/A	BSW	✓	✓	✓
185/55R16	83V	5J	194	610	487	1074	300/44	380/A/A	BSW	✓	✓	✓
185/60R14	82H	6J	189	578	475	1047	300/44	380/A/A	BSW	✓	✓	✓
185/60R15	88H	5 1/2J	189	603	560	1235	340/50	380/A/A	BSW	✓	✓	✓
185/60R15	84H	5 1/2J	189	603	500	1102	300/44	380/A/A	BSW	✓	✓	✓
185/65R14	86H	5 1/2J	189	596	530	1168	300/44	380/A/A	BSW	✓	✓	✓
185/65R15	88H	6J	189	621	560	1235	300/44	380/A/A	BSW	✓	✓	✓
195/50R15	82V	6J	201	577	475	1047	300/44	380/A/A	BSW	✓	✓	✓
195/55R15	85V	6J	201	595	515	1135	300/44	380/A/A	BSW	✓	✓	✓
195/55R16	87V	6J	201	620	545	1201	300/44	380/A/A	BSW	✓	✓	✓
195/55R16	91W	6J	201	620	615	1356	340/50	380/A/A	BSW	✓	✓	✓
195/60R15	88V	6J	201	615	560	1235	300/44	380/A/A	BSW	✓	✓	✓
195/60R15	88H	6J	201	615	560	1235	300/44	380/A/A	BSW	✓	✓	✓
195/60R16	89H	6J	201	640	580	1279	300/44	380/A/A	BSW	✓	✓	✓
195/65R15	91V	6J	201	635	615	1356	300/44	380/A/A	BSW	✓	✓	✓
195/65R15	95H	6J	201	635	690	1521	340/50	380/A/A	BSW	✓	✓	✓
195/65R15	91H	6J	201	635	615	1356	300/44	380/A/A	BSW	✓	✓	✓
205/55R16	91V	6 1/2J	214	632	615	1356	300/44	380/A/A	BSW	✓	✓	✓
205/60R15	91H	6 1/2J	209	627	615	1356	300/44	380/A/B	BSW	✓	✓	✓
205/60R15	91V	7J	209	627	615	1356	300/44	380/A/B	BSW	✓	✓	✓
205/60R16	92V	6J	209	652	630	1389	300/44	380/A/A	BSW	✓	✓	✓
205/65R15	94V	6J	209	647	670	1477	300/44	380/A/A	BSW	✓	✓	✓
205/65R15	94H	6J	209	647	670	1477	300/44	380/A/A	BSW	✓	✓	✓
205/65R16	95T	6J	209	672	690	1521	300/44	380/A/A	BSW	✓	✓	✓
215/60R16	95V	6J	221	664	690	1521	300/44	380/A/A	BSW	✓	✓	✓
215/60R16	99V	6 1/2J	221	664	775	1709	340/50	380/A/A	BSW	✓	✓	✓
215/60R17	96T	6J	221	690	710	1565	300/44	380/A/A	BSW	✓	✓	✓
215/65R15	100H	6J	221	661	800	1764	340/50	380/A/B	BSW	✓	✓	✓
215/65R16	98H	6 1/2J	221	686	750	1653	300/44	380/A/A	BSW	✓	✓	✓
215/65R17	99T	6 1/2J	221	712	775	1709	300/44	380/A/A	BSW	✓	✓	✓
215/70R14	96H	6 1/2J	221	658	710	1565	300/44	380/A/A	BSW	✓	✓	✓
215/70R15	98T	6 1/2J	221	683	750	1653	300/44	380/A/A	BSW	✓	✓	✓
225/60R16	98V	6 1/2J	228	676	750	1653	300/44	380/A/B	BSW	✓	✓	✓
225/60R17	99H	7J	228	702	775	1709	300/44	380/A/A	BSW	✓	✓	✓
225/65R16	100T	7J	228	698	800	1764	300/44	380/A/B	BSW	✓	✓	✓
225/65R17	102H	6 1/2J	228	724	850	1874	300/44	380/A/B	BSW	✓	✓	✓
235/60R16	100H	6 1/2J	240	688	800	1764	300/44	380/A/B	BSW	✓	✓	✓
235/65R16	103T	6 1/2J	240	712	875	1930	300/44	380/A/B	BSW	✓	✓	✓
235/65R17	104H	6 1/2J	240	738	900	1984	300/44	380/A/A	BSW	✓	✓	✓
235/70R15	103T	7J	240	711	875	1929	300/44	380/A/A	BSW	✓	✓	✓

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice



UTQG: 420/A/A

Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Silicon-containing tread compound

New Silicon-containing tread compound improves grip on wet road conditions and reduce rolling resistance, provide safety ride and reduce fuel consumption.

"Skiving" pattern

"Skiving" pattern design. Stereoscopic straight line "Skiving" pattern design absorb shakes from road, and provide a more comfortable driving.

Silence design

Silence pitches design. Computer-simulated tread pitches design reduces the driving resonance with excellent quiet and comfortable ride.

Big block pattern

Big block pattern in the outside. Big block in the outside ensure the great rigidity, handling and sport performance.

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall	ECE R111	ECE R112	ECE R113
					(kg)	(Lbs)						
145/65R15	72T	4 1/2J	150	569	355	783	300/44	420/A/A	BSW	✓	✓	✓
NEW 145/70R12	69T	4.50B	150	509	325	716	300/44	420/A/A	BSW	✓	✓	✓
145/70R13	71T	4.50B	150	534	345	761	300/44	420/A/A	BSW	✓	✓	✓
NEW 145/80R12	74T	4.00B	145	537	375	827	300/44	420/A/A	BSW	✓	✓	✓
145/80R13	75T	4.00B	145	562	387	853	300/44	420/A/A	BSW	✓	✓	✓
NEW 155/60R14	72H	4 1/2J	157	542	355	783	300/44	420/A/A	BSW	✓	✓	✓
155/65R13	73T	4.50B	157	532	365	805	300/44	420/A/A	BSW	✓	✓	✓
155/65R14	75T	4 1/2J	157	558	387	853	300/44	420/A/A	BSW	✓	✓	✓
155/70R12	73T	4.50B	157	523	365	805	300/44	420/A/A	BSW	✓	✓	✓
155/70R13	75T	4.50B	157	548	387	853	300/44	420/A/A	BSW	✓	✓	✓
155/70R14	77T	4 1/2J	157	574	412	908	300/44	420/A/A	BSW	✓	✓	✓
155/80R13	79T	4.50B	157	578	437	963	300/44	420/A/A	BSW	✓	✓	✓
NEW 165/50R15	73V	5J	170	547	365	805	300/44	420/A/A	BSW	✓	✓	✓
NEW 165/55R14	72V	5J	170	538	355	783	300/44	420/A/A	BSW	✓	✓	✓
NEW 165/55R15	75V	5J	170	563	387	853	300/44	420/A/A	BSW	✓	✓	✓
165/60R14	75H	5J	170	554	387	853	300/44	420/A/A	BSW	✓	✓	✓
165/60R15	81H XL	5J	170	579	462	1019	340/50	420/A/A	BSW	✓	✓	✓
165/65R13	77T	5.00B	170	544	412	908	300/44	420/A/A	BSW	✓	✓	✓
165/65R14	79T	5J	170	570	437	963	300/44	420/A/A	BSW	✓	✓	✓
165/65R15	81T	5J	170	595	462	1019	300/44	420/A/A	BSW	✓	✓	✓
165/70R12	77T	5.00B	170	537	412	908	300/44	420/A/A	BSW	✓	✓	✓
165/70R13	79T	5.00B	170	562	437	963	300/44	420/A/A	BSW	✓	✓	✓
165/70R14	81T	5J	170	588	462	1019	300/44	420/A/A	BSW	✓	✓	✓
165/80R13	83T	4.50B	165	594	487	1074	300/44	420/A/A	BSW	✓	✓	✓
NEW 175/50R15	75H	5 1/2J	182	557	387	853	300/44	420/A/A	BSW	✓	✓	✓
175/50R16	77V	5 1/2J	182	582	412	908	300/44	420/A/A	BSW	✓	✓	✓
175/55R15	77V	5 1/2J	182	573	412	908	300/44	420/A/A	BSW	✓	✓	✓
175/60R13	77T	5.00B	177	540	412	908	300/44	420/A/A	BSW	✓	✓	✓
175/60R14	79H	5.00B	177	566	437	963	300/44	420/A/A	BSW	✓	✓	✓
175/60R15	81H	5J	177	591	462	1019	300/44	420/A/A	BSW	✓	✓	✓
175/65R13	80T	5.00B	177	558	450	992	300/44	420/A/A	BSW	✓	✓	✓
175/65R14	82T	5 J	177	584	475	1047	300/44	420/A/A	BSW	✓	✓	✓
175/65R14	82H	5 J	177	584	475	1047	300/44	420/A/A	BSW	✓	✓	✓
175/65R14	86T	5 J	177	584	530	1168	340/50	420/A/A	BSW	✓	✓	✓
175/65R15	84H	5 J	177	609	500	1102	300/44	420/A/A	BSW	✓	✓	✓

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
175/70R12	80T	5.00B	177	551	450	992	300/44	420/A/A	BSW	✓	✓	✓
175/70R13	82T	5.00B	177	576	475	1047	300/44	420/A/A	BSW	✓	✓	✓
175/70R14	84T	5J	177	602	500	1102	300/44	420/A/A	BSW	✓	✓	✓
185/50R16	81V	6J	194	592	462	1019	300/44	420/A/A	BSW	✓	✓	✓
185/55R14	80H	6J	194	560	450	992	300/44	420/A/A	BSW	✓	✓	✓
185/55R15	82V	6 J	194	585	475	1047	300/44	420/A/A	BSW	✓	✓	✓
185/55R16	83V	6J	194	610	487	1074	300/44	420/A/A	BSW	✓	✓	✓
185/60R13	80H	5.50B	189	552	450	992	300/44	420/A/A	BSW	✓	✓	✓
185/60R14	82H	5 1/2J	189	578	475	1047	300/44	420/A/A	BSW	✓	✓	✓
185/60R15	88H XL	5 1/2J	189	603	560	1235	340/50	420/A/A	BSW	✓	✓	✓
NEW 185/60R16	86H	5 1/2J	189	628	530	1168	300/44	420/A/A	BSW	✓	✓	✓
185/65R14	86H	5 1/2J	189	596	530	1168	300/44	420/A/A	BSW	✓	✓	✓
185/65R15	88H	5.5J	189	621	560	1235	300/44	420/A/A	BSW	✓	✓	✓
185/70R13	86T	5.50B	189	590	530	1168	300/44	420/A/A	BSW	✓	✓	✓
185/70R14	88H	5 1/2J	189	616	560	1235	300/44	420/A/A	BSW	✓	✓	✓
195/50R15	82V	6 J	201	577	475	1047	300/44	420/A/A	BSW	✓	✓	✓
195/50R16	84V	6J	201	602	500	1102	300/44	420/A/A	BSW	✓	✓	✓
195/55R15	85V	6 J	201	595	515	1135	300/44	420/A/A	BSW	✓	✓	✓
195/55R16	87V	6 J	201	620	545	1201	300/44	420/A/A	BSW	✓	✓	✓
195/60R14	86H	6 J	201	590	530	1168	300/44	420/A/A	BSW	✓	✓	✓
195/60R15	88V	6 J	201	615	560	1235	300/44	420/A/A	BSW	✓	✓	✓
195/60R15	88H	6 J	201	615	560	1235	300/44	420/A/A	BSW	✓	✓	✓
195/60R16	89H	6 J	201	640	580	1278	300/44	420/A/A	BSW	✓	✓	✓
195/65R14	89H	6 J	201	610	580	1278	300/44	420/A/A	BSW	✓	✓	✓
195/65R15	91H	6 J	201	635	615	1356	300/44	420/A/A	BSW	✓	✓	✓
195/65R15	91V	6 J	201	635	615	1356	300/44	420/A/A	BSW	✓	✓	✓
195/70R14	91H	6 J	201	630	615	1355	300/44	420/A/A	BSW	✓	✓	✓
205/50R15	86V	6 1/2J	214	587	530	1168	300/44	420/A/A	BSW	✓	✓	✓
205/55R15	88V	6 1/2J	214	607	560	1235	300/44	420/A/A	BSW	✓	✓	✓
205/55R16	91V	6.5J	214	632	615	1356	300/44	420/A/A	BSW	✓	✓	✓
205/60R14	88H	6 J	209	602	560	1234	300/44	420/A/A	BSW	✓	✓	✓
205/60R15	91V	6 J	209	627	615	1355	300/44	420/A/A	BSW	✓	✓	✓
205/60R16	92V	6 J	209	652	630	1389	300/44	420/A/A	BSW	✓	✓	✓
205/65R15	94V	6 J	209	647	670	1477	300/44	420/A/A	BSW	✓	✓	✓
205/65R15	94H	6 J	209	647	670	1477	300/44	420/A/A	BSW	✓	✓	✓

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
205/65R16	95H	6 J	209	672	690	1521	300/44	420/A/A	BSW	✓	✓	✓
205/70R14	95H	6 J	209	644	690	1521	300/44	420/A/A	BSW	✓	✓	✓
205/70R15	96H	6 J	209	669	710	1565	300/44	420/A/A	BSW	✓	✓	✓
205/75R15	97T	5 1/2J	203	689	730	1609	300/44	420/A/A	BSW	✓	✓	✓
205/80R16	104S XL	5 1/2J	203	734	900	1984	340/50	420/A/A	BSW	✓	✓	✓
215/55R16	93V	7 J	226	642	650	1432	300/44	420/A/A	BSW	✓	✓	✓
215/55R17	94V	7J	226	668	670	1477	300/44	420/A/A	BSW	✓	✓	✓
215/60R15	94H	6 1/2J	221	639	670	1477	300/44	420/A/A	BSW	✓	✓	✓
215/60R16	99H XL	6 1/2J	221	664	775	1709	340/50	420/A/A	BSW	✓	✓	✓
215/60R17	96T	6 1/2J	221	690	710	1565	300/44	420/A/A	BSW	✓	✓	✓
215/65R15	96H	6 1/2J	221	661	710	1565	300/44	420/A/A	BSW	✓	✓	✓
215/65R16	98H	6 1/2J	221	686	750	1653	300/44	420/A/A	BSW	✓	✓	✓
215/65R17	99T	6 1/2J	221	712	775	1709	300/44	420/A/A	BSW	✓	✓	✓
215/70R14	96H	6 1/2J	221	658	710	1565	300/44	420/A/A	BSW	✓	✓	✓
215/70R15	98H	6 1/2J	221	683	750	1653	300/44	420/A/A	BSW	✓	✓	✓
225/55R16	95V	7 J	233	654	690	1521	300/44	420/A/A	BSW	✓	✓	✓
225/55R17	101H	7 J	233	680	825	1818	340/50	420/A/A	BSW	✓	✓	✓
225/60R15	96V	6 1/2J	228	651	710	1565	300/44	420/A/A	BSW	✓	✓	✓
225/60R16	98H	6.5J	228	676	750	1653	300/44	420/A/A	BSW	✓	✓	✓
225/60R16	98V	6.5J	228	676	750	1653	300/44	420/A/A	BSW	✓	✓	✓
225/60R17	99H	6 1/2J	228	702	775	1708	300/44	420/A/A	BSW	✓	✓	✓
225/65R16	100T	6 1/2J	228	698	800	1764	300/44	420/A/A	BSW	✓	✓	✓
225/65R17	102H	6 1/2J	228	724	850	1873	300/44	420/A/A	BSW	✓	✓	✓
225/70R15	100H	6 1/2J	228	697	800	1764	300/44	420/A/A	BSW	✓	✓	✓
235/60R16	100H	7 J	240	688	800	1763	300/44	420/A/A	BSW	✓	✓	✓
235/65R16	103T	7J	240	712	875	1929	300/44	420/A/A	BSW	✓	✓	✓
235/65R17	104H	7J	240	738	900	1984	300/44	420/A/A	BSW	✓	✓	✓

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice

Asymmetrical pattern design, balanced and optimized pattern groove design

This design full of personality can improve excellent handling performance and give people an extraordinary double-sided charm visual experience. And also effectively reduce noise and improve tire comfort.

Wide longitudinal groove design

The wide longitudinal grooves can drain water quickly, effectively avoiding tire slipping on wet roads and improving wet handling.

Break through the traditional design of the lateral groove on the inner shoulder

It can reduce the rigidity of the tire shoulders, effectively suppress eccentric wear, block the transmission of noise from the central block, reduce tire noise, and bring excellent driving comfort.

Special hook groove design on outer shoulder

It can effectively reduce heat generation at the shoulder, reduce resonance during driving, and effectively reduce tire noise.



UTQG: 400/A/A

Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
155/60R15	74T	4.50B	157	567	375	827	300/44	400/A/A	BSW	✓	✓	✓
155/65R13	73T	4.50B	157	532	365	805	300/44	400/A/A	BSW	✓	✓	✓
155/65R14	75T	4.50B	157	558	387	853	300/44	400/A/A	BSW	✓	✓	✓
155/70R13	75T	4.50B	157	548	387	853	300/44	400/A/A	BSW	✓	✓	✓
155/80R13	79T	4.50B	157	578	437	963	300/44	400/A/A	BSW	✓	✓	✓
165/60R14	75H	5.00B	170	554	387	853	300/44	400/A/A	BSW	✓	✓	✓
165/60R15	81H XL	5.00B	170	579	462	1019	340/50	400/A/A	BSW	✓	✓	✓
165/65R13	77T	5.00B	170	544	412	908	300/44	400/A/A	BSW	✓	✓	✓
165/65R15	81H	5J	170	595	462	1019	300/44	400/A/A	BSW	✓	✓	✓
165/70R14	85T XL	5.00B	170	588	515	1135	340/50	400/A/A	BSW	✓	✓	✓
165/70R14	81T	5.00B	170	588	462	1019	300/44	400/A/A	BSW	✓	✓	✓
175/50R16	77V	5 1/2J	182	582	412	908	300/44	400/A/A	BSW	✓	✓	✓
175/55R15	77H	5 1/2J	182	573	412	908	300/44	400/A/A	BSW	✓	✓	✓
175/60R14	79H	5.00B	177	566	437	963	300/44	400/A/A	BSW	✓	✓	✓
175/60R15	81H	5J	177	591	462	1019	300/44	400/A/A	BSW	✓	✓	✓
175/65R14	86T XL	5.00B	177	584	530	1168	340/50	400/A/A	BSW	✓	✓	✓
175/65R14	82H	5.00B	177	584	475	1047	300/44	400/A/A	BSW	✓	✓	✓
175/65R15	84H	5J	177	609	500	1102	300/44	400/A/A	BSW	✓	✓	✓
175/70R13	82T	5.00B	177	576	475	1047	300/44	400/A/A	BSW	✓	✓	✓
175/70R14	88T XL	5.00B	177	602	560	1235	340/50	400/A/A	BSW	✓	✓	✓
175/70R14	84T	5.00B	177	602	500	1102	300/44	400/A/A	BSW	✓	✓	✓
185/50R14	77V	6J	194	542	412	908	300/44	400/A/A	BSW	✓	✓	✓
185/50R16	81V	6J	194	592	462	1019	300/44	400/A/A	BSW	✓	✓	✓
185/55R14	80H	6J	194	560	450	992	300/44	400/A/A	BSW	✓	✓	✓
185/55R15	82V	6J	194	585	475	1047	300/44	400/A/A	BSW	✓	✓	✓
185/55R16	87V XL	6J	194	610	545	1202	340/50	400/A/A	BSW	✓	✓	✓
185/60R14	82H	5 1/2J	189	578	475	1047	300/44	400/A/A	BSW	✓	✓	✓
185/60R15	88H XL	5 1/2J	189	603	560	1235	340/50	400/A/A	BSW	✓	✓	✓
185/60R15	84H	5 1/2J	189	603	500	1102	300/44	400/A/A	BSW	✓	✓	✓
185/65R14	86H	5 1/2J	189	596	530	1168	300/44	400/A/A	BSW	✓	✓	✓
185/65R15	88H	5 1/2J	189	621	560	1235	300/44	400/A/A	BSW	✓	✓	✓
185/70R14	88T	5 1/2J	189	616	560	1235	300/44	400/A/A	BSW	✓	✓	✓
195/50R15	82V	6J	201	577	475	1047	300/44	400/A/A	BSW	✓	✓	✓
195/50R16	88V XL	6J	201	602	560	1235	340/50	400/A/A	BSW	✓	✓	✓
195/55R15	85V	6J	201	595	515	1135	300/44	400/A/A	BSW	✓	✓	✓
195/55R16	91V XL	6J	201	620	615	1356	340/50	400/A/A	BSW	✓	✓	✓
195/60R15	88V	6J	201	615	560	1235	300/44	400/A/A	BSW	✓	✓	✓
195/60R15	88H	6J	201	615	560	1235	300/44	400/A/A	BSW	✓	✓	✓
195/65R14	89H	6J	201	610	580	1279	300/44	400/A/A	BSW	✓	✓	✓
195/65R15	95T XL	6J	201	635	690	1521	340/50	400/A/A	BSW	✓	✓	✓
195/65R15	91V	6J	201	635	615	1356	300/44	400/A/A	BSW	✓	✓	✓
205/50R16	91W XL	6 1/2J	214	612	615	1356	340/50	400/A/A	BSW	✓	✓	✓
205/55R16	94W XL	6 1/2J	214	632	670	1477	340/50	400/A/A	BSW	✓	✓	✓
205/55R16	91V	6 1/2J	214	632	615	1356	300/44	400/A/A	BSW	✓	✓	✓
205/60R15	91V	6J	209	627	615	1356	300/44	400/A/A	BSW	✓	✓	✓
205/60R16	96V XL	6J	209	652	710	1565	340/50	400/A/A	BSW	✓	✓	✓
205/60R16	92V	6J	209	652	630	1389	300/44	400/A/A	BSW	✓	✓	✓
205/65R15	94V	6J	209	647	670	1477	300/44	400/A/A	BSW	✓	✓	✓
215/55R16	97W XL	7J	226	642	730	1609	340/50	400/A/A	BSW	✓	✓	✓
215/60R16	99H XL	6 1/2J	221	664	775	1709	340/50	400/A/A	BSW	✓	✓	✓
215/60R16	95V	6 1/2J	221	664	690	1521	300/44	400/A/A	BSW	✓	✓	✓
215/65R15	96H	6 1/2J	221	661	710	1565	300/44	400/A/A	BSW	✓	✓	✓
215/65R16	98H	6 1/2J	221	686	750	1653	300/44	400/A/A	BSW	✓	✓	✓
225/55R16	99W XL	7J	233	654	775	1709	340/50	400/A/A	BSW	✓	✓	✓
225/60R16	102V XL	6 1/2J	228	676	850	1874	340/50	400/A/A	BSW	✓	✓	✓

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice

Asymmetric tread pattern

Asymmetric tread pattern design with lateral grooves linked inside provide excellent drainage performance.

Wide and large shoulder

Wide and large shoulder blocks with sipes design ensure the blocks peristalsis slightly while turning corner and changing lanes, bring stable handling and great driving performance.

Linked pattern

Linked pattern design. Linked pattern design reduce the driving noise and provide great wetland grip performance.

Vertical ribs

Vertical ribs improve high-speed driving stability.



UTQG: 300/A/A

Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Handling

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
195/40R17	81W	7J	200	588	462	1019	340/50	300/A/A	BSW	✓	✓	✓
195/45R15	82V XL	6 1/2J	195	557	475	1047	340/50	300/A/A	BSW	✓	✓	✓
195/45R16	84W	6 1/2J	195	582	500	1102	340/50	300/A/A	BSW	✓	✓	✓
195/50R16	84V	6J	201	602	500	1102	300/44	300/A/A	BSW	✓	✓	✓
195/55R20	91V	6J	201	722	615	1356	300/44	300/A/A	BSW	✓	✓	✓
205/40R17	84W	7 1/2J	212	596	500	1102	340/50	300/A/A	BSW	✓	✓	✓
205/45R16	87W	7J	206	590	545	1201	340/50	300/A/A	BSW	✓	✓	✓
205/45R17	88W	7J	206	616	560	1235	340/50	300/A/A	BSW	✓	✓	✓
205/50R16	91W	6 1/2J	214	612	615	1356	340/50	300/A/A	BSW	✓	✓	✓
205/50R17	93W	6 1/2J	214	638	650	1433	340/50	300/A/A	BSW	✓	✓	✓
205/55R16	91W	6 1/2J	214	632	615	1356	300/44	300/A/A	BSW	✓	✓	✓
205/55R16	94W	6 1/2J	214	632	670	1477	340/50	300/A/A	BSW	✓	✓	✓
205/55R19	97V XL	6 1/2J	214	709	730	1609	340/50	300/A/A	BSW	✓	✓	✓
205/55ZR17	95W XL	6 1/2J	214	658	690	1521	340/50	300/A/A	BSW	✓	✓	✓
215/35R18	84W	7 1/2J	218	607	500	1102	340/50	300/A/A	BSW	✓	✓	✓
215/40R17	87W	7 1/2J	218	604	545	1202	340/50	300/A/A	BSW	✓	✓	✓
215/40R18	89W	7 1/2J	218	629	580	1279	340/50	300/A/A	BSW	✓	✓	✓
215/45R17	91W	7 J	213	626	615	1356	340/50	300/A/A	BSW	✓	✓	✓
215/45R18	93W	7J	213	651	650	1433	340/50	300/A/A	BSW	✓	✓	✓
215/50R17	95W	7 J	226	648	690	1521	340/50	300/A/A	BSW	✓	✓	✓
215/50ZR18	92W	7J	226	673	630	1389	300/44	300/A/A	BSW	✓	✓	✓
215/55R16	97W	7J	226	642	730	1609	340/50	300/A/A	BSW	✓	✓	✓
215/55R17	94W	7 J	226	668	670	1477	300/44	300/A/A	BSW	✓	✓	✓
215/55R18	99W	7J	226	693	775	1709	340/50	300/A/A	BSW	✓	✓	✓
225/30ZR20	85W	8 J	230	644	515	1135	340/50	300/A/A	BSW	✓	✓	✓
225/35R19	84W	8J	230	641	500	1102	300/44	300/A/A	BSW	✓	✓	✓
225/35R20	90W	8J	230	666	600	1323	340/50	300/A/A	BSW	✓	✓	✓
225/40R18	92W	8 J	230	637	630	1389	340/50	300/A/A	BSW	✓	✓	✓
225/40ZR19	93W XL	8J	230	663	650	1433	340/50	300/A/A	BSW	✓	✓	✓
225/45R17	94W	7 1/2J	225	634	670	1477	340/50	300/A/A	BSW	✓	✓	✓
225/45R18	95W	7 1/2J	225	659	690	1521	340/50	300/A/A	BSW	✓	✓	✓
225/50R17	98W	7J	233	658	750	1653	340/50	300/A/A	BSW	✓	✓	✓
225/50ZR18	99W XL	7J	233	683	775	1709	340/50	300/A/A	BSW	✓	✓	✓
225/55R16	99W	7 J	233	654	775	1709	340/50	300/A/A	BSW	✓	✓	✓
225/55R17	97V	7J	233	680	730	1609	300/44	300/A/A	BSW	✓	✓	✓
225/55R17	101W	7J	233	680	825	1819	340/50	300/A/A	BSW	✓	✓	✓
225/55R18	102W XL	7 J	233	705	850	1874	340/50	300/A/A	BSW	✓	✓	✓
225/55R19	99V	7 J	233	731	775	1709	300/44	300/A/A	BSW	✓	✓	✓
235/30R22	90W XL	8 1/2J	242	701	600	1323	340/50	300/A/A	BSW	✓	✓	✓
235/30ZR20	88W XL	8 1/2J	241	650	560	1235	340/50	300/A/A	BSW	✓	✓	✓
235/35R19	91W	8 1/2J	241	647	615	1356	340/50	300/A/A	BSW	✓	✓	✓
235/35R20	92W	8 1/2J	241	672	630	1389	340/50	300/A/A	BSW	✓	✓	✓
235/40R18	95W	8 1/2J	241	645	690	1521	340/50	300/A/A	BSW	✓	✓	✓
235/45R17	97W	8 J	236	644	730	1609	340/50	300/A/A	BSW	✓	✓	✓
235/45R18	98W XL	8 J	236	669	750	1653	340/50	300/A/A	BSW	✓	✓	✓

L-ZEAL 56

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
235/45R19	95W	8J	236	695	695	1521	300/44	300/A/A	BSW	✓	✓	✓
235/50R17	100W XL	7 1/2J	245	668	668	1764	340/50	300/A/A	BSW	✓	✓	✓
235/50R18	97V	7 1/2J	245	693	693	1609	300/44	300/A/A	BSW	✓	✓	✓
235/50R19	103V	7 1/2J	245	719	719	1929	340/50	300/A/A	BSW	✓	✓	✓
235/50ZR20	104W XL	7 1/2J	245	744	744	1984	340/50	300/A/A	BSW	✓	✓	✓
235/55R17	99V	7 1/2J	245	690	690	1709	300/44	300/A/A	BSW	✓	✓	✓
235/55R17	103W	7 1/2J	245	690	690	1929	340/50	300/A/A	BSW	✓	✓	✓
235/55R18	104V	7 1/2J	245	715	715	1984	340/50	300/A/A	BSW	✓	✓	✓
235/55R19	105V	7 1/2J	245	741	741	2039	340/50	300/A/A	BSW	✓	✓	✓
235/55ZR20	105W XL	7 1/2J	245	766	766	2039	340/50	300/A/A	BSW	✓	✓	✓
245/30R22	92W XL	8 1/2J	248	707	707	1389	340/50	300/A/A	BSW	✓	✓	✓
245/30ZR20	95W XL	8 1/2J	248	656	656	1521	340/50	300/A/A	BSW	✓	✓	✓
245/35R19	93W	8 1/2J	248	655	655	1433	340/50	300/A/A	BSW	✓	✓	✓
245/35R20	95W	8 1/2J	248	680	680	1521	340/50	300/A/A	BSW	✓	✓	✓
245/35ZR21	96W XL	8 1/2J	248	705	705	1565	340/50	300/A/A	BSW	✓	✓	✓
245/40R17	95W XL	8 1/2J	248	628	628	1521	340/50	300/A/A	BSW	✓	✓	✓
245/40R18	97W	8 1/2J	248	653	653	1609	340/50	300/A/A	BSW	✓	✓	✓
245/40ZR19	98W XL	8 1/2J	248	679	679	1653	340/50	300/A/A	BSW	✓	✓	✓
245/40ZR20	99W	8 1/2J	248	704	704	1709	340/50	300/A/A	BSW	✓	✓	✓
245/45R17	99W XL	8 J	243	652	652	1709	340/50	300/A/A	BSW	✓	✓	✓
245/45R18	100W	8 J	243	677	677	1764	340/50	300/A/A	BSW	✓	✓	✓
245/45R19	98W	8J	243	703	703	1653	300/44	300/A/A	BSW	✓	✓	✓
245/45ZR20	103W XL	8J	243	728	728	1929	340/50	300/A/A	BSW	✓	✓	✓
245/50R18	100V	7 1/2J	253	703	703	1764	300/44	300/A/A	BSW	✓	✓	✓
245/50R19	105V XL	7 1/2J	253	729	729	2039	340/50	300/A/A	BSW	✓	✓	✓
245/50ZR20	105W XL	7 1/2J	253	754	754	2039	340/50	300/A/A	BSW	✓	✓	✓
245/55R19	103V	7 1/2J	253	753	753	1929	300/44	300/A/A	BSW	✓	✓	✓
255/30R22	95W XL	9 J	260	713	713	1521	340/50	300/A/A	BSW	✓	✓	✓
255/30ZR20	92Y XL	9J	260	662	662	1389	340/50	300/A/A	BSW	✓	✓	✓
255/30ZR21	93W XL	9J	260	687	687	1433	340/50	300/A/A	BSW	✓	✓	✓
255/30ZR24	97W	9 J	260	764	764	1609	340/50	300/A/A	BSW	✓	✓	✓
255/35R19	96W	9J	260	661	661	1565	340/50	300/A/A	BSW	✓	✓	✓
255/35R20	97W	9J	260	686	686	1609	340/50	300/A/A	BSW	✓	✓	✓
255/35ZR18	94W	9 J	260	635	635	1477	340/50	300/A/A	BSW	✓	✓	✓
255/40ZR18	99W XL	9J	260	661	661	1709	340/50	300/A/A	BSW	✓	✓	✓
255/45R18	99W	8 1/2J	255	687	687	1709	300/44	300/A/A	BSW	✓	✓	✓
255/45R19	100W	8 1/2J	255	713	713	1764	300/44	300/A/A	BSW	✓	✓	✓
255/45ZR20	105W XL	8 1/2J	255	738	738	2039	340/50	300/A/A	BSW	✓	✓	✓
255/50R18	106V XL	8J	265	713	713	2094	340/50	300/A/A	BSW	✓	✓	✓
255/50R19	103V	8J	265	739	739	1929	300/44	300/A/A	BSW	✓	✓	✓
255/50R20	109V XL	8J	265	764	764	2271	340/50	300/A/A	BSW	✓	✓	✓
255/55R18	105V	8 J	265	737	737	2039	300/44	300/A/A	BSW	✓	✓	✓
255/55R19	111V XL	8J	265	763	763	2403	340/50	300/A/A	BSW	✓	✓	✓
265/30ZR19	93W	9 1/2J	271	643	643	1433	340/50	300/A/A	BSW	✓	✓	✓
265/30ZR22	97W	9 1/2J	271	719	719	1609	340/50	300/A/A	BSW	✓	✓	✓

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
265/35ZR18	97W	9 1/2J	271	643	730	1609	340/50	300/A/A	BSW	✓	✓	✓
265/40ZR18	101W XL	9 1/2J	271	669	825	1819	340/50	300/A/A	BSW	✓	✓	✓
265/45ZR20	108W XL	9J	266	746	1000	2205	340/50	300/A/A	BSW	✓	✓	✓
265/45ZR22	110W XL	9J	266	797	1060	2337	340/50	300/A/A	BSW	✓	✓	✓
265/50R19	110V XL	8 1/2J	277	749	1060	2337	340/50	300/A/A	BSW	✓	✓	✓
265/50R20	111V XL	8 1/2J	277	774	1090	2403	340/50	300/A/A	BSW	✓	✓	✓
275/30R20	97W XL	9 1/2J	278	674	730	1609	340/50	300/A/A	BSW	✓	✓	✓
275/30ZR19	96W	9 1/2J	278	649	710	1565	340/50	300/A/A	BSW	✓	✓	✓
275/30ZR21	98W XL	9 1/2J	278	699	750	1653	340/50	300/A/A	BSW	✓	✓	✓
275/35ZR19	100W XL	9 1/2J	278	675	800	1764	340/50	300/A/A	BSW	✓	✓	✓
275/35ZR20	102W	9 1/2J	278	700	850	1874	340/50	300/A/A	BSW	✓	✓	✓
275/40ZR18	103W XL	9 1/2J	278	677	875	1929	340/50	300/A/A	BSW	✓	✓	✓
275/40ZR19	105W XL	9 1/2J	278	703	925	2039	340/50	300/A/A	BSW	✓	✓	✓
275/40ZR20	106W XL	9 1/2J	278	728	950	2094	340/50	300/A/A	BSW	✓	✓	✓
275/40ZR21	107W XL	9 1/2J	278	753	975	2149	340/50	300/A/A	BSW	✓	✓	✓
275/45R19	108V XL	9J	273	731	1000	2205	340/50	300/A/A	BSW	✓	✓	✓
275/45R20	110V XL	9J	273	756	1060	2337	340/50	300/A/A	BSW	✓	✓	✓
275/45ZR21	110W XL	9J	273	781	1060	2337	340/50	300/A/A	BSW	✓	✓	✓
275/50R20	113V XL	8 1/2J	284	784	1150	2535	340/50	300/A/A	BSW	✓	✓	✓
275/50R21	113V XL	8 1/2J	284	809	1150	2535	340/50	300/A/A	BSW	✓	✓	✓
275/55R19	111V	8 1/2J	284	785	1090	2403	300/44	300/A/A	BSW	✓	✓	✓
275/55R20	117V XL	8 1/2J	284	810	1285	2833	340/50	300/A/A	BSW	✓	✓	✓
275/60R20	119H XL	8J	279	838	1360	2998	340/50	300/A/A	BSW	✓	✓	✓
285/30ZR20	99W	10 J	290	680	775	1709	340/50	300/A/A	BSW	✓	✓	✓
285/35ZR18	101W	10 J	290	657	825	1819	340/50	300/A/A	BSW	✓	✓	✓
285/35ZR22	106W XL	10	290	759	950	2094	340/50	300/A/A	BSW	✓	✓	✓
285/45R19	107V	9 1/2J	285	739	975	2149	300/44	300/A/A	BSW	✓	✓	✓
285/50R20	116V XL	9J	297	794	1250	2756	340/50	300/A/A	BSW	✓	✓	✓
285/50R22	118V XL	9J	297	845	1320	2910	340/50	300/A/A	BSW	✓	✓	✓
295/25ZR22	97W	10 1/2J	301	707	730	1609	340/50	300/A/A	BSW	✓	✓	✓
295/40R22	112V XL	10 1/2J	301	795	1120	2469	340/50	300/A/A	BSW	✓	✓	✓
305/35R20	107V XL	11J	313	722	975	2149	340/50	300/A/A	BSW	✓	✓	✓
305/40R20	112V XL	11J	313	752	1120	2469	340/50	300/A/A	BSW	✓	✓	✓
315/35ZR20	110W XL	11 J	320	728	1060	2337	340/50	300/A/A	BSW	✓	✓	✓
315/35ZR21	111W XL	11J	320	753	1090	2403	340/50	300/A/A	BSW	✓	✓	✓
315/40R21	115V XL	11J	320	785	1215	2679	340/50	300/A/A	BSW	✓	✓	✓

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice





"V-shaped" pattern design

30 multi-angle "V-shaped" pattern design ensure high-speed handling and stability in straight lines and bends.

"Y-shaped" directional pattern design

"Y-shaped" directional pattern design provides excellent horizontal or vertical drainage performance.

Shoulder design

Open shoulder design self-cleans the slush in the grooves.

Tread pattern design

Central longitudinal ribs increase the contact area with road surface, and enhance braking performance in any road conditions.



UTQG: 400/A/A

Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
255/50R20	109V XL	8J	265	764	1030	2271	340/50	400/A/A	BSW	✓	✓	✓
255/55R19	111V	8 J	265	763	1090	2403	340/50	400/A/A	BSW	✓	✓	✓
255/55R20	110V XL	8J	265	788	1060	2337	340/50	400/A/A	BSW	✓	✓	✓
265/35ZR22	102W XL	9 1/2J	271	745	850	1874	340/50	400/A/A	BSW	✓	✓	✓
265/40R22	106V XL	9 1/2J	271	771	950	2094	340/50	400/A/A	BSW	✓	✓	✓
265/50R20	111V	8 1/2J	277	774	1090	2403	340/50	400/A/A	BSW	✓	✓	✓
275/25ZR24	96W	10J	283	748	710	1565	340/50	400/A/A	BSW	✓	✓	✓
275/40ZR20	106W XL	9 1/2J	278	728	950	2094	340/50	400/A/A	BSW	✓	✓	✓
275/40ZR22	107W XL	9 1/2J	275	779	975	2149	340/50	400/A/A	BSW	✓	✓	✓
275/45R20	110V XL	9 J	273	756	1060	2337	340/50	400/A/A	BSW	✓	✓	✓
275/55R20	117V XL	8 1/2J	284	810	1285	2833	340/50	400/A/A	BSW	✓	✓	✓
275/60R20	119H XL	8 J	279	838	1360	2998	340/50	400/A/A	BSW	✓	✓	✓
285/35ZR22	106W	10 J	290	759	950	2094	340/50	400/A/A	BSW	✓	✓	✓
285/40R22	110V	10 J	290	787	1060	2337	340/50	400/A/A	BSW	✓	✓	✓
285/45R22	114V XL	9 1/2J	285	815	1180	2601	340/50	400/A/A	BSW	✓	✓	✓
285/50R20	116V	9 J	297	794	1250	2756	340/50	400/A/A	BSW	✓	✓	✓
295/30ZR22	103W	10 1/2J	301	737	875	1929	340/50	400/A/A	BSW	✓	✓	✓
295/35ZR24	110W	10 1/2J	301	816	1060	2337	340/50	400/A/A	BSW	✓	✓	✓
295/45ZR20	114W	10 J	296	774	1180	2601	340/50	400/A/A	BSW	✓	✓	✓
305/35ZR24	112W	11J	313	824	1120	2469	340/50	400/A/A	BSW	✓	✓	✓
305/40R22	114V XL	11 J	313	803	1180	2601	340/50	400/A/A	BSW	✓	✓	✓
305/45R22	118V XL	10J	303	833	1320	2910	340/50	400/A/A	BSW	✓	✓	✓
315/35ZR20	110W XL	11J	320	728	1060	2337	340/50	400/A/A	BSW	✓	✓	✓

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice



UTQG: 400/A/A

Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Handling

Asymmetric tread pattern

Asymmetric tread pattern design and functionally differentiated in medial and lateral sidewall improve steering performance in wet road conditions, and ensure high-speed stability.

Silicon-containing tread compound

New Silicon-containing tread compound enhance grip in wet road conditions and reduce rolling resistance.

Low-noise design

Creative tread grooves' fine lines design effectively reduce noise at high-speed driving.

Anti-skip design

A mass of steel sheets and grooves design provide great grip ability and driving performance on wetland.

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
NEW 165/35R17	68V XL	6 J	170	547	315	694	340/50	400/A/A	BSW	-	-	-
165/40R17	72V	6 J	170	564	355	783	340/50	400/A/A	BSW	✓	✓	✓
NEW 165/45R17	76V XL	5 1/2J	165	579	400	882	340/50	400/A/A	BSW	-	-	-
185/35R17	82V	6 1/2J	183	562	475	1047	340/50	400/A/A	BSW	✓	✓	✓
185/35R18	83V	6 1/2J	183	587	487	1074	340/50	400/A/A	BSW	✓	✓	✓
NEW 185/40R17	78V XL	6 1/2J	188	580	425	937	340/50	400/A/A	BSW	-	-	-
195/45R16	84V XL	6 1/2J	195	582	500	1102	340/50	400/A/A	BSW	✓	✓	✓
195/45ZR17	85W XL	6 1/2J	195	608	515	1135	340/50	400/A/A	BSW	✓	✓	✓
205/35R20	84V	7 1/2J	212	652	500	1102	340/50	400/A/A	BSW	✓	✓	✓
205/40R17	84W XL	7 1/2J	212	596	500	1102	340/50	400/A/A	BSW	✓	✓	✓
205/45R16	87W XL	7 J	206	590	545	1201	340/50	400/A/A	BSW	✓	✓	✓
205/45R17	88W XL	7 J	206	616	560	1235	340/50	400/A/A	BSW	✓	✓	✓
205/50R16	91W XL	6 1/2J	214	612	615	1356	340/50	400/A/A	BSW	✓	✓	✓
205/50R17	93W XL	6 1/2J	214	638	650	1433	340/50	400/A/A	BSW	✓	✓	✓
205/55R16	94W XL	6 1/2J	214	632	670	1477	340/50	400/A/A	BSW	✓	✓	✓
205/55ZR17	95W XL	6 1/2J	214	658	690	1521	340/50	400/A/A	BSW	✓	✓	✓
215/35ZR18	84W XL	7 1/2J	218	607	500	1102	340/50	400/A/A	BSW	✓	✓	✓
215/35ZR19	85W XL	7 1/2J	218	633	515	1135	340/50	400/A/A	BSW	✓	✓	✓
215/40ZR16	86W XL	7 1/2J	218	578	530	1168	340/50	400/A/A	BSW	✓	✓	✓
215/40ZR17	87W XL	7 1/2J	218	604	545	1201	340/50	400/A/A	BSW	✓	✓	✓
215/40ZR18	89W XL	7 1/2J	218	629	580	1279	340/50	400/A/A	BSW	✓	✓	✓
215/45R16	90V XL	7J	213	600	600	1323	340/50	400/A/A	BSW	✓	✓	✓
215/45R17	91W XL	7 J	213	626	615	1356	340/50	400/A/A	BSW	✓	✓	✓
215/45ZR18	93W XL	7J	213	651	650	1433	340/50	400/A/A	BSW	✓	✓	✓
215/50R17	95W XL	7 J	226	648	690	1521	340/50	400/A/A	BSW	✓	✓	✓
215/55R17	98W XL	7 J	226	668	750	1653	340/50	400/A/A	BSW	✓	✓	✓
215/55R18	99V	7 J	226	693	775	1709	340/50	400/A/A	BSW	✓	✓	✓
215/55ZR16	97W XL	7J	226	642	730	1609	340/50	400/A/A	BSW	✓	✓	✓
225/35ZR19	88W XL	8J	230	641	560	1235	340/50	400/A/A	BSW	✓	✓	✓
225/35ZR20	90W	8 J	230	666	600	1323	340/50	400/A/A	BSW	✓	✓	✓

THUNDER U09

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
225/40R18	92W XL	8 J	230	637	630	1389	340/50	400/A/A	BSW	√	√	√
225/45R17	94W XL	7 1/2J	225	634	670	1477	340/50	400/A/A	BSW	√	√	√
225/45R18	95W XL	7 1/2J	225	659	690	1521	340/50	400/A/A	BSW	√	√	√
225/45ZR19	96W XL	7 1/2J	225	685	710	1565	340/50	400/A/A	BSW	√	√	√
225/50R17	98W XL	7 J	233	658	750	1653	340/50	400/A/A	BSW	√	√	√
225/50ZR16	96W XL	7J	233	632	710	1565	340/50	400/A/A	BSW	√	√	√
225/55R16	99W XL	7 J	233	654	775	1709	340/50	400/A/A	BSW	√	√	√
225/55R17	101W XL	7 J	233	680	825	1819	340/50	400/A/A	BSW	√	√	√
225/55R18	102V	7 J	233	705	850	1874	340/50	400/A/A	BSW	√	√	√
225/55R19	99V	7J	233	731	775	1709	300/44	400/A/A	BSW	√	√	√
235/35ZR19	91W XL	8 1/2J	241	647	615	1356	340/50	400/A/A	BSW	√	√	√
235/40R18	95W XL	8 1/2J	241	645	690	1521	340/50	400/A/A	BSW	√	√	√
235/40ZR19	96W	8 1/2J	241	671	710	1565	340/50	400/A/A	BSW	√	√	√
235/45R17	97W XL	8 J	236	644	730	1609	340/50	400/A/A	BSW	√	√	√
235/45ZR18	98W XL	8 J	236	669	750	1653	340/50	400/A/A	BSW	√	√	√
235/45ZR19	99W XL	8J	236	695	775	1709	340/50	400/A/A	BSW	√	√	√
235/50R17	100V	7 1/2J	245	668	800	1764	340/50	400/A/A	BSW	√	√	√
235/50R18	97V	7 1/2J	245	693	730	1609	300/44	400/A/A	BSW	√	√	√
235/50ZR19	103W XL	7 1/2J	245	719	875	1929	340/50	400/A/A	BSW	√	√	√
235/55R18	104V	7 1/2J	245	715	900	1984	340/50	400/A/A	BSW	√	√	√
235/55R19	105V XL	7 1/2J	245	741	925	2039	340/50	400/A/A	BSW	√	√	√
235/55ZR17	103W	7 1/2J	245	690	875	1929	340/50	400/A/A	BSW	√	√	√
245/35ZR19	93W XL	8 1/2J	248	655	650	1433	340/50	400/A/A	BSW	√	√	√
245/35ZR20	95WXL	8 1/2J	248	680	690	1521	340/50	400/A/A	BSW	√	√	√
245/40R18	97W XL	8 1/2J	248	653	730	1609	340/50	400/A/A	BSW	√	√	√
245/40ZR17	95W XL	8 1/2J	248	628	690	1521	340/50	400/A/A	BSW	√	√	√
245/40ZR19	98W XL	8 1/2J	248	679	750	1653	340/50	400/A/A	BSW	√	√	√
245/40ZR20	99WXL	8 1/2J	248	704	775	1709	340/50	400/A/A	BSW	√	√	√
245/45R18	100W XL	8 J	243	677	800	1764	340/50	400/A/A	BSW	√	√	√
245/45R19	102W XL	8 J	243	703	850	1874	340/50	400/A/A	BSW	√	√	√

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
245/45ZR17	99W	8 J	243	652	775	1709	340/50	400/A/A	BSW	√	√	√
245/50ZR18	104W	7 1/2J	253	703	900	1984	340/50	400/A/A	BSW	√	√	√
245/55R19	107V XL	7 1/2J	253	753	975	2149	340/50	400/A/A	BSW	√	√	√
255/30ZR19	91Y XL	9J	260	637	615	1356	340/50	400/A/A	BSW	√	√	√
255/35ZR18	94W XL	9J	260	635	670	1477	340/50	400/A/A	BSW	√	√	√
255/35ZR19	96W XL	9J	260	661	710	1565	340/50	400/A/A	BSW	√	√	√
255/35ZR20	97W XL	9J	260	686	730	1609	340/50	400/A/A	BSW	√	√	√
255/40ZR18	99W XL	9J	260	661	775	1709	340/50	400/A/A	BSW	√	√	√
255/40ZR19	100W XL	9J	260	687	800	1764	340/50	400/A/A	BSW	√	√	√
255/45ZR18	103W	8 1/2J	255	687	875	1929	340/50	400/A/A	BSW	√	√	√
255/45ZR19	104W XL	8 1/2J	255	713	900	1984	340/50	400/A/A	BSW	√	√	√
255/50R19	107V XL	8J	265	739	975	2149	340/50	400/A/A	BSW	√	√	√
255/55R18	109V	8 J	265	737	1030	2271	340/50	400/A/A	BSW	√	√	√
265/35ZR18	97W XL	9 1/2J	271	643	730	1609	340/50	400/A/A	BSW	√	√	√
265/45ZR21	108W XL	9J	266	771	1000	2205	340/50	400/A/A	BSW	√	√	√
275/30ZR19	96W XL	9 1/2J	278	649	710	1565	340/50	400/A/A	BSW	√	√	√
275/30ZR20	97W XL	9 1/2J	278	674	730	1609	340/50	400/A/A	BSW	√	√	√
275/35ZR18	99W XL	9 1/2J	278	649	775	1709	340/50	400/A/A	BSW	√	√	√
275/35ZR19	100Y XL	9 1/2J	278	675	800	1764	340/50	400/A/A	BSW	√	√	√
275/35ZR20	102W XL	9 1/2J	278	700	850	1874	340/50	400/A/A	BSW	√	√	√
275/40ZR19	105W XL	9 1/2J	278	703	925	2039	340/50	400/A/A	BSW	√	√	√
275/45ZR21	110W XL	9J	273	781	1060	2337	340/50	400/A/A	BSW	√	√	√
285/45R19	111V XL	9 1/2J	285	739	1090	2403	340/50	400/A/A	BSW	√	√	√
295/35ZR21	107W XL	10 1/2J	301	739	975	2149	340/50	400/A/A	BSW	√	√	√
295/40ZR21	111W XL	10 1/2J	301	769	1090	2403	340/50	400/A/A	BSW	√	√	√

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice

L-ZEAL 56 RUN FLAT

21 / 22



High-strength bead structure

High-strength bead structure design prevents the tires from falling off the ring when driving at 0 air pressure, and improves the driving durability.

Apex Low-heat-generation formula design

Low-heat-generation formula design of apex can effectively reduce the heat generated when the tire is running under pressure and improve the durability.

Sidewall with high-strength cord reinforcement layer

Sidewall adopts a high-strength cord reinforcement layer to increase the sidewall strength, maintain good thermal stability under pressure shortage, and improve low-pressure durability.

Sidewall with dual composite sidewall support rubber

Sidewall adopts dual composite sidewall support rubber, which has high support strength and good buffering performance. Unique formula design can improve sidewall strength and reduce heat generation, increasing sidewall durability and providing safe driving.



UTQG: 300/A/A

Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Handling

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
					(kg)	(Lbs)						
205/45ZRF17	88W XL	7J	206	616	560	1235	340/50	300/A/A	BSW	✓	✓	✓
205/50ZRF17	93W XL	6 1/2J	214	638	650	1433	340/50	300/A/A	BSW	✓	✓	✓
215/55ZRF18	99W XL	7J	226	693	775	1709	340/50	300/A/A	BSW	✓	✓	✓
225/35ZRF19	84W	8J	230	641	500	1102	300/44	300/A/A	BSW	✓	✓	✓
225/40ZRF18	92W XL	8 J	230	637	630	1389	340/50	300/A/A	BSW	✓	✓	✓
225/40ZRF19	93W XL	8J	230	663	650	1433	340/50	300/A/A	BSW	✓	✓	✓
225/45ZRF17	94W XL	7 1/2J	225	634	670	1477	340/50	300/A/A	BSW	✓	✓	✓
225/45ZRF18	95W XL	7 1/2J	225	659	690	1521	340/50	300/A/A	BSW	✓	✓	✓
225/50ZRF17	98W XL	7J	233	658	750	1653	340/50	300/A/A	BSW	✓	✓	✓
225/50ZRF18	95W	7J	233	683	690	1521	300/44	300/A/A	BSW	✓	✓	✓
225/55RF17	97V	7J	233	680	730	1609	300/44	300/A/A	BSW	✓	✓	✓
235/35ZRF19	91W XL	8 1/2J	241	647	615	1356	340/50	300/A/A	BSW	✓	✓	✓
235/45ZRF19	95W	8J	236	695	690	1521	300/44	300/A/A	BSW	✓	✓	✓
235/50RF18	97V	7 1/2J	245	693	730	1609	300/44	300/A/A	BSW	✓	✓	✓
235/50RF19	99V	7 1/2J	245	719	775	1709	300/44	300/A/A	BSW	✓	✓	✓
235/55RF17	99V	7 1/2J	245	690	775	1709	300/44	300/A/A	BSW	✓	✓	✓
235/55RF18	100V	7 1/2J	245	715	800	1764	300/44	300/A/A	BSW	✓	✓	✓
235/55RF19	101V	7 1/2J	245	741	825	1819	300/44	300/A/A	BSW	✓	✓	✓
245/35ZRF19	93W XL	8 1/2J	248	655	650	1433	340/50	300/A/A	BSW	✓	✓	✓
245/35ZRF20	95W XL	8 1/2J	248	680	690	1521	340/50	300/A/A	BSW	✓	✓	✓
245/40ZRF17	95W XL	8 1/2J	248	628	690	1521	340/50	300/A/A	BSW	✓	✓	✓
245/40ZRF18	97W XL	8 1/2J	248	653	730	1609	340/50	300/A/A	BSW	✓	✓	✓
245/40ZRF19	98W XL	8 1/2J	248	679	750	1653	340/50	300/A/A	BSW	✓	✓	✓
245/40ZRF20	99W XL	8 1/2J	248	704	775	1709	340/50	300/A/A	BSW	✓	✓	✓
245/45ZRF17	99W XL	8 J	243	652	775	1709	340/50	300/A/A	BSW	✓	✓	✓
245/45ZRF18	100W XL	8 J	243	677	800	1764	340/50	300/A/A	BSW	✓	✓	✓
245/45ZRF19	98W	8J	243	703	750	1653	300/44	300/A/A	BSW	✓	✓	✓
245/45ZRF20	103W XL	8J	243	728	875	1929	340/50	300/A/A	BSW	✓	✓	✓
245/50RF18	100V	7 1/2J	253	703	800	1764	300/44	300/A/A	BSW	✓	✓	✓
245/50RF19	105V XL	7 1/2J	253	729	925	2039	340/50	300/A/A	BSW	✓	✓	✓
255/35ZRF18	94W XL	9 J	260	635	670	1477	340/50	300/A/A	BSW	✓	✓	✓
255/35ZRF19	96W XL	9J	260	661	710	1565	340/50	300/A/A	BSW	✓	✓	✓
255/40ZRF18	99W XL	9J	260	661	775	1709	340/50	300/A/A	BSW	✓	✓	✓
255/45RF20	101V	8 1/2J	255	738	825	1819	300/44	300/A/A	BSW	✓	✓	✓
255/45ZRF18	99W	8 1/2J	255	687	775	1709	300/44	300/A/A	BSW	✓	✓	✓
255/45ZRF19	100W	8 1/2J	255	713	800	1764	300/44	300/A/A	BSW	✓	✓	✓
255/50RF19	103V	8J	265	739	875	1929	300/44	300/A/A	BSW	✓	✓	✓
255/55RF18	105V	8J	265	737	925	2039	300/44	300/A/A	BSW	✓	✓	✓
275/30ZRF20	97W XL	9 1/2J	278	674	730	1609	340/50	300/A/A	BSW	✓	✓	✓
275/35ZRF19	100W XL	9 1/2J	278	675	800	1763.68	340/50	300/A/A	BSW	✓	✓	✓
275/35ZRF20	102W XL	9 1/2J	278	700	850	1874	340/50	300/A/A	BSW	✓	✓	✓
275/40ZRF18	99W	9 1/2J	278	677	775	1709	300/44	300/A/A	BSW	✓	✓	✓
275/40ZRF19	105W XL	9 1/2J	278	703	925	2039	340/50	300/A/A	BSW	✓	✓	✓
275/40ZRF19	101W	9 1/2J	278	703	825	1819	300/44	300/A/A	BSW	✓	✓	✓
275/40ZRF20	102W	9 1/2J	278	728	850	1874	300/44	300/A/A	BSW	✓	✓	✓
285/45RF19	107V	9 1/2J	285	739	975	2149	300/44	300/A/A	BSW	✓	✓	✓
315/35ZRF20	110W XL	11 J	320	728	1060	2337	340/50	300/A/A	BSW	✓	✓	✓
315/35ZRF20	106W	11 J	320	728	950	2094.37	300/44	300/A/A	BSW	✓	✓	✓

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice

VAN

VAN

L-MAX9	31
L-STRONG36	33

LT

L-POWER28	35
TOURWAYS52	37



Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Silence design

Silence design of steel sheets. 700 pieces sipes divide the "Z" type tread blocks into small pieces greatly reduce tire noise and improve driving comfort, enjoying quiet and comfortable effect that same series tires cannot bring.

Simulate design

Simulate double "Y" tread pattern design improve grip performance without reducing tread blocks' rigidity, shorten braking distance, and improve driving safety.

Zigzag grooves

Zigzag pattern grooves design. Classic zigzag grooves provide excellent driving stability, and assure a smooth and comfortable ride.

White sidewall design

White sidewall. The white sidewall with 20mm width design is provided beautiful and dignified, suitable for car modification.

Size	LI/SI	PR	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	Sidewall			
						(kg)	(Lbs)					
165/70R14C	89/87R	8.5	5J	170	588	580/545	1279/1202	375/54	BSW	✓	✓	✓
175/65R14C	90/88R	8.5	5J	177	584	600/560	1323/1235	375/54	WSW	✓	✓	✓
175/75R16C	101/99R	9	5J	177	668	825/775	1819/1705	475/69	BSW	✓	✓	✓
185R14C	102/100R	8.2	5 1/2J	188	650	850/800	1875/1765	450/65	WSW	✓	✓	✓
185R14C	102/100R	9	5 1/2J	188	650	850/800	1875/1765	450/65	BSW	✓	✓	✓
185R15C	103/102R	8.2	5 1/2J	188	674	875/850	1929/1874	450/65	BSW	✓	✓	✓
195/60R16C	99/97T	8.5	6	201	640	775/730	1709/1609	375/54	BSW	✓	✓	✓
195/70R15C	104/102R	9	6J	201	655	900/850	1984/1874	450/65	BSW	✓	✓	✓
195/75R16C	107/105R	9	5 1/2J	196	698	975/925	2149/2039	475/69	BSW	✓	✓	✓
195R14C	106/104R	8.2	5 1/2J	198	666	950/900	2094/1984	450/65	WSW	✓	✓	✓
195R14C	106/104R	9	5 1/2J	198	666	950/900	2094/1984	450/65	BSW	✓	✓	✓
195R15C	106/104R	9	5 1/2J	196	693	950/900	2094/1984	450/65	BSW	✓	✓	✓
195R15C	106/104R	8.2	5 1/2J	196	693	950/900	2094/1984	450/65	BSW	✓	✓	✓
205/65R16C	107/105R	9	6J	209	672	975/925	2149/2039	475/69	BSW	✓	✓	✓
205/70R15C	106/104R	8.5	6	209	669	950/900	2094/1984	450/65	BSW	✓	✓	✓
205/75R14C	109/107R	8.5	5 1/2J	203	664	1030/975	2271/2149	475/69	BSW	✓	✓	✓
205/75R15C	109/107R	8.5	5 1/2J	203	689	1030/975	2271/2149	475/69	BSW	✓	✓	✓
205/75R16C	110/108R	8.5	5 1/2	203	714	1060/1000	2337/2204	475/69	BSW	✓	✓	✓
205R14C	109/107R	8.5	6J	208	686	1030/975	2271/2150	450/65	BSW	✓	✓	✓
215/60R16C	103/101T	8.5	6 1/2	221	664	875/825	1929/1819	375/54	BSW	✓	✓	✓
215/60R17C	109/107T	8.5	6 1/2J	221	690	1030/975	2271/2149	475/69	BSW	✓	✓	✓
215/65R15C	104/102R	8.5	6 1/2	221	661	900/850	1984/1874	375/54	BSW	✓	✓	✓
215/65R16C	109/107R	9	6 1/2J	221	686	1030/975	2271/2149	475/69	BSW	✓	✓	✓
215/70R15C	104/101R	9	6 1/2J	221	683	900/825	1984/1819	450/65	BSW	✓	✓	✓
NEW 215/70R16C	108/106R	8.5	6 1/2J	221	708	1000/950	2205/2094	375/54	BSW	✓	✓	✓
215/75R14C	112/110R	8.5	6J	216	678	1120/1060	2469/2337	475/69	BSW	✓	✓	✓
215/75R16C	116/114R	8.5	6J	216	728	1250/1180	2756/2601	525/76	BSW	✓	✓	✓
215R14C	112/110R	9	6J	218	700	1120/1060	2469/2337	450/65	BSW	✓	✓	✓
225/65R16C	112/110R	9	6 1/2J	228	698	1120/1060	2469/2337	475/69	BSW	✓	✓	✓
225/70R15C	112/110R	8.5	6 1/2	228	697	1120/1060	2469/2337	450/65	BSW	✓	✓	✓
225/75R16C	116/114R	8.5	6J	223	744	1250/1180	2756/2601	475/69	BSW	✓	✓	✓
235/65R16C	115/113R	9	7J	240	712	1215/1150	2679/2535	475/69	BSW	✓	✓	✓

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice



Zigzag grooves

Zigzag groove design. Zigzag and trailed main grooves enhance the strong traction; improve the drainage and anti-skip performance. Large slope tread grooves design provides excellent stone removing performance.

3D steel sheets

3D interlaced steel sheets design. 3D interlaced steel sheets increase the grip ability, braking force and safety of driving.

Closed shoulder

Coherent close shoulder design. Enhanced rid and coherent close block design on shoulder prevents the leaning-grind caused by heavy rigidity, and remain the high-speed turning agility at the same time.

Irregular patter

Irregular pattern and multi-pitch design brings silence and comfortable ride.



Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Size	LI/SI	PR	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	Sidewall			
						(kg)	(Lbs)					
145R12C	86/84Q	8	4.00B	145	537	530/500	1168/1102	450/65	BSW	✓	✓	✓
NEW 145R13C	88/86Q	8	4.00B	147	566	560/530	1235/1168	450/65	BSW	✓	✓	✓
155/70R12LT	104/102R	12	4.50B	157	523	900/850	1984/1874	650	BSW	✓	✓	✓
155R12LT/C	88/86S	8	4.50B	157	553	560/530	1235/1168	450/65	BSW	✓	✓	✓
155R13LT/C	90/88Q	8	4.50B	157	578	600/560	1323/1235	450/65	BSW	✓	✓	✓
165/70R13	79T	--	5.00B	170	562	437	964	300/44	BSW	✓	✓	✓
165/70R13LT	88/86R	6	5.00B	170	562	560/530	1235/1168	375	BSW	✓	✓	✓
165/70R14	81T	--	5J	170	588	462	1019	300/44	BSW	✓	✓	✓
165R13LT	94/93R	8	4.50B	165	594	670/650	1477/1433	450/65	BSW	✓	✓	✓
165R14LT	91/90R	6	4 1/2J	165	620	615/600	1356/1323	350/51	BSW	✓	✓	✓
175/70R14LT	95/93S	6	5J	177	602	690/650	1521/1433	375/54	BSW	✓	✓	✓
175/75R14LT	94/91R	8	5J	177	618	670/615	1477/1356	450/65	BSW	✓	✓	✓
175R13LT	97/95R	8	5.00B	177	610	730/690	1609/1521	450/65	BSW	✓	✓	✓
175R14LT	99/97R	8	5J	178	634	775/730	1709/1609	450/65	BSW	✓	✓	✓
NEW 5.00R12LT	83/81Q	8	3.50B	143	568	487/462	1074/1019	450/65	BSW	✓	✓	✓
NEW 5.50R12LT	92/90Q	10	3.50B	160	595	630/600	1389/1323	560/81	BSW	-	-	-
5.50R13LT	88/84Q	8	4.00B	160	620	560/500	1235/1102	460/67	BSW	-	-	-

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice

A/T M/T



H/T

A/T

R/T

M/T



Four wide vertical drainage grooves

Offer necessary high-speed performance of SUV and cross-country vehicle, provide great wetland drainage, and improve steering and handling ability on wet road.

Directional rib in the center of rownwith particularly

Designed lateral grooves and multiple sipes for balanced block rigidity, provide excellent drainage performance, ensure good handing performance in rain or snow.

Continuously closed design on the tire shoulder & supported by longitudinal vertical grooves

Reduce the rigidity of tire shoulder and restrain the eccentric wear effectively, block noise spread of central pattern, reduce the noise and bring extraordinary driving comfort.

Restrain the eccentric wear rib design on tire shoulder

Stabilize tire shoulder contour, reduce eccentric wear of tire shoulder, and improves the handling stability when turning at high speed.



UTQG: 420/A/A

Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Offroad

Size	LI/SI	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall	0-60	0-100	5-60
					(kg)	(Lbs)						
215/60R17	96H	6 1/2J	221	690	710	1565	300/44	420/A/A	BSW	✓	✓	✓
215/65R16	98H	6 1/2J	221	686	750	1653	300/44	420/A/A	BSW	✓	✓	✓
215/65R17	99V	6 1/2J	221	712	775	1709	300/44	420/A/A	BSW	✓	✓	✓
215/70R16	100H	6 1/2J	221	708	800	1764	300/44	420/A/A	BSW	✓	✓	✓
225/55R18	98H	7J	233	705	750	1653	300/44	420/A/A	BSW	✓	✓	✓
225/60R17	99H	6 1/2J	228	702	775	1709	300/44	420/A/A	BSW	✓	✓	✓
225/60R18	104H XL	6 1/2J	228	727	900	1984	340/50	420/A/A	BSW	✓	✓	✓
225/65R17	102H	6 1/2J	228	724	850	1874	300/44	420/A/A	BSW	✓	✓	✓
225/70R16	107H XL	6 1/2J	228	722	975	2149	340/50	420/A/A	BSW	✓	✓	✓
235/55R18	104H XL	7 1/2J	245	715	900	1984	340/50	420/A/A	BSW	✓	✓	✓
235/60R16	100H	7J	240	688	800	1764	300/44	420/A/A	BSW	✓	✓	✓
235/60R17	106H XL	7J	240	714	950	2094	340/50	420/A/A	BSW	✓	✓	✓
235/60R18	107H XL	7J	240	739	975	2149	340/50	420/A/A	BSW	✓	✓	✓
235/60R19	107H XL	7J	240	765	975	2149	340/50	420/A/A	BSW	✓	✓	✓
235/65R17	104H	7J	240	738	900	1984	300/44	420/A/A	BSW	✓	✓	✓
235/65R18	110H XL	7J	240	763	1060	2337	340/50	420/A/A	BSW	✓	✓	✓
235/65R19	109H XL	7	240	789	1030	2271	340/50	420/A/A	BSW	✓	✓	✓
235/70R16	106H	7J	240	736	950	2094	300/44	420/A/A	BSW	✓	✓	✓
245/55R19	107V XL	7 1/2J	253	753	975	2149	340/50	420/A/A	BSW	✓	✓	✓
245/60R18	105H	7J	248	751	925	2039	300/44	420/A/A	BSW	✓	✓	✓
245/65R17	111H XL	7J	248	750	1090	2403	340/50	420/A/A	BSW	✓	✓	✓
245/70R16	111H XL	7J	248	750	1090	2403	340/50	420/A/A	BSW	✓	✓	✓
245/70R17	114T XL	7J	248	776	1180	2601	340/50	420/A/A	BSW	✓	✓	✓
255/50R19	107V XL	8J	265	739	975	2149	340/50	420/A/A	BSW	✓	✓	✓
255/55R19	111V XL	8J	265	763	1090	2403	340/50	420/A/A	BSW	✓	✓	✓
255/60R17	110H XL	7 1/2J	260	738	1060	2337	340/50	420/A/A	BSW	✓	✓	✓
255/60R18	112H XL	7 1/2J	260	763	1120	2469	340/50	420/A/A	BSW	✓	✓	✓
255/65R16	109H	7 1/2J	260	738	1030	2271	300/44	420/A/A	BSW	✓	✓	✓
255/65R17	110H	7 1/2J	260	764	1060	2337	300/44	420/A/A	BSW	✓	✓	✓
255/70R16	111T	7 1/2J	260	764	1090	2403	300/44	420/A/A	BSW	✓	✓	✓
255/70R18	113T	7 1/2J	260	815	1150	2535	300/44	420/A/A	BSW	✓	✓	✓
265/60R18	110H	8J	272	775	1060	2337	300/44	420/A/A	BSW	✓	✓	✓
265/65R17	112H	8J	272	776	1120	2469	300/44	420/A/A	BSW	✓	✓	✓
265/70R16	112T	8J	272	778	1120	2469	300/44	420/A/A	BSW	✓	✓	✓
265/70R17	115T	8J	272	804	1215	2679	300/44	420/A/A	BSW	✓	✓	✓
265/70R18	116T	8J	272	829	1250	2756	300/44	420/A/A	BSW	✓	✓	✓
275/60R18	117H XL	8J	279	787	1285	2833	340/50	420/A/A	BSW	✓	✓	✓
275/65R17	115T	8J	279	790	1215	2679	300/44	420/A/A	BSW	✓	✓	✓
275/70R16	114T	8J	279	792	1180	2601	300/44	420/A/A	BSW	✓	✓	✓
285/50R20	116V XL	9J	297	794	1250	2756	340/50	420/A/A	BSW	✓	✓	✓
285/60R18	116H	8 1/2J	292	799	1250	2756	300/44	420/A/A	BSW	✓	✓	✓
285/65R17	116T	8 1/2J	292	802	1250	2756	300/44	420/A/A	BSW	✓	✓	✓

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice

TERRAMAX LSR1 A/T

45 / 46



All-terrain design

All-terrain four-season tire pattern, more strengthful tread block design.

Stone ejection design

Open tread pattern design effectively prevents stone retention, strengthen stone ejection performance.

Zigzag steel sheets

Small zigzag "3D steel sheet" design effectively deliver grips on wet road conditions, enhance driving traction.

Abrasion resistance formula

Special tread glue formula delivers a longer life.



UTQG: 460/A/A

Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Offroad

Size	LI/SI	PR	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
						(kg)	(Lbs)						
235/65R17	104T	-	7 J	240	738	900	1984	300/44	460/A/A	BSW	√	√	√
235/70R16	106T	-	7 J	240	736	950	2094	300/44	460/A/A	BSW	√	√	√
235/75R15	109S XL	-	6 1/2J	235	733	1030	2271	340/50	460/A/A	BSW	√	√	√
245/65R17	107S	-	7 J	248	750	975	2149	300/44	460/A/A	BSW	√	√	√
245/70R16	107T	-	7 J	248	750	975	2149	300/44	460/A/A	BSW	√	√	√
265/70R16	112T	-	8 J	272	778	1120	2469	300/44	460/A/A	BSW	√	√	√
265/70R17	115S	-	8 J	272	804	1215	2679	300/44	460/A/A	BSW	√	√	√
31X10.50R15LT	109S	6	8 1/2J	268	775	1030	2270	350/50	-	BSW	√	√	√
LT225/75R16	115/112Q	10	6 J	223	744	1215/1120	2470/2680	550/80	-	BSW	√	√	√
LT235/85R16	120/116Q	10	6 1/2J	235	806	1380/1260	3042/2778	550/80	-	BSW	√	√	√
LT245/75R16	120/116Q	10	7 J	248	774	1380/1260	3042/2778	550/80	-	BSW	√	√	√
LT265/70R17	121/118R	10	8 J	272	804	1450/1320	3195/2910	550/80	-	BSW	√	√	√

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice

TERRAMAX LSR2 A/T

47 / 48



UTQG: 400/A/A

Rolling Resistance

Wet Performance

Quietness

Comfort

Tread Life

Offroad

All-terrain design

All-terrain four-season tire pattern, more strengthful tread block design.

Stone ejection design

Open tread pattern design effectively prevents stone retention, strengthen stone ejection performance.

Zigzag steel sheets

Small zigzag "3D steel sheet" design effectively deliver grips on wet road conditions, enhance driving traction.

Abrasion resistance formula

Special tread glue formula delivers a longer life.

Size	LI/SI	PR	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
						(kg)	(Lbs)						
175/75R13	84T	-	5.00B	177	593	500	1102	300/44	400/A/A	BSW	-	-	-
175/75R14	86T	-	5J	177	618	530	1168	300/44	400/A/A	BSW	-	-	-
185/75R16C	104/102R	8	5J	184	684	900/850	1984/1874	475/69	-	BSW	√	√	√
205/60R15	91H	-	6J	209	627	615	1356	300/44	400/A/A	BSW	-	-	-
205/60R16	92H	-	6J	209	652	630	1389	300/44	400/A/A	BSW	-	-	-
205/65R15	94H	-	6J	209	647	670	1477	300/44	400/A/A	BSW	-	-	-
205/70R15	96H	-	6J	209	669	710	1565	300/44	400/A/A	BSW/WSW	-	-	-
205R16C	110/108S	8	6J	208	736	1060/1000	2337/2205	450/65	-	WSW	√	√	√
215/65R16	98T	-	6 1/2J	221	686	750	1653	300/44	400/A/A	BSW	√	√	√
215/65R17	99T	-	6 1/2J	221	712	775	1708	300/44	400/A/A	BSW	√	√	√
215R15C	112/110S	8	6J	218	725	1120/1060	2469/2337	450/65	-	BSW	√	√	√
225/60R17	99H	-	6 1/2J	228	702	775	1708	300/44	400/A/A	BSW	√	√	√
225/70R16	103T	-	6 1/2J	228	722	875	1929	300/44	400/A/A	BSW	√	√	√
245/75R15C	109/107S	6	7J	248	749	1030/975	2271/2149	375/54	-	BSW	√	√	√
245/75R16	111T	-	7J	248	774	1090	2403	300/44	400/A/A	WSW	√	√	√
255/60R18	112T	-	7 1/2J	260	763	1120	2469	340/50	400/A/A	BSW	√	√	√
255/70R15C	112/110S	6	7 1/2J	260	739	1120/1060	2469/2337	375/54	-	BSW	√	√	√
255/70R16	111T	-	7 1/2J	260	764	1090	2403	300/44	400/A/A	WSW	√	√	√
265/50R20	111S XL	-	8 1/2J	277	774	1090	2403	340/50	400/A/A	BSW/WSW	√	√	√
265/60R18	110T	-	8 J	272	775	1060	2336	300/44	400/A/A	BSW/WSW	√	√	√
265/65R17	112T	-	8 J	272	776	1120	2469	300/44	460/A/A	BSW/WSW	√	√	√
265/70R16	112T	-	8 J	272	778	1120	2469	300/44	460/A/A	BSW	√	√	√
265/70R17	115S	-	8 J	272	804	1215	2679	300/44	460/A/A	BSW	√	√	√
275/55R20	117S XL	-	8 1/2J	284	810	1285	2833	340/50	400/A/A	BSW	√	√	√
275/65R17	115T	-	8J	279	790	1215	2679	300/44	400/A/A	WSW	√	√	√
275/65R18	116T	-	8 J	279	815	1250	2755	300/44	400/A/A	BSW	√	√	√
NEW 285/50R20	116T XL	-	9	297	794	1250	2756	340/50	400/A/A	BSW	√	√	√
NEW 285/55R20	119S XL	-	9 J	297	822	1360	2998	340/50	400/A/A	BSW	√	√	√
285/60R18	120S XL	-	8 1/2J	292	799	1400	3086	340/50	460/A/A	BSW	√	√	√
285/65R17	116T	-	8 1/2J	292	802	1250	2755	300/44	400/A/A	WSW	√	√	√
NEW 305/50R20	120S XL	-	9 1/2J	316	814	1400	3086	340/50	400/A/A	BSW	√	√	√
NEW 305/60R18	120S	-	9 J	311	823	1400	3086	300/44	460/A/A	BSW	√	√	√
31X10.50R15LT	109S	6	8 1/2J	268	775	1030	2270	350/50	-	WSW	√	√	√
LT215/75R15	100/97Q	6	6J	216	703	800/730	1765/1610	350/50	-	WSW	√	√	√
LT215/85R16	115/112Q	10	6J	216	772	1215/1120	2679/2469	575/84	-	WSW	√	√	√
LT235/75R15	104/101S	6	6 1/2J	235	733	900/825	1985/1820	350/50	-	WSW	√	√	√
LT245/65R17	111/108R	8	7J	248	750	1090/1000	2403/2205	450/65	-	WSW	√	√	√
LT245/70R16	113/110S	8	7J	248	750	1150/1060	2535/2335	450/65	-	WSW	√	√	√
LT245/70R17	119/116S	10	7J	248	776	1360/1250	3000/2755	550/80	-	WSW	√	√	√
LT245/75R17	121/118S	10	7J	248	800	1450/1320	3195/2910	550/80	-	WSW	√	√	√
LT265/70R16	121/118S	10	8J	272	778	1450/1320	3195/2910	550/80	-	WSW	√	√	√
LT265/75R16	123/120Q	10	7 1/2J	267	804	1550/1400	3415/3085	550/80	-	BSW	-	-	-
LT285/60R18	122/119Q	10	8 1/2J	292	799	1500/1360	3305/3000	550/80	-	BSW	-	-	-
LT285/65R18	125/122R	10	8 1/2J	292	827	1650/1500	3640/3305	550/80	-	WSW	-	-	-
LT285/70R17	121/118Q	10	8 1/2J	292	832	1450/1320	3195/2910	550/80	-	BSW/WSW	√	√	√
LT285/75R16	126/123Q	10	8 J	286	834	1700/1550	3750/3415	550/80	-	BSW	-	-	-
LT325/60R18	124/121Q	10	9 1/2J	331	847	1600/1450	3525/3195	450/65	-	BSW	-	-	-
LT325/65R18	127/124Q	10	9 1/2J	331	879	1750/1600	3860/3525	450/65	-	BSW	-	-	-

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice



Open pattern shoulder design

Improve the longitudinal grip of the tires, and ensure the traction performance of muddy, gravel and snow roads.

Staggered pattern shoulder design

The staggered shoulder shape is combined with stronger skeleton material to prevent the side rock from damaging the tire and improve the grip of the tire.

Different Under-shoulder pattern design

Protect the tire shoulder and upper sidewall from damage, improve the grip of the tire on muddy roads, and improve the grip under low adhesion conditions with low air pressure, different of two shoulder design to meet the needs of different users on the tire appearance.

Large shoulder matching small flower pattern block design in the middle

Ensure the off-road performance of tires, improve the comfort of pavement, and realize the perfect combination of off-road and road driving performance.

Composite pitch fit pitch random arrangement design

Improve tire grip and comfort, and reduce tire regular noise.

Size	LI/SI	PR	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	UTQG	Sidewall			
						(kg)	(Lbs)						
235/70R16	109Q XL	-	7 J	240	736	1030	2271	340/50	560/A/B	WSW	✓	✓	✓
235/75R15	109Q XL	-	6 1/2J	235	733	1030	2271	340/50	560/A/B	WSW	✓	✓	✓
245/75R16	111Q	-	7 J	248	774	1090	2403	300/44	560/A/B	WSW	✓	✓	✓
255/70R16	111Q	-	7 1/2J	260	764	1090	2403	300/44	560/A/B	WSW	✓	✓	✓
265/50R20	111Q XL	-	8 1/2J	277	774	1090	2403	340/50	560/A/B	WSW	✓	✓	✓
265/60R18	114Q XL	-	8J	272	775	1180	2601	340/50	560/A/B	WSW	✓	✓	✓
265/65R17	116Q XL	-	8J	272	776	1250	2756	340/50	560/A/B	WSW	✓	✓	✓
265/65R18	116Q XL	-	8J	272	801	1250	2756	340/50	560/A/B	WSW	✓	✓	✓
265/70R16	116Q XL	-	8J	272	778	1250	2756	340/50	560/A/B	WSW	✓	✓	✓
265/70R17	115Q	-	8 J	272	804	1215	2679	300/44	560/A/B	WSW	✓	✓	✓
275/60R20	116Q XL	-	8J	279	838	1250	2756	340/50	560/A/B	WSW	✓	✓	✓
275/65R18	116Q XL	-	8J	279	815	1250	2756	340/50	560/A/B	WSW	✓	✓	✓
27X8.50R14LT	95Q	6	7J	218	674	690	1520	350/50	-	WSW		POR	
285/45R22	114Q XL	-	9 1/2J	285	815	1180	2601	340/50	560/A/B	WSW	✓	✓	✓
31X10.50R15LT	109Q	6	8 1/2J	268	775	1030	2270	350/50	-	WSW		POR	
33X12.50R15LT	108Q	6	10J	318	826	1000	2205	250/35	-	WSW		POR	
33X12.50R18LT	118Q	10	10J	318	826	1320	2910	450/65	-	WSW		POR	
33X12.50R20LT	114Q	10	10J	318	826	1180	2600	450/65	-	WSW		POR	
33X12.50R22LT	109Q	10	10J	318	826	1030	2270	450/65	-	WSW		POR	
35X12.50R17LT	121Q	10	10J	318	877	1450	3195	450/65	-	WSW		POR	
35X12.50R18LT	118Q	8	10J	318	877	1320	2910	350/50	-	WSW		POR	
35X12.50R20LT	121Q	10	10J	318	877	1450	3195	450/65	-	WSW		POR	
35X12.50R22LT	117Q	10	10J	318	877	1285	2835	450/65	-	WSW		POR	
LT245/75R16	120/116Q	10	7 J	248	774	1380/1260	3042/2778	550/80	-	WSW		POR	
LT265/70R17	118/115Q	8	8 J	272	804	1320/1215	2910/2680	450/65	-	WSW		POR	
LT265/75R16	119/116Q	8	7 1/2J	267	804	1360/1250	3000/2755	450/65	-	WSW		POR	
LT285/55R20	117/114Q	8	9J	297	822	1285/1180	2835/2600	450/65	-	WSW		POR	
LT285/65R18	121/118Q	8	8 1/2J	292	827	1450/1320	3195/2910	450/65	-	WSW		POR	
LT285/70R17	116/113Q	6	8 1/2J	292	832	1250/1150	2755/2535	350/50	-	WSW		POR	
LT285/75R16	116/113Q	6	8 J	286	834	1250/1150	2755/2535	350/50	-	WSW		POR	

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice

Wet Performance

Tread Life

Offroad



Pyramid-shaped pattern

Pyramid-shaped pattern design improves grip and traction on muddy and sandstone roads.

Self-cleaning grooves

Slush self-cleaning and rejection groove design guarantee a safe and smooth drive.

Rigidity shoulder

The shoulder extends to sidewall tread block design greatly protect the tire from external puncture or injury.

Anti-skip design

IA mass of steel sheets and grooves design provide great grip ability and driving performance on wetland.

Size	LI/SI	PR	Rim	SW (mm)	OD (mm)	Load Index		Max Pressure Kpa/Psi	Sidewall	
						(kg)	(Lbs)			
31X10.50R15LT	109Q	6	8 1/2J	268	775	1030	2270	350/50	BSW	POR
32X11.50R15LT	113Q	6	9 J	290	801	1150	2535	350/50	BSW	POR
33X12.50R15LT	108Q	6	10J	318	826	1000	2205	250/35	BSW	POR
33X12.50R17LT	120Q	10	10 J	318	826	1400	3085	450/65	BSW	POR
LT215/75R15	100/97Q	6	6 J	216	703	800/730	1765/1610	350/50	BSW	POR
LT215/85R16	115/112Q	10	6 J	216	772	1215/1120	2680/2470	550/80	BSW	POR
LT225/75R16	115/112N	10	6 J	223	744	1215/1120	2680/2470	550/80	BSW	POR
LT235/75R15	104/101Q	6	6 1/2J	235	733	900/825	1985/1820	350/50	BSW	POR
LT235/85R16	120/116Q	10	6 1/2J	235	806	1380/1260	3042/2778	550/80	BSW	POR
LT245/75R16	120/116N	10	7 J	248	774	1380/1260	3042/2778	550/80	BSW	POR
LT305/70R16	124/121P	10	9 J	311	834	1600/1450	3525/3195	450/65	BSW	POR
LT315/75R16	127/124Q	10	8 1/2J	313	878	1750/1600	3860/3525	450/65	BSW	POR

* New Developing Sizes/ The Labeling Information are Subject to Change Without Notice

Wet Performance

Tread Life

Offroad