



www.tiredirect.com.mx

TYRE PRODUCT CATALOGUE



TIRE DIRECT



/TIRE_DIRECT



/TIREDIRECTMX



TIRE DIRECT

RAINMASTER

AGRICULTURAL TYRE

BIAS LIGHT TRUCK TYRE



R1



SIZE	PR	PATTERN	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG
5.00-12	6	R1	4.00E	15	490	145	250	405
5.50-17	6	R1	4.50E	13	720	150	250	520
6.00-12	6	R1	4.50E	22	640	165	250	405
6.00-14	8	R1	4.50E	18	690	165	250	685
6.00-16	8	R1	4.50E	18	745	165	250	975
6.50-16	6	R1	5.00F	25	785	180	250	565
7.00-16	8	R1	5.00F	25	785	180	250	665
7.50-16	8	R1	5.00F	25	910	205	250	760
7.50-20	6	R1	5.50F	26	910	205	210	760
8-16	6	R1	6.0-16	26	790	210	210	615
8-18	6	R1	6.0-16	26	900	205	300	750
8.3-16	4	R1	W7	26	845	205	210	665
8.3-20	6	R1	W7	26	895	210	240	695
8.3-24	6	R1	W7	26	995	210	240	810
9.5-16	6	R1	W8	23	880	240	210	800
9.5-20	6	R1	W8	33	950	240	210	810
9.5-24	8	R1	W8	30	1050	240	280	1110
9.5-28	8	R1	W8	33	1150	240	280	1115
10.00-15	8	R1	8LB	19	855	276	240	1425
10.75-15.3	10	R1	9	22	780	264	390	1090
11.2-20	8	R1	W10	33	1005	285	240	1085
11.2-24	8	R1	W10	33	1105	285	240	1225
11.2-28	8	R1	W10	34	1205	285	240	1305
11.2-38	8	R1	W10	46.5	1540	305	180	1630
12.4-24	8	R1	W11	36	1160	315	230	1415
12.4-28	8	R1	W11	36	1260	315	230	1510
12.4-32	6	R1	W11	36	1360	315	170	1355
12-38	10	R1	DW11	35	1575	330	220	1800
13.6/12-38	10	R1	W12	35	1565	345	250	2215
13.6-24	8	R1	W12	37	1210	345	210	1545
13.6-28	10	R1	W12	33	1310	345	250	1910
14.9-24	10	R1	W13	39	1265	378	230	1990
14.9-28	8	R1	W13	38	1315	378	180	1820
14.9-28	10	R1	W13	38	1365	378	230	1880
14.9-30	10	R1	W13	38	1415	378	230	2190
15.5/80-24	10	R1	W13	35	1240	394	400	3300
15.5-38	10	R1	W14L	36	1570	395	230	2320
15-24	10	R1	DW14	35	1330	410	280	2800
16.9-28	10	R1	W15L	39	1435	430	200	2380
16.9-30	10	R1	W15L	40	1485	430	200	2455
16.9-34	10	R1	W15L	39	1585	430	200	2605
16.9-38	10	R1	W15L	39	1685	430	200	2760
18.4-26	12	R1	DW16	38	1450	467	230	2985
18.4-30	10	R1	W16L	41	1550	467	180	2815
18.4-34	10	R1	W16L	38	1655	467	180	2990
18.4-38	10	R1	W16L	41	1755	467	180	3165
18.4-42	10	R1	W16A	51	1857	467	180	3330
20.8-38	10	R1	W18L	42	1835	528	160	3475
23.1-26	12	R1	DW20	42	1605	587	170	3610
23.1-30	10	R1	DW20	42	1705	625	160	3750
24.5-32	12	R1	DW21A	42	1805	625	140	4360
405/70-24	14	R1	13	37	1075	410	400	3550



PR-1



R2-A



R2-B

SIZE	PR	PATTERN	STANDARD RIM	TREAD DEPTH MM PR-1	TREAD DEPTH MM R2	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG
6.00-12	6	PR-1, R2	4.50E	50	40	688	160	250	405
7.50-16	8	PR-1, R2	5.50F	73	62	910	205	300	750
8.3-20	8	PR-1, R2	W7	78	65	950	210	270	970
8.3-24	10	PR-1, R2	W7	78	65	1050	210	270	1135
9.5-20	10	PR-1, R2	W8	80	70	1050	240	310	1420
9.5-24	10	PR-1, R2	W8	78	63	1150	240	240	1315
11.2-24	10	PR-1, R2	W10	85	75	1205	285	210	1465
11-32	12	PR-1, R2	W10	94	85	1460	305	160	1080
12.4-24	8	PR-1, R2	W11	85	75	1215	315	260	1980
13.6-38	10	PR-1, R2	W12	90	78	1710	345	250	2780
14.9-24	10	PR-1, R2	W13	78	65	1320	378	230	1800
14.9-26	10	PR-1, R2	W13	90	75	1330	378	230	1880
14.9-28	10	PR-1, R2	W13	90	75	1385	378	230	1920
14.9-30	10	PR-1, R2	W13	100	85	1560	378	230	2190
16.9-30	10	PR-1, R2	W15L	90	75	1585	430	200	2455
16.9-34	10	PR-1, R2	1235	90	75	315	W15L	260	1800
18.4-30	12	PR-1, R2	W16L	90	75	1550	467	230	3000
18.4-34	10	PR-1, R2	W16L	90	75	1650	467	230	3100
18.4-38	10	PR-1, R2	W16L	90	75	1750	467	180	3200
19.5L-24	8	PR-1, R2	W15L, W16L, W16A	88	79	1382	495	140	1900
20.8-38	10	PR-1, R2	W18L	95	80	1835	528	160	3400
23.1-26	10	PR-1, R2	DW20A	89	75	1662	587	140	2900
28L-26	10	R2	DW25	/	93	1615	715	150	4845



IRRIGATION-A



IRRIGATION-B

SIZE	PR	PATTERN	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG
11.2-24	6	IRRIGATION TIRE	W10	25	1105	285	1045/1225	180/240
11.2-38	8	IRRIGATION TIRE	W10	25	1448	285	950/1150	120/180
13.6-24	8	IRRIGATION TIRE	W12	25	1210	345	340/1545	180/250
14.9-24	8	IRRIGATION TIRE	W13	26	1285	378	1510/1760	140/180



F-2



F-2M



F3

SIZE	PR	PATTERN	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG
4.00-12	4	F-2	4.00E	11	540	112	340	250
5.00-15	4	F-2	4J	13	664	130	300	365
5.50-16	8	F-2	4	13	713	150	390	530
6.00-16	8	F-2	4	10	739	159	360	560
6.50-16	8	F-2	4.5	14	761	173	330	615
6.50-20	8	F-2	5.00F	16	860	180	585	880
7.50-16	10	F-2	5.5	19	808	203	390	875
7.50-18	8	F-2	5.50F	20.5	860	205	370	930
7.50-20	8	F-2	5.50F	21	910	205	370	1020
10.00-16	10	F-2	W8L	23	894	274	390	1360
11.00-16	10	F-2	W10L	23	967	315	345	1350
11L-15	8	F-2	8	21	815	274	300	950
10.00-16	10/12	F-2M	W8L	16	894	274	300	1060
11.00-16	10/12	F-2M	W10L	16	967	315	410	1550
11L-15	10	F3	8LB	11	813	279	360	1060
11L-16	12	F3	8LB	11	838	279	440	1250
14.5/75-16.1	10	F3	11LB	15	940	373	280	1450



I-1

SIZE	PR	PATTERN	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG
5.90-15	4	I-1	4.5	5.5	657.9	157.5	250	515
6.70-15	6	I-1	4.5	5	703.6	167.6	300	730
7.60L-15	8	I-1	5.5	6.5	721.4	200.7	360	950
7.50-16	8	I-1	5.5	6.5	765	205	227	960
9.5L-14	8	I-1	8	6	741	241	300	1090
9.5L-15	8	I-1	8LB	6	767	241	300	1120
11L-14	8	I-1	8KB	6	752	279	250	1100
11L-15	12	I-1	W8L	6	777	279	360	1450
12.5L-15	12	I-1	10	6	823	318	360	1750
11L-14	6	I-1	8	6.5	747	274	190	925
11L-16	8	I-1	8	6.4	798	274	250	1215
12.5L-16	12	I-1	10	10	841	312	360	1800
16.5-16.1	12	I-1	14	8	1024	419	280	2575

INDUSTRIAL TYRE



SKS-1

SKS-2

SKS-3

SKS-4

SIZE	PR	PATTERN	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOAD/EAU	MAX SPEED Km/h
10-16.5TL	10	SKS-1	8.25	23	773	264	620	2375	8
10-16.5TL	10	SKS-2 SKS-3 SKS-4	8.25	27	773	264	600	2375	10
12-16.5TL	12	SKS-1	9.75	24	831	307	550	2865	8
12-16.5TL	12	SKS-2 SKS-3 SKS-4	9.75	33	831	307	560	3075	10
14-17.5TL	14	SKS-1	10.5	24	921	349	550	3875	8
15-19.5TL	14	SKS-1	11.75	24	1019	389	480	4565	8
11L-16	12	SKS-1	8	24	838	279	440	1250	10
33*15.5-16.5	12	SKS-1	12	12	838	394	379	4423	5



L5-1

L5-2

SIZE	PR	PATTERN	OVERALL DIAMETER MM	SECTION WIDTH MM	STANDARD RIM	RELEVANT PRESSURE KPA	LOAD PRESSURE		MAX SPEED KM/H
							DRIVE	DRIVE	
10-16.5	10	L5-1 L5-2	790	268	8.25	520	2135	2135	10
12-16.5	12	SKS-5A SKS-5B	836	315	9.75	550	2865	2865	10



R4-A R4-B L5-1 L5-2 R4-E

SIZE	PR	PATTERN	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG
16.9-24 TL	12	R4-A	W15L	27	1309	429	260	3250
16.9-28 TL	12	R4-A	W15L	26	1410	429	200	2380
21L-24 TL	14	R4-A R4-E	DW18	32	1378	533	250	4200
18.4-26 TL	12	R4-A	DW16	26	1450	467	230	2985
17.5L-24 TL	10	R4-A	W15L	26	1241	445	220	2800
19.5L-24 TL	12	L5-1 L5-2	DW17	28	1314	495	230	3450
10.5/80-18 TL	12	R4-B	9	22	907	274	430	2075
12.5/80-18 TL	12	R4-B	9	25.5	987	308	370	2625



FORKLIFT TYRE

SIZE	PR	TREAD DEPTH MM	STANDARD RIM	OVERALL DIAMETER MM	SECTION WIDTH MM	PRESSURE KPA	MAX. LOAD				Type
							HEAVY DUTY FORKLIFT 25km/h		OTHER INDUSTRIAL VEHICLES		
							DRIVING	STEERING	10km/h	25km/h	
4.00-8	8	9	3.00D	415	112	930	745	630	630	465	TT
5.00-8	10		3.00D	470	137	1000	1150	970	/	/	
6.00-9	10	12	4.00E	540	160	860	1505	1275	1275	940	TT
6.50-10	10	12	5.00F	590	175	790	1655	1400	1400	1030	
7.00-12	12	16	5.00S	676	190	860	2375	2005	2005	1480	TT
7.00-12	14	16	5.00S	676	190	1000	2590	2190	2190	1610	TT
8.25-15	14	16	6.5	840	235	830	3775	3185	3185	2350	TT
18x7-8	14	13	4.33R	465	173	970	1505	1270	/	/	TT
28x9-15	14	18	7.0	710	220	970	3050	2575	2575	1900	TT



Tire Direct
La nueva generación

OFF THE ROAD TYRE



G2



L2

SIZE	PR	STANDARD RIM	TREAD DEPTH	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG	TYPE
13.00-24	16	8/9.00DC	25.5	1300	350	400	2725/3200	TT/TL
14.00-24	16	8/9.00DC	25.5	1370	375	350	3075/3650	TT/TL
15.5-25	16	12.00/1.3	25.5	1275	395	250	3250	TT/TL
17.5-25	16	14.00/1.5	26	1350	445	275	3350	TT/TL
20.5-25	16	17.00/2.0	28.5/29.5	1490	520	275/325	5450/6000	TT/TL
23.5-25	20	19.00/2.5	31.5	1615	595	200	4750	TT/TL



E3/L3

SIZE	PR	STANDARD RIM	TREAD DEPTH	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG	TYPE
16/70-20	16	13	23	1075	410	450/350	5150/2900	TT/TL
16/70-24	16	13	23	1175	410	450/350	5600/3350	TT/TL
15.5-25	16	12.00/1.3	23.5	1275	395	475/325	6150/3750	TT/TL
17.5-25	16	14.00/1.5	26	1350	445	475/300	7300/4250	TT/TL
20.5-25	20	17.00/2.0	29	1490	520	450/325	9500/6000	TT/TL
23.5-25	24	19.50/2.5	30	1615	595	375/300	10900/7300	TT/TL
26.5-25	28	22.00/3.0	35	1750	675	475/350	15500/10000	TT/TL
29.5-26	28	26.00/3.5	38	1875	750	425/325	17600/11500	TT/TL
29.5-29	32	25.00/3.5	38	1975	750	425/325	19000/12150	TT/TL
1300-24	20	9.00DC	25	1300	350	375	4500/9500	TT/TL
1300-25	20	10.00/1.5	25	1310	360	475	5000/10000	TT/TL
1400-24	20	10	25.5	1370	375	475	4625/8500	TT/TL
1400-25	20	10	25.5	1380	366	575	5150/9500	TT/TL
1600-24	24	11.25	28.5	1490	430	650	6000/10600	TT/TL
1600-25	28	11.25/2.0	28	1490	430	575	6700/11500	TT/TL
1800-25	36	13.00/2.5	32	1615	495	625	9250/16000	TT/TL

**E3/L3 B****E3B**

SIZE	PR	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG	TYPE
17.5-25	16	14.00/1.5	26	1350	445	475/300	7300	TT/TL
20.5-25	20	17.00/2.0	29	1490	520	450/325	9500	TT/TL
23.5-25	20	19.50/2.5	30	1615	595	375/300	10900	TT/TL
26.5-25	28	22.00/3.0	35	1750	675	475/350	15500	TT/TL
29.5-25	28	25.00/3.5	38	1875	750	425/325	17500	TT/TL

SIZE	PR	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG	TYPE
1300-24	16	9.00DC	23.5	1300	350	400	3200	TT/TL
1300-26	28	8.5/1.3	22	1300	335	740/740	5570/5010	TT/TL
1400-24	20	10	25	1370	375	700/475	8500/4625	TT/TL
1400-25	20	10	25.5	1318	366	850/575	9500/5150	TT/TL
1600-25	28	11.25/2.0	28/57.5	1490	430	750/575	11500/6700	TT/TL
1800-25	36	13.00/2.5	28	1615	495	850/575	16000	TT/TL

**L5**

SIZE	PR	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG	TYPE
20.5-25	28	17.00/2.0	71	1548	521	625	11500	TT/TL
23.5-25	28	19.50/2.5	78.5	1673	597	550	13600	TT/TL
26.5-25	32	22.00/3.0	87.5	1798	673	550	17000	TT/TL
29.5-25	34	25.00/3.5	95	1921	749	525	20000	TT/TL

**L-5S**

SIZE	PR	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG	TYPE
9.00-20	12	7	15	1015	255	625	4000	TT/TL
10.00-20	20	7.5	/	1025	288	670	3260	TT
11.00-20	16	8	16	1080	290	725	5450	TT/TL
12.00-20	24	8.5	50	1173	315	900	6300	TT/TL
12.00-24	24	8.5	55	1275	315	975	7500	TT/TL
14.00-24	24	10	65	1420	375	850	9500	TT/TL

**R3****E3C**

SIZE	PR	PATTERN	STANDARD RIM	TREAD DEPTH MM	OVERALL DIAMETER MM	SECTION WIDTH MM	RELEVANT PRESSURE KPA	MAX LOADING KG	TYPE
18.4-26	12	R3 Roller	DW16A	24	1,426	467	220	2,650	TT/TL
23.1-26	12	R3 Roller	DW20	16	1,500	595	170	3,655	TT/TL

SIZE	PR	PATTERN	OVERALL DIAMETER MM	SECTION WIDTH MM	TREAD DEPTH MM	MAX LOADING KG	RELEVANT PRESSURE KPA	TYPE
8.25-20	14	E3C	992	245	6.5	2060	675	TT
9.00-20	14	E3C	1020	260	7	2500	700	TT
10.00-20	16	E3C	1062	280	7	3000	810	TT

RAINMASTER

SOLID TYRE

13

SOLID TYRE



SM-1

SIZE	RIM	TYRE DIMENSIONS		TYRE LOAD LIMITS(kg) AT VARIOUS MAXIMUM SPEEDS AND ON VARIOUS TYPES OF EQUIPMENT									
				COUNTERBALANCED LIFT TRUCKS						OTHER INDUSTRIAL VEHICLES			
		OD (mm)	S.W (mm)	10KM/h		15KM/h		25KM/h		Static		25km/h	
				DRIVING	STEERING	DRIVING	STEERING	DRIVING	STEERING				
4.00-8	3.00D-8	410	108	1090	840	995	785	925	710	1135	710		
5.00-8	3.00D-8	454	123	1255	985	1145	890	1060	815	1305	815		
6.00-9	4.00E-9	532	143	1975	1520	1805	1390	1675	1290	2065	1290		
6.50-10	5.00F-10	580	164	2715	2090	2485	1910	2310	1775	2840	1775		
7.00-12	5.00S-12	655	170	3105	2390	2835	2180	2635	2025	3240	2025		
8.25-15	6.5-15	814	208	5085	3910	4640	3570	4310	3315	5304	3315		
15x4.5-8	3.00D-8	380	111	1005	775	915	705	850	655	1050	655		
15x4.5-8	3.25I-8	380	111	1090	840	995	785	925	710	1135	710		
16x6-8	4.33R-8	420	153	1545	1190	1410	1085	1305	1005	1610	1005		
18x7-8	4.33R-8	456	156	2430	1870	2215	1705	2060	1585	2535	1585		
21x8-9	6.00E-9	530	185	2890	2225	2645	2035	2455	1890	3025	1890		
23x9-10	6.50F-10	590	200	3730	2870	3405	2620	3160	2430	3690	2430		
23x10-12	8.00G-12	595	240	4450	3425	4060	3125	3770	2900	4640	2900		
27x10-12	8.00G-12	675	237	4595	3535	4200	3230	3900	3000	4800	3000		
28x9-15	7.0-15	700	222	4060	3125	3710	2855	3445	2650	4240	2650		
140/55-9	4.00E-9	384	135	1380	1060	1260	970	1170	900	1440	900		
200/50-10	6.50F-10	458	198	2910	2240	2665	2050	2470	1900	3040	1900		
250-15	7.0-15	725	230	5220	4015	4770	3670	4425	3405	5450	3405		
250-15	7.5-15	725	230	5595	4305	5110	3930	4745	3650	5840	3650		
300-15	8.0-15	825	258	6895	5305	6300	4845	5850	4500	7200	4500		

14

SOLID TYRE

Tire Direct
La nueva generación



SM



TR

Size	
Inch	mm
6"2"4	150*80*100
6"3"4	150*80*100
7"3"5	178*76*127
8"3"5	204*76*119
8 1/2"3"6	215*75*148
9"3"5	229*76*127
9"4"5	229*102*127
9"5"5	229*127*127
10"3"6 1/2	254*76*165
10"4"6 1/2	254*102*165
10"5"6 1/2	254*127*165
10"6"6 1/2	254*152*165
10"7"6 1/2	254*178*165
10 1/2"4"6 1/2	267*102*165
10 1/2"5"6 1/2	267*127*165
10 1/2"6"6 1/2	267*152*165
11"5 1/4"8 3/4	280*135*170
11 3/4"4"8 3/4	300*90
11 3/4"4"6	300*100
11 3/4"5"6	300*125
12"5"7 3/4	305*125*184
12"5 1/2"8	305*140*203
12"6 1/2"8	305*165*203
12 1/2"5 3/4"6 1/2	315*145*170
13"5 3/4"7 1/2	330*145*193
13 1/2"4 1/2"8	343*114*203
13 1/2"5 1/2"8	343*140*203
13 1/2"6 1/2"8	343*165*203
13 1/2"7 1/2"8	343*191*203
13 1/2"8 1/2"8	343*216*203
14"4 1/2"8	356*114*203
14"5"10	356*127*254
15"4 1/2"11 1/4	381*114*286
15"5"11 1/4	381*127*286
15"6"11 1/4	381*153*286
15"7"11 1/4	381*178*286
15"8"11 1/4	381*203*286

Size	
Inch	mm
15"9"11 1/4	381*229*286
15 1/2"5"10	394*127*254
15 1/2"6"10	394*153*254
15 1/2"7"10	394*178*254
15 1/2"8"10	394*203*254
15 1/2"9"10	394*229*254
16"4 1/2"10 1/2	406*114*267
16"5"10 1/2	406*127*267
16"5 1/2"10 1/2	406*140*267
16"6"10 1/2	406*152*267
16"6 1/2"10 1/2	406*165*267
16"7"10 1/2	406*178*267
16"7 1/2"10 1/2	406*191*267
16"8"10 1/2	406*203*267
16"9"10 1/2	406*229*267
16"7"11 1/4	406*178*286
16 1/4"5"11 1/4	413*127*286
16 1/4"6"11 1/4	413*152*286
16 1/4"7"11 1/4	413*178*286
16 1/4"8"11 1/4	413*203*286
16 1/4"9"11 1/4	413*229*286
18"5"12 1/8	457*127*308
18"6"12 1/8	457*152*308
18"7"12 1/8	457*178*308
18"8"12 1/8	457*203*308
18"9"12 1/8	457*229*308
18"10"12 1/8	457*254*308
18"7"14	457*178*356
18"8"14	457*203*356
18"9"14	457*229*356
19"10"14	485*255*350
20"5"16	508*127*406
20"6"16	508*153*406
20"7"16	508*178*406
20"8"16	506*203*406
20"9"16	506*229*406
20"10"16	506*254*406
21"5"15	533*127*381

Size	
Inch	mm
21"6"15	533*152*381
21"7"15	533*178*381
21"8"15	533*203*381
21"9"15	533*229*381
21"10"15	533*254*381
21"11"15	533*280*381
21"9"16	533*229*406
22"6"17 3/4	559*152*451
22"5"16	559*127*406
22"6"16	559*152*406
22"7"16	559*178*406
22"8"16	559*203*406
24 1/2"9"19	620*230*475
24 1/2"10"19	620*255*475
26"6"20	660*152*508
26"7"20	660*178*508
26"8"20	660*203*508
26"9"20	660*229*508
26"10"20	660*254*508
26"11"20	660*280*508
26"12"20	660*305*508
28"7"22	711*178*559
28"8"22	711*203*559
28"9"22	711*229*559
28"10"22	711*254*559
28"11"22	711*280*559
28"12"22	711*305*559
28"14"22	711*356*559
28"16"22	711*406*559
36"10"30	915*254*762
36"12"30	915*305*762
36"14"30	915*356*708
36"16"30	915*406*762
40"10"30	1016*254*762
40"12"30	1016*305*762
40"14"30	1016*356*762
40"16"30	1016*508*762

