

Tire Direct
La nueva generación

ROADCLAW

TIRES



2022

PRODUCT CATALOGUE

COMPANY BRIEF

Roadclaw Tyre (Hongkong) Limited was founded in 2012. Roadclaw is specializing in semi-steel radial tire development and global sales, its product portfolio covered segments like PCR, UHP, H/T,LT, A/T,R/T & M/T with more than 400 summer tire sizes, rim size range from 13inch to 30inch. Thanks to its professional and innovative technical team, Roadclaw is supplying the best in class tires with competitive prices for business partners, its footprints have covered over 80 countries. Roadclaw's growing reputation is based upon a commitment to excellence in providing tire solutions and services for partners all over the world.



CATALOGUE

PCR HP UHP TIRE



EX30



EX30^{RFT}



EX80

SUV UHP TIRE



RC70



RC97

SUV & 4X4 TIRE



PRIXADO H/T



PRIXADO H/T+



PRIXADO A/T



PRIXADO R/T



MT ONE

VAN TIRE



EX50



EX30



Outstanding grip in
dry & wet conditions



Asymmetric Ultra-High
Performance tread
pattern design



Advanced silica
compound



Computer optimized
pitch design to
reduce driving noise



4 longitudinal grooves
ensure effective water
drainage



EX 30



RIM inch	SIZE	L.I./S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi	
14	165/55R14	72H	5.0J	4.5J—6.0J	10	783	44	
	185/55R15	82V	6.0J	5.0J—6.5J	10	1047	44	
15	195/55R15	85V	6.0J	5.5J—7.0J	10	1135	44	
	165/50R15	76V XL	5.0J	4.5J—6.0J	10	882	49	
16	195/50R15	82V	6.0J	5.5J—7.0J	10	1047	44	
	195/50R16	88V XL	6.0J	5.5J—7.0J	10	1235	49	
	195/55R16	87V	6.0J	5.5J—7.0J	10	1202	44	
	205/55R16	91V	6.5J	5.5J—7.5J	10	1356	44	
	215/55ZR16	97W XL	7.0J	6.0J—7.5J	10	1609	49	
	205/50ZR16	87W	6.5J	5.5J—7.5J	10	1202	44	
	195/45R16	84V XL	6.5J	6.0J—7.5J	10	1102	49	
	205/45ZR16	87W XL	7.0J	6.5J—7.5J	10	1202	49	
	205/55ZR17	95W XL	6.5J	5.5J—7.5J	10	1521	49	
	17	215/55ZR17	98W XL	7.0J	6.0J—7.5J	10	1653	49
225/55ZR17		101W XL	7.0J	6.0J—8.0J	10	1819	49	
235/55ZR17		103W XL	7.5J	6.5J—8.5J	10	1929	49	
205/50ZR17		93W XL	6.5J	5.5J—7.0J	10	1433	49	
215/50ZR17		95W XL	7.0J	6.0J—7.5J	10	1521	49	
225/50ZR17		98W XL	7.0J	6.0J—8.0J	10	1653	49	
195/45ZR17		85W XL	6.5J	6.0J—7.5J	10	1135	49	
205/45ZR17		88W XL	7.0J	6.5J—7.5J	10	1235	49	
215/45ZR17		91W XL	7.0J	7.0J—8.0J	10	1356	49	
225/45ZR17		94W XL	7.5J	7.0J—8.5J	10	1477	49	
235/45ZR17		97W XL	8.0J	7.5J—9.0J	10	1609	49	
205/40ZR17		84W XL	7.5J	7.0J—8.0J	10	1102	49	
215/40ZR17		87W XL	7.5J	7.0J—8.5J	10	1202	49	
245/40ZR17		91W	8.5J	8.0J—9.5J	10	1356	44	
18		215/55R18	95V	7.0J	6.0J—7.5J	10	1521	44
	225/55R18	98V	7.0J	6.0J—8.0J	10	1653	44	
	235/55R18	104V XL	7.5J	6.5J—8.5J	11	1984	49	
	225/50ZR18	95W	7.0J	6.0J—8.0J	10	1521	44	
	235/50ZR18	101W XL	7.5J	6.5J—8.5J	10	1819	49	
	245/50ZR18	104W XL	7.5J	7.0J—8.5J	10	1984	49	
	215/45ZR18	93W XL	7.0J	7.0J—8.0J	10	1433	49	
	225/45ZR18	95W XL	7.5J	7.0J—8.5J	10	1521	49	
	235/45ZR18	98W XL	8.0J	7.5J—9.0J	10	1653	49	
	245/45ZR18	100W XL	8.0J	7.5J—9.0J	10	1764	49	
	255/45ZR18	103W XL	8.5J	8.0J—9.5J	10	1929	49	
	275/45ZR18	107W XL	9.0J	8.5J—10.5J	10	2149	49	
	215/40ZR18	89W XL	7.5J	7.0J—8.5J	10	1279	49	
	225/40ZR18	92W XL	8.0J	7.5J—9.0J	10	1389	49	
	235/40ZR18	95W XL	8.5J	8.0J—9.5J	10	1521	49	
	245/40ZR18	97W XL	8.5J	8.0J—9.5J	10	1609	49	
	255/40ZR18	99W XL	9.0J	8.5J—10.0J	10	1709	49	
	275/40ZR18	103W XL	9.5J	9.0J—11.0J	10	1929	49	
	19	215/35ZR18	84W XL	7.5J	7.0J—8.5J	10	1102	49
		255/35ZR18	94W XL	9.0J	8.5J—10.0J	10	1477	49
265/35ZR18		97W XL	9.5J	9.0J—10.5J	10	1609	49	
275/35ZR18		99W XL	9.5J	9.0J—11.0J	10	1709	49	
225/55R19		99V	7.0J	6.0J—8.0J	10	1709	44	
235/55ZR19		101W	7.5J	6.5J—8.5J	11	1819	44	
255/55ZR19		111W XL	8.0J	7.0J—9.0J	11	2403	49	
275/55ZR19		111W	8.5J	7.5J—9.5J	11	2403	44	
235/50ZR19		103W XL	7.5J	6.5J—8.5J	10	1929	49	
255/50ZR19		107W XL	8.0J	7.0J—9.0J	11	2149	49	
265/50ZR19		110W XL	8.5J	7.5J—9.5J	11	2337	49	
225/45ZR19		96W XL	7.5J	7.0J—8.5J	10	1565	49	
235/45ZR19		99W XL	8.0J	7.5J—9.0J	10	1709	49	
245/45ZR19		102W XL	8.0J	7.5J—9.0J	10	1874	49	
255/45ZR19		104W XL	8.5J	8.0J—9.5J	10	1984	49	
225/40ZR19		93W XL	8.0J	7.5J—9.0J	10	1433	49	
235/40ZR19		96W XL	8.5J	8.0J—9.5J	10	1565	49	
245/40ZR19		98W XL	8.5J	8.0J—9.5J	10	1653	49	
255/40ZR19	100W XL	9.0J	8.5J—10.0J	10	1764	49		
275/40ZR19	105W XL	9.5J	9.0J—11.0J	10	2039	49		

RIM inch	SIZE	L.I./S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
19	225/35ZR19	88W XL	8.0J	7.5J—9.0J	10	1235	49
	235/35ZR19	91W XL	8.5J	8.0J—9.5J	10	1356	49
	245/35ZR19	93W XL	8.5J	8.0J—9.5J	10	1433	49
	255/35ZR19	96W XL	9.0J	8.5J—10.0J	10	1565	49
	265/35ZR19	98W XL	9.5J	9.0J—10.5J	10	1653	49
	275/35ZR19	100W XL	9.5J	9.0J—11.0J	10	1764	49
	255/30ZR19	91W XL	9.0J	8.5J—9.5J	10	1356	49
	265/30ZR19	93W XL	9.5J	9.0J—10.0J	10	1433	49
	275/30ZR19	96W XL	9.5J	9.0J—10.0J	10	1565	49
	295/30ZR19	100W XL	10.5J	10.0J—11.0J	10	1764	49
	305/30ZR19	102W XL	11.0J	10.5J—11.5J	10	1874	49
20	235/50ZR20	104W XL	7.5J	6.5J—8.5J	11	1984	49
	245/50R20	102V	7.5J	7.0J—8.5J	11	1874	44
	255/50ZR20	109W XL	8.0J	7.0J—9.0J	11	2271	49
	275/50ZR20	113W XL	8.5J	7.5J—9.5J	11	2535	49
	245/45ZR20	103W XL	8.0J	7.5J—9.0J	10	1929	49
	255/45ZR20	105W XL	8.5J	8.0J—9.5J	10	2039	49
	265/45ZR20	108W XL	9.0J	8.5J—10.0J	11	2205	49
	275/45ZR20	110W XL	9.0J	8.5J—10.5J	11	2337	49
	285/45ZR20	112W XL	9.5J	9.0J—10.5J	11	2469	49
	245/40ZR20	99W XL	8.5J	8.0J—9.5J	10	1709	49
	255/40ZR20	101W XL	9.0J	8.5J—10.0J	10	1819	49
	275/40ZR20	106W XL	9.5J	9.0J—11.0J	10	2094	49
	285/40ZR20	108W XL	10.0J	9.5J—11.0J	11	2205	49
	295/40ZR20	110W XL	10.5J	10.0J—11.5J	11	2337	49
	225/35ZR20	93W XL	8.0J	7.5J—9.0J	10	1433	49
	235/35ZR20	92W XL	8.5J	8.0J—9.5J	10	1389	49
	245/35ZR20	95W XL	8.5J	8.0J—9.5J	10	1521	49
	255/35ZR20	102W XL	9.0J	8.5J—10.0J	10	1874	49
	275/35ZR20	102W XL	9.5J	9.0J—11.0J	10	1874	49
	285/35ZR20	104W XL	10.0J	9.5J—11.0J	11	1984	49
	295/35ZR20	105W XL	10.5J	10.0J—11.5J	10	2039	49
	315/35ZR20	110W XL	11.0J	10.5J—12.5J	10	2337	49
	225/30ZR20	85W XL	8.0J	8.0J	10	1135	49
	235/30ZR20	88W XL	8.5J	8.5J	10	1235	49
	245/30ZR20	95W XL	8.5J	8.0J—9.0J	10	1521	49
	255/30ZR20	92W XL	9.0J	8.5J—9.5J	10	1389	49
	275/30ZR20	97W XL	9.5J	9.0J—10.0J	10	1609	49
295/30ZR20	101W XL	10.5J	10.0J—11.0J	10	1819	49	
305/30ZR20	103W XL	11.0J	10.5J—11.5J	10	1929	49	
21	275/50ZR21	113W XL	8.5J	7.5J—9.5J	11	2535	49
	265/45ZR21	104W	9.0J	8.5J—10.0J	11	1984	44
	275/45ZR21	110W XL	9.0J	8.5J—10.5J	11	2337	49
	245/40ZR21	100W XL	8.5J	8.0J—9.5J	11	1764	49
	255/40ZR21	102W XL	9.0J	8.5J—10.0J	11	1874	49
	265/40ZR21	105W XL	9.5J	9.0J—10.5J	11	2039	49
	275/40ZR21	107W XL	9.5J	9.0J—11.0J	11	2149	49
	285/40ZR21	109W XL	10.0J	9.5J—11.0J	11	2271	49
	295/40ZR21	111W XL	10.5J	10.0J—11.5J	11	2403	49
	245/35ZR21	96W XL	8.5J	8.0J—9.5J	11	1565	49
	255/35ZR21	98W XL	9.0J	8.5J—10.0J	11	1653	49
	265/35ZR21	101Y XL	9.5J	9.0J—10.5J	11	1819	49
	275/35ZR21	103W XL	9.5J	9.0J—11.0J	11	1929	49
	285/35ZR21	105W XL	10.0J	9.5J—11.0J	11	2039	49
	295/35ZR21	107W XL	10.5J	10.0J—11.5J	11	2149	49
	285/30ZR21	100W XL	10.0J	9.5J—10.5J	11	1764	49
	305/30ZR21	104Y XL	11.0J	10.5J—11.5J	11	1984	49
	315/30ZR21	105W XL	11.0J	10.5J—11.5J	11	2039	49
	22	285/45R22	114V XL	9.5J	9.0J—10.5J	11	2601
265/40ZR22		106W XL	9.5J	9.0J—10.5J	11	2094	49
275/40ZR22		107W XL	9.5J	9.0J—11.0J	11	2149	49
285/40ZR22		110W XL	10.0J	9.5J—11.0J	11	2337	49
265/35ZR22		102W XL	9.5J	9.0J—10.5J	11	1874	49
285/35ZR22		106W XL	10.0J	9.5J—11.0J	10	2094	49
265/30ZR22		97W XL	9.5J	9.0J—10.0J	11	1609	49



EX30RFT



Outstanding grip in
dry & wet
conditions



Asymmetric Ultra-
High Performance
tread pattern design



Advanced silica
compound



Computer optimized
pitch design to
reduce driving noise



4 longitudinal grooves
ensure effective water
drainage



EX 30RFT




RIM inch	SIZE	L.I/S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
16	205/55RF16	91V	6.5J	5.5J—7.5J	10	1356	44
17	225/55ZRF17	97W	7.0J	6.0J—8.0J	10	1609	44
	205/50ZRF17	89W	6.5J	5.5J—7.5J	10	1279	44
	225/50ZRF17	94W	7.0J	6.0J—8.0J	10	1477	44
	205/45RF17	84V	7.0J	6.5J—7.5J	10	1102	44
	225/45ZRF17	91W	7.5J	7.0J—8.5J	10	1356	44
18	225/45ZRF18	91W	7.5J	7.0J—8.5J	10	1356	44
	225/40ZRF18	88W	8.0J	7.5J—9.0J	10	1235	44
	245/40ZRF18	93W	8.5J	8.0J—9.5J	10	1433	44
	255/40ZRF18	95W	9.0J	8.5J—10.0J	10	1521	44
	275/40ZRF18	99W	9.5J	9.0J—11.0J	10	1709	44
	255/35ZRF18	90W	9.0J	8.5J—10.0J	10	1323	44
19	245/45ZRF19	98W	8.0J	7.5J—9.0J	10	1653	44
	225/40ZRF19	89W	8.0J	7.5J—9.0J	10	1279	44
	245/40ZRF19	94W	8.5J	8.0J—9.5J	10	1477	44
	275/40ZRF19	101W	9.5J	9.0J—11.0J	10	1819	44
	255/35ZRF19	92W	9.0J	8.5J—10.0J	10	1389	44
	275/35ZRF19	96W	9.5J	9.0J—11.0J	10	1565	44
20	245/40ZRF20	95W	8.5J	8.0J—9.5J	10	1521	44
	275/40ZRF20	102W	9.5J	9.0J—11.0J	11	1874	44
	275/35ZRF20	98W	9.5J	9.0J—11.0J	10	1653	44
	315/35ZRF20	106W	11.0J	10.5J—12.5J	10	2094	44



EX80




Asymmetric tread pattern designed for HP tires



Silica-reinforced tire tread compounds



Excellent performance in wet & dry handling



Anti-hydroplaning design with wide grooves in the contact patch help for water evacuation



EX 80



RIM inch	SIZE	L./S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
13	175/70R13	82T	5.0J	4.5J—6.0J	10	1047	44
14	175/70R14	84T	5.0J	4.5J—6.0J	10	1102	44
	185/70R14	88T	5.5J	4.5J—6.0J	10	1235	44
	195/70R14	91T	6.0J	5.0J—6.5J	10	1356	44
	175/65R14	82T	5.0J	5.0J—6.0J	10	1047	44
	185/65R14	86H	5.5J	5.0J—6.5J	10	1168	44
	165/60R14	75H	5.0J	4.5J—6.0J	10	853	44
	185/60R14	82H	5.5J	5.0J—6.5J	10	1047	44
	185/55R14	80H	6.0J	5.0J—6.5J	10	992	44
15	205/70R15	96H	6.0J	5.0J—7.0J	10	1565	44
	175/65R15	84H	5.0J	5.0J—6.0J	10	1102	44
	185/65R15	88H	5.5J	5.0J—6.5J	10	1235	44
	195/65R15	91V	6.0J	5.5J—7.0J	10	1356	44
	205/65R15	94V	6.0J	5.5J—7.5J	10	1477	44
	185/60R15	84H	5.5J	5.0J—6.5J	10	1102	44
	195/60R15	88V	6.0J	5.5J—7.0J	10	1235	44
	205/60R15	91V	6.0J	5.5J—7.5J	10	1356	44
16	205/65R16	95H	6.0J	5.5J—7.5J	10	1521	44
	215/65R16	98H	6.5J	6.0J—7.5J	10	1653	44
	195/60R16	89H	6.0J	5.5J—7.0J	10	1279	44
	205/60R16	92H	6.0J	5.5J—7.5J	10	1389	44
	215/60R16	95H	6.5J	6.0J—7.5J	10	1521	44
	225/60R16	98H	6.5J	6.0J—8.0J	10	1653	44
17	215/60R17	96V	6.5J	6.0J—7.5J	10	1565	44
	225/60R17	99V	6.5J	6.0J—8.0J	10	1709	44
	235/60R17	102H	7.0J	6.5J—8.5J	11	1874	44
18	225/60R18	104V XL	6.5J	6.0J—8.0J	11	1984	49
	235/60R18	107V XL	7.0J	6.5J—8.5J	11	2149	49



RC70



Silica-reinforced
tire tread
compounds



Solid continuous
center rib provides
better handling and
reduce irregular wear



Upgraded UHP casing offers
high-speed stability and
durability



Extra-wide footprint with
directional tread pattern
design



RC 70



RIM inch	SIZE	L.I/S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
20	285/30ZR20	99W XL	10.0J	9.5J—10.5J	11	1709	49
22	245/30ZR22	92W XL	8.5J	8.0J—9.0J	11	1389	49
	295/25ZR22	97W XL	10.5J	10.0J—11.0J	11	1609	49
28	295/25ZR28	103W XL	10.5J	10.0J—11.0J	11	1929	49
	325/35R28	120V XL	11.5J	11.0J—13.0J	11	3086	49
30	265/30ZR30	105W XL	9.5J	9.0J—10.0J	11	2039	49
	275/25ZR30	108W XL	10.0J	10.0J	11	2205	49



RC97



Silica-reinforced
tire tread
compounds



Reinforced
construction for
stability



Extra strong shoulder
block design
improves lateral grip



V-shaped tread
design with two wide
& deep grooves
provide excellent anti-
hydroplaning capability



RC 97



RIM inch	SIZE	L./S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
20	275/55R20	117H XL	8.5J	7.5J—9.5J	11	2833	49
	265/50R20	111V XL	8.5J	7.5J—9.5J	12	2403	49
	285/50R20	112V	9.0J	8.0J—10.0J	11	2469	44
22	285/45R22	114V XL	9.5J	9.0J—10.5J	12	2601	49
	305/45R22	118V XL	10.0J	9.5J—11.5J	11	2910	49
	265/40R22	106V XL	9.5J	9.0J—10.5J	12	2094	49
	305/40R22	114V XL	11.0J	10.0J—12.0J	12	2601	49
	265/35R22	102V XL	9.5J	9.0J—10.5J	11	1874	49
	225/30ZR22	87W XL	8.0J	8.0J	11	1202	49
	235/30ZR22	90W XL	8.5J	8.5J	11	1323	49
	255/30ZR22	95W XL	9.0J	8.5J—9.5J	11	1521	49
24	245/30ZR24	94W XL	8.5J	8.0J—9.0J	11	1477	49
	255/30ZR24	97W XL	9.0J	8.5J—9.5J	11	1609	49
	275/30ZR24	101W XL	9.5J	9.0J—10.0J	12	1819	49
	275/25ZR24	96W XL	10.0J	10.0J	12	1565	49
	295/35R24	110V XL	10.5J	10.0J—11.5J	12	2337	49
	305/35R24	112V XL	11.0J	10.0J—12.0J	11	2469	49
26	255/30ZR26	100W XL	9.0J	8.5J—9.5J	12	1764	49
	295/30ZR26	107W XL	10.5J	10.0J—11.0J	12	2149	49
	305/30ZR26	109W XL	11.0J	10.5J—11.5J	12	2271	49
	275/25ZR26	100W XL	10.0J	10.0J	12	1764	49



PRIXADO H/T



Optimized zigzag sipes promote wet traction for all-season drivability



Non-directional tread design with 5-rib for ride stability and reduce irregular wear



Wide-tread design offers extra contact patch



4 wide circumferential tread grooves provide excel water evacuation




PRIXADO H/T




RIM inch	SIZE	L.I/S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
16	215/70R16	100T	6.5J	5.5J—7.0J	12	1764	44
	225/70R16	103T	6.5J	6.0J—7.5J	12	1929	44
	LT225/75R16 E	115/112S	6.0J	6.0J—7.0J	15	2680/2470	80
	LT245/75R16 E	120/116S	7.0J	6.5J—8.0J	15	3085/2755	80
	LT265/75R16 E	123/120S	7.5J	7.0J—8.0J	16	3415/3085	80
17	LT235/80R17 E	120/117S	6.5J	6.0J—7.5J	15	3085/2835	80
	LT245/70R17 E	119/116S	7.0J	6.5J—8.0J	15	3000/2755	80
	LT265/70R17 E	121/118S	8.0J	7.0J—9.0J	16	3195/2910	80
18	265/70R18	116T	8.0J	7.0J—9.0J	13	2756	44



PRIXADO H/T⁺




Upgraded carcass construction to secure stability and durability



Computer optimized sipes provide excellent performance on wet and dry roads



5-rib tread design to against irregular wear



4 main grooves enable extra drainage




PRIXADO H/T +




RIM inch	SIZE	L.I./S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
16	235/75R15	109T XL	6.5J	6.0J—8.0J	11	2271	49
	LT225/75R16 E	115/112S	6.0J	6.0J—7.0J	12	2680/2470	80
	LT245/75R16 E	120/116S	7.0J	6.5J—8.0J	12	3085/2755	80
	235/70R16	106T	7.0J	6.0J—8.0J	11	2094	44
	245/70R16	111T XL	7.0J	6.5J—8.0J	11	2403	49
	255/70R16	111T	7.5J	6.5J—8.5J	11	2403	44
	265/70R16	112T	8.0J	7.0J—9.0J	11	2469	44
	275/70R16	114T	8.0J	7.0J—9.0J	11	2601	44
	215/65R16	98H	6.5J	6.0J—7.5J	11	1653	44
	235/60R16	100H	7.0J	6.5J—8.5J	11	1764	44
17	245/70R17	110T	7.0J	6.5J—8.0J	11	2337	44
	265/70R17	115T	8.0J	7.0J—9.0J	11	2679	44
	225/65R17	102T	6.5J	6.0J—8.0J	11	1874	44
	235/65R17	108H XL	7.0J	6.5J—8.5J	11	2205	49
	245/65R17	111T XL	7.0J	7.0J—8.5J	11	2403	49
	265/65R17	112T	8.0J	7.5J—9.5J	11	2469	44
	285/65R17	116H	8.5J	8.0J—10.0J	11	2756	44
	225/60R17	99H	6.5J	6.0J—8.0J	11	1709	44
	255/60R17	106H	7.5J	7.0J—9.0J	11	2094	44
18	255/70R18	113T	7.5J	6.5J—8.5J	11	2535	44
	235/65R18	106H	7.0J	6.5J—8.5J	11	2094	44
	265/65R18	114T	8.0J	7.5J—9.5J	11	2601	44
	275/65R18	116T	8.0J	7.5J—9.5J	11	2756	44
	225/60R18	104V XL	6.5J	6.0J—8.0J	11	1984	49
	235/60R18	107V XL	7.0J	6.5J—8.5J	11	2149	49
	245/60R18	105H	7.0J	7.0J—8.5J	11	2039	44
	265/60R18	110H	8.0J	7.5J—9.5J	11	2337	44
	285/60R18	116H	8.5J	8.0J—10.0J	11	2756	44
	255/55R18	109V XL	8.0J	7.0J—9.0J	11	2271	49
19	245/55R19	103V	7.5J	7.0J—8.5J	11	1929	44
	255/60R19	109H	7.5J	7.0J—9.0J	11	2271	44
20	275/60R20	115H	8.0J	7.5J—9.5J	11	2679	44
	235/55R20	102V	7.5J	6.5J—8.5J	11	1874	44
	255/55R20	110V XL	8.0J	7.0J—9.0J	11	2337	49
	275/55R20	117H XL	8.5J	7.5J—9.5J	11	2833	49
	285/50R20	116V XL	9.0J	8.0J—10.0J	11	2756	49




PRIXADO A/T



Aggressive tread design offers outstanding All-Terrain traction



Strong carcass construction design improves handling for on/off road driving



Proven cut-resistant rubber compound applied



Excellent highway performance



PRIXADO A/T




RIM inch	SIZE	L./S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
14	LT215/75R14 D	104/101S	6.0J	5.5J—7.0J	14	1985/1820	65
15	LT215/75R15 D	106/103S	6.0J	5.5J—7.0J	14	2095/1930	65
	235/75R15	105T	6.5J	6.0J—8.0J	12	2039	44
	265/70R15	112T	8.0J	7.0J—9.0J	12	2469	44
	31X10.5R15LT C	109S	8.5J	7.0J—9.0J	14	2270	50
16	215/70R16 (OWL)	100T	6.5J	5.5J—7.0J	11	1764	44
	225/70R16 (OWL)	103T	6.5J	6.0J—7.5J	11	1929	44
	235/70R16	106T	7.0J	6.0J—8.0J	12	2094	44
	245/70R16	111T XL	7.0J	6.5J—8.0J	12	2403	49
	255/70R16	111T	7.5J	6.5J—8.5J	12	2403	44
	265/70R16	112T	8.0J	7.0J—9.0J	12	2469	44
	205/60R16	92H	6.0J	5.5J—7.5J	11	1389	44
	LT215/85R16 D	110/107Q	6.0J	5.5J—7.0J	14	2335/2150	65
	LT225/75R16 E	115/112S	6.0J	6.0J—7.0J	14	2680/2470	80
	LT245/75R16 E	120/116S	7.0J	6.5J—8.0J	16	3085/2755	80
17	225/70R17	108T XL	6.5J	6.0J—7.5J	11	2205	49
	265/70R17	115T	8.0J	7.0J—9.0J	12	2679	44
	LT275/70R17 E	121/118S	8.0J	7.0J—8.5J	16	3195/2910	80
	245/65R17	111T XL	7.0J	7.0J—8.5J	12	2403	49
	265/65R17	112T	8.0J	7.5J—9.5J	12	2469	44
	275/65R17	115T	8.0J	7.5J—9.5J	12	2679	44
18	LT275/70R18 E	125/122S	8.0J	7.0J—8.5J	16	3640/3305	80
	LT285/65R18 E	125/122S	8.5J	8.0J—10.0J	16	3640/3305	80
	265/60R18	110H	8.0J	7.5J—9.5J	12	2337	44
19	255/55R19	111V XL	8.0J	7.0J—9.0J	12	2403	49
20	275/55R20	117H XL	8.5J	7.5J—9.5J	12	2833	49
	265/50R20	111V XL	8.5J	7.5J—9.5J	12	2403	49
	285/50R20	116V XL	9.0J	8.0J—10.0J	12	2756	49



PRIXADO R/T




Aggressive rubber block & sidewall design contributes to off road performance




Optimized sipes on blocks provide outstanding wet handling

Proven cut & chipping-resistant tread compound



Strong carcass construction design improves handling for on/off road driving



Stone ejector on shoulder groves to prevent damage




PRIXADO R/T




RIM inch	SIZE	L./S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
15	31X10.50R15LT	109Q	8.5J	7.0J—9.0J	16	2270	50
	33X12.50R15LT	108Q	10.0J	8.0J—10.5J	16	2205	35
16	235/70R16	109T XL	7.0J	6.0J—8.0J	14	2271	49
	LT225/75R16	115/112R	6.0J	6.0J—7.5J	14	2680/2470	80
	LT245/75R16	120/116R	7.0J	6.5J—8.0J	16	3042/2755	80
	LT265/75R16	123/120R	7.5J	7.0J—9.0J	16	3415/3085	80
	LT285/75R16	126/123R	8.0J	7.5J—9.0J	16	3750/3415	80
17	LT245/75R17	121/118R	7.0J	6.5J—8.0J	16	3195/2910	80
	LT265/70R17	121/118R	8.0J	7.0J—9.0J	16	3195/2910	80
	LT285/70R17	121/118R	8.5J	7.5J—9.5J	16	3195/2910	80
	265/65R17	112T	8.0J	7.5J—9.5J	14	2469	44
	33X12.50R17LT	120Q	10.0J	8.5J—11.0J	16	3085	65
18	33X12.50R18LT	118Q	10.0J	8.5J—11.0J	16	2910	65
	265/60R18	110T	8.0J	7.5J—9.5J	14	2337	44
20	275/55R20	117T XL	8.5J	7.5J—9.5J	14	2833	49
	LT285/55R20	122/119R	9.0J	8.5J—10.0J	16	3305/3000	80
	265/50R20	111T XL	8.5J	7.5J—9.5J	14	2403	49
	285/50R20	116T XL	9.0J	8.0J—10.0J	14	2756	49
	33X12.50R20LT	114Q	10.0J	8.5J—11.0J	16	2600	65
	35X12.50R20LT	121Q	10.0J	8.5J—11.0J	16	3195	65
22	LT285/55R22	124/121R	9.0J	8.5J—10.0J	16	3525/3195	80
	33X12.50R22LT	109Q	10.0J	8.5J—11.0J	16	2270	65
24	33X12.50R24LT	101Q	11.5J	10.5J—12.5J	16	1820	65




MT ONE




Aggressive rubber block design for extreme off road conditions



Proven off-road rubber compound for anti-cut / tear/ puncture



Heavy-duty construction improves tire durability



Stone ejector on grooves to prevent damage



MT ONE



RIM inch	SIZE	L.I./S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
15	LT235/75R15 C	104/101S	6.5J	6.0J—8.0J	16	1985/1820	50
	30X9.50R15LT C	104Q	7.5J	6.5J—8.5J	16	1985	50
	31X10.50R15LT C	109Q	8.5J	7.0J—9.0J	16	2270	50
	32X11.50R15LT C	113Q	9.0J	8.0J—10.0J	16	2535	50
	33X12.50R15LT C	108Q	10.0J	8.0J—10.5J	16	2205	35
16	LT245/75R16 C	108/104Q	7.0J	6.5J—8.0J	16	2205/1985	50
	LT265/75R16 E	123/120Q	7.5J	7.0J—9.0J	16	3415/3085	80
	LT285/75R16 E	126/123R	8.0J	7.5J—9.0J	16	3750/3415	80
	LT265/70R16 D	117/114Q	8.0J	7.0J—9.0J	16	2835/2600	65
17	LT265/70R17 E	121/118Q	8.0J	7.0J—9.0J	19	3195/2910	80
	LT285/70R17 E	121/118R	8.5J	7.5J—9.5J	19	3195/2910	80
	LT295/70R17 E	121/118Q	8.5J	7.5J—10.0J	19	3195/2910	80
	LT265/65R17 D	116/113Q	8.0J	7.5J—9.5J	19	2755/2535	65
	35X12.50R17LT	121Q	10.0J	8.5J—11.0J	21	3195	65
18	LT285/65R18 E	125/122Q	8.5J	8.0J—10.0J	19	3640/3305	80
	33X12.50R18LT	118Q	10.0J	8.5J—11.0J	21	2910	65
	35X12.50R18LT	123Q	10.0J	8.5J—11.0J	21	3415	65
20	LT275/65R20 E	126/123Q	8.0J	8.0J—9.5J	19	3750/3415	80
	33X12.50R20LT	114Q	10.0J	8.5J—11.0J	21	2600	65
	35X12.50R20LT	121Q	10.0J	8.5J—11.0J	21	3195	65
22	33X12.50R22LT	109Q	10.0J	8.5J—11.0J	21	2270	65
	35X12.50R22LT	117Q	10.0J	8.5J—11.0J	21	2835	65



EX50



Two-in-one shoulder design improves lateral grip



Non-directional, 4-rib tread design optimizes ride stability and reduce irregular wear



Reinforced construction for heavy duty light trucks



Excellent performance in wet & dry handling



EX 50



FUEL

WEAR

MILEAGE

RIM inch	SIZE	L.I./S.S	STD RIM inch	Approved Rim inch	Tread Depth 32nds	Max Load lbs	Max Infl. Pressure psi
14	*175/65R14C	90/88T	5.0J	5.0J—5.5J	11	1323/1235	54
	*185R14C	102/100R	5.5J	5.0J—6.0J	11	1874/1764	54
	*195R14C	106/104R	5.5J	5.0J—6.0J	11	2094/1984	65
	*205R14C	109/107R	6.0J	5.5J—6.5J	11	2271/2149	65
15	*195R15C	107/105N	5.5J	5.0J—6.0J	11	2149/2039	65
	*195/70R15C	104/102R	6.0J	5.0J—6.0J	11	1984/1874	65
	*205/70R15C	106/104R	6.0J	5.5J—6.5J	11	2094/1984	65
	*215/70R15C	109/107R	6.5J	5.5J—7.0J	11	2271/2149	65
	*225/70R15C	112/110R	6.5J	6.0J—7.0J	11	2469/2337	65
	*205/65R15C	102/100T	6.0J	5.5J—6.5J	11	1874/1764	54
	*215/65R15C	104/102R	6.5J	6.0J—7.0J	11	1984/1874	54
16	*185/75R16C	104/102R	5.0J	5.0J—6.0J	11	1984/1874	69
	*195/75R16C	107/105R	5.5J	5.0J—6.0J	11	2149/2039	69
	*215/75R16C	116/114R	6.0J	5.5J—7.0J	11	2756/2601	76
	*225/75R16C	121/120R	6.0J	6.0J—7.0J	11	3197/3086	83
	*215/70R16C	108/106T	6.5J	5.5J—7.0J	11	2205/2094	54
	*195/65R16C	104/102T	6.0J	5.5J—6.0J	11	1984/1874	69
	*205/65R16C	107/105T	6.0J	5.5J—6.5J	11	2149/2039	69
	*215/65R16C	109/107R	6.5J	6.0J—7.0J	11	2271/2149	69
	*225/65R16C	112/110R	6.5J	6.0J—7.0J	11	2469/2337	69
	235/65R16C	118/116R	7.0J	6.5J—7.5J	11	3195/2755	76

ROADCLAW
TIRES

Tire Direct
La nueva generación



TIRE DIRECT



/TIRE_DIRECT



/TIREDIRECTMX



TIRE DIRECT