

ZIMMATIC

TRUCK & BUS TYRES



ZLS6+

POSITION



- Four vertically continuous grooves provide precise handling performance.
- Excellent anti-skid performance, excellent high-speed performance.
- New shoulder wedge formula design supplies better shoulder heat dispersion performance.

Size	PR	Load Index	Speed Rating	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	RIM	Max Load Single/ Dual (kgs)	Inflation Pressure (Kpa)
11R22.5	16	146/143	M	15	1054	279	8.25	3000/2725	830
11R24.5	16	149/146	M	15	1104	279	8.25	3250/3000	830



ZMD8

POSITION



- Wide groove design supplies excellent traction and braking performance.
- Deep tread depth supplies good groove bottom protection and improves penetrate resistance.
- Special tread design effectively improves self-cleaning performance.

Size	PR	Load Index	Speed Rating	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	RIM	Max Load Single/ Dual (kgs)	Inflation Pressure (Kpa)
11R22.5	16	146/143	M	20.5	1054	279	8.25	3000/2725	830
11R24.5	16	149/146	M	20.5	1104	279	8.25	3250/3000	830



ZMA1

POSITION



- The large and deep grooves on the shoulders aim to increase the driving performance.
- Three main longitudinal grooves provide good directional stability and reduce irregular wear and are adapted to various conditions.
- Wider running surface and the puncture resistance formula reduce abrasion.

Size	PR	Load Index	Speed Rating	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	RIM	Max Load Single/ Dual (kgs)	Inflation Pressure (Kpa)
11R22.5	16	146/143	K	15	1054	279	8.25	3000/2725	830



Tire Direct
La nueva generación



TIRE DIRECT



/TIRE_DIRECT



/TIREDIRECTMX



TIRE DIRECT